



CITY OF FOUNTAIN VALLEY

www.fountainvalley.org

10200 SLATER AVENUE • FOUNTAIN VALLEY, CA 92708-4736 • (714) 593-4400, FAX: (714) 593-4498

February 3, 2010

Mr. Simon Eching
California Department of Water Resources
Water Use and Efficiency Branch
P.O. Box 942836
Sacramento, CA 94236-0001

RE: Landscape Ordinance Notification and Documents per requirements of the
Water Conservation in Landscaping Act of 2006 (AB 1881)

Dear Mr. Eching,

Please find enclosed a copy of Ordinance No. 1440 revising the City of Fountain Valley's Landscape Code as well as Resolution No. 9235 adopting guidelines for the city's water conservation in landscaping provisions. Both were approved in December 2009 before the January 1, 2010 deadline.

If you should have any questions or comments regarding this matter, I can be reached at (714) 593-4431. Thank you.

Sincerely,

City of Fountain Valley

Steven Ayers
Planner

Encl. Ordinance 1440
Resolution No. 9235

ORDINANCE NO. _____

**AN ORDINANCE OF THE CITY COUNCIL OF THE CITY OF
FOUNTAIN VALLEY REPEALING AND REENACTING
CHAPTER 21.20 OF THE FOUNTAIN VALLEY MUNICIPAL
CODE PERTAINING TO LANDSCAPING**

WHEREAS, the State Legislature has enacted the Water Conservation in Landscaping Act (A.B. 1881) which is set forth at Government Code Section 65591 *et seq.* (Article 10.7 Water Conservation in Landscaping); and

WHEREAS, said legislation was adopted after the Legislature made findings about the importance of water and water conservation to California's economy and which determined that landscaping design, installation, maintenance and management should be water efficient; and

WHEREAS, the City Council does also adopt those findings as set forth in Government Code Section 65993; and

WHEREAS, said legislation required that the State adopt a model water efficiency ordinance and that all local agencies adopt said ordinance or a similar ordinance by January 1, 2010; and

WHEREAS, the state model ordinance is quite lengthy and contains many technical provisions that are inappropriate for a codified ordinance; and

WHEREAS, the Municipal Water District of Orange County (MWDOC) and the Orange County Council of Governments (OCCOG) has met with stakeholders and developed a more user-friendly ordinance which adopts the more technical requirements in a Guideline publication; and

WHEREAS, the City Council does hereby further find that:

- (1) Orange County has an established, large reclaimed water infrastructure system;
- (2) Allocation-based and tiered water rate structures allow public agencies to document water use in landscapes;
- (3) Incentive-based water use efficiency programs have been actively implemented within Orange County since before 1991;
- (4) Current local design practices in new landscapes typically achieve the State Model Water Efficient Landscape Ordinance water use goals;
- (5) All water services within the City are metered;
- (6) Orange County is a leader in researching and promoting the use of smart automatic irrigation controllers with more than 4,500 installations as of June 2009;
- (7) All new irrigation controllers sold after 2012 within Orange County will be smart controllers;
- (8) Landscape plan submittal and review has been a long-standing practice in Fountain Valley;
- (9) The average rainfall in Orange County is approximately 12 inches per year;
- (10) The City, as the local water purveyor, is implementing enforcement of water waste prohibitions for all existing metered landscaped areas within its jurisdiction; and

WHEREAS, consistent with these findings, the purpose of the City's water efficient landscape ordinance is to establish an alternative model acceptable under AB 1881 as

being at least as effective as the State Model Water Efficient Landscape Ordinance in the context of conditions in the City in order to:

- (1) promote the benefits of consistent landscape ordinances with neighboring local and regional agencies;
- (2) promote the values and benefits of landscapes while recognizing the need to invest water and other resources as efficiently as possible;
- (3) establish a structure for planning, designing, installing, and maintaining and managing water efficient landscapes in new construction and rehabilitated projects;
- (4) establish provisions for water management practices and water waste prevention for existing landscapes;
- (5) use water efficiently without waste by setting a Maximum Applied Water Allowance as an upper limit for water use and reduce water use to the lowest practical amount;
- (6) encourage the use of economic incentives that promote the efficient use of water, such as implementing a budget-based tiered-rate structure; and

WHEREAS, the OCCOG recommends, and the City Council does hereby agree, that the OCCOG ordinance is the better regulation and meets the requirements of the law while being user friendly, especially in allowing self-certification, and will provide consistency throughout Orange County; and

WHEREAS, the City Council does further state its intention to adopt the OCCOG Guidelines by resolution and to integrate that document into this ordinance;

NOW, THEREFORE, THE CITY COUNCIL OF THE CITY OF FOUNTAIN VALLEY
DOES HEREBY ORDAIN AS FOLLOWS:

Section 1. That Chapter 21.20 of the Fountain Valley Municipal Code is hereby repealed in its entirety:

Section 2. That Chapter 21.20 of the Fountain Valley Municipal Code is hereby reenacted to read as follows:

"Chapter 21.20

: Landscaping

21.20.010 Purpose. It is the purpose of this chapter to establish landscape standards to mitigate the effects of urbanization on the environment and to provide for an aesthetically pleasing urban setting. The city recognizes the importance of landscaping to the health, well-being, and quality of life of the community and desires to enhance the overall appearance of development projects in the city. It is the intent of this chapter to establish a measure of uniformity in landscaping for new projects as well as provide a mechanism to require upgrading of existing landscaping in existing developments when improvements are proposed. It is also the intent of this chapter to encourage optimum use of drought-tolerant plant materials in conjunction with water-conserving automatic irrigation systems and to allow synthetic turf meeting the standards set forth herein to further assist water conservation. In adopting this Chapter, the City is complying with the Water Conservation in Landscaping Act, Government Code Section 65590 *et seq.*

21.20.020 Applicability. All nonresidential, multi-family residential projects, single-family residential subdivisions and single-family properties shall provide landscaping in compliance with the requirements of this chapter.

21.20.030 Definitions.

"Hydro-zone" means a portion of the landscaped area having plants with similar water needs that are served by a valve or set of valves with the same schedule, unless a naturalized hydrozone or synthetic turf is used. A hydro-zone may be irrigated or non-irrigated. For example, a naturalized area planted with native vegetation that will not need supplemental irrigation once established is a non-irrigated hydro-zone.

"Landscaped area." All planting areas, turf areas, and water features in a landscape design plan subject to the Maximum Applied Water Allowance and Estimated Applied Water Use calculations. The landscaped area does not include footprints of buildings or structures, sidewalks, driveways, parking lots, decks, patios, gravel or stone walks, other pervious or nonpervious hardscapes, and other non-irrigated areas designated for non-development (e.g., open spaces and existing native vegetations).

"Landscaping." The planting and continuous maintenance of some combination of natural vegetation (e.g., trees, shrubs, vines, ground covers, flowers on lawns). In addition to plant life, landscaping may also include synthetic turf, as defined herein, a limited amount of stones, benches, ponds, and statuary.

"Recreational area." Areas of active play or recreation (e.g., sports fields, schoolyards, picnic grounds) or other areas with intense foot traffic.

"Synthetic turf." Man-made, synthetic material manufactured from nylon, polypropylene, polyethylene, or a blend of nylon, polypropylene and polyethylene fibers

which simulates the appearance of live turf, organic turf, grass, sod, or lawn, and meets the requirements of Section 21.20.070.

"Turf." A single-bladed grass or sod.

21.20.040 Landscape area requirements.

(a) Nonresidential and Multi-family Uses. Each land use, except single-family, shall provide and maintain fifteen percent of the site in landscaped areas. The landscape area requirement may include setback areas and other unused areas of the site that are not intended for future use. Parking lot landscaping shall not be counted towards meeting this requirement.

(b) Single-family Subdivisions. All areas between the front of the residence and the front property line shall be landscaped within six months of issuance of the certificate of occupancy or three months from recorded sale (date of recording) whichever is earlier. Landscaped areas shall be planted with live plant materials or synthetic turf meeting the criteria provided in Section 21.20.070, for a minimum of fifty percent of the subject area. If installed by the developer, landscape plans shall be in compliance with Section 21.20.050(a) (Landscape standards). If installed by the individual homeowner, landscape plans do not require city approval.

(c) Unused Areas. All areas of a project site not intended for a specific use, including pad sites in shopping centers held for future development, shall be landscaped unless it is determined by the director that landscaping is not necessary to fulfill the purposes of this chapter.

(d) Parking Areas.

(1) Perimeter Parking Lot Landscaping.

(A) **Adjacent to Streets:** Parking areas adjoining a public street shall be designed to provide a landscaped planting strip between the street right-of-way and parking area a minimum fifteen feet in width. The planting strip shall include a landscaped berm a minimum of three feet in height. The perimeter planting strip shall not be included within the interior parking lot landscaping calculations.

(B) **Adjacent to Residential Use.** Parking areas for nonresidential uses adjoining residential uses shall provide a solid masonry wall and landscaped buffer yard a minimum of ten feet in width between the parking area and the common property line bordering the residential use. For each one hundred lineal feet of landscaped buffer yard, a minimum of six trees shall be provided.

(2) **Interior Parking Lot Landscaping.**

(A) **Amount of Landscaping.** For off-street parking areas with ten or more spaces, a minimum of fifteen percent of the total off-street parking area shall be landscaped with at least one tree for each ten parking stalls and appropriate shrubs and ground cover. Setback areas required to be landscaped by other subsections of this chapter shall not be considered part of the required parking lot landscaping.

(B) **Planters Required.** Trees shall be in planters located throughout the parking area. In order to be considered within the parking area, trees shall be located in planters that are bounded on at least three sides by parking area paving. Planters shall have a minimum interior dimension of five feet. All ends of parking lanes shall have landscaped islands.

(C) Larger Projects. Parking lots with more than one hundred spaces shall provide a concentration of landscape elements at primary entrances, including specimen trees, flowering plants, enhanced paving, and project identification.

(e) All new landscaped areas, after January 1, 2010, shall be installed in compliance with Section 21.20.050(c).

21.20.050 Landscape standards.

(a) General Requirements.

(1) Landscape Plan. A comprehensive landscape and irrigation plan prepared and signed by a California licensed landscape contractor or landscape architect shall be submitted for review and approval when required by the department. Landscape materials, trees, shrubs, groundcover, turf, synthetic turf and other vegetation, and planting symbols shall be clearly drawn and plants labeled by botanical name, common name, container size, spacing and quantities of each group of plants indicated.

(2) Minimum Width. Landscaped areas that may be counted toward required landscaping shall have a minimum width of three feet, exclusive of curb or wall.

(3) Concrete Curb Required. Landscaping shall be protected with a minimum six-inch high concrete curb.

(4) Maintenance Required. Landscaping shall be continuously maintained free of weeds, debris, litter or temporary signage.

(5) Irrigation Required. All landscaped areas (except naturalized hydro-zones) shall be provided with an automatic irrigation system as provided in Section 21.20.050(c) unless synthetic turf is used.

(6) Limitation on Turf Area. The percentage of turf or synthetic turf for nonresidential projects shall not exceed forty-five percent of the required landscaping area and multi-family residential development shall not exceed seventy-five percent of the required landscaping area.

(b) Planting material.

(1) Trees.

(A) Trees shall not be planted under any eave, overhang, or balcony.

(B) Trees shall be staked in compliance with city standards.

(C) The minimum interior width of planters containing trees shall be three feet exclusive of curbs. Areas provided with twenty-four inch box trees or larger shall have planters with a minimum interior width of four feet exclusive of curbs.

(D) Trees in landscape planters less than ten feet in width or located closer than five feet from a permanent structure shall be provided with root barriers.

(2) Groundcover and Shrubs.

(A) All areas required to be landscaped shall be covered with non-deciduous groundcover, shrubs, turf, or other types of plants that are predominantly drought-tolerant.

(B) A minimum of two five-gallon size shrubs shall be provided for every six feet of distance along street setbacks.

(C) Artificial groundcover or shrubs shall not be allowed except for synthetic turf meeting the standards of Section 21.20.070.

(D) Crushed rock, redwood chips, pebbles, stone, and similar materials shall be allowed up to fifteen percent of the total required landscape area.

(c) Water Efficient Landscape Provisions.

(1) Beginning January 1, 2010, all planting, irrigation, and landscape-related improvements required by these water efficient landscape provisions shall apply to the following landscape projects:

(A) new landscape installations or landscape rehabilitation projects by public agencies or private non-residential developers, except for cemeteries, with a landscaped area, including pools or other water features but excluding hardscape, equal to or greater than 2,500 square feet, and which are otherwise subject to a discretionary approval of a landscape plan, or which otherwise require a ministerial permit for a landscape or water features;

(B) new landscape installations or landscape rehabilitation projects by developers or property managers of single-family and multi-family residential projects or complexes with a landscaped area, including pools or other water features but excluding hardscape, equal to or greater than 2,500 square feet, and which are otherwise subject to a discretionary approval of a landscape plan, or which otherwise require a ministerial permit for a landscape or water feature;

(C) new landscape installation projects by individual homeowners on single-family or multi-family residential lots with a total project landscaped area, including pools or other water features but excluding hardscape, equal to or greater than 5,000 square feet, and which are otherwise subject to a discretionary approval of a landscape plan, or which otherwise require a ministerial permit for a landscape or water feature;

(2) Section 5(B) of the Landscape Water Use Standards of this Water Efficient Landscape Ordinance shall apply to:

(A) all landscaped areas, whether installed prior to or after January 1, 2010;
and

(B) all landscaped areas installed after January 1, 2010, to which these water efficient landscape provisions apply as required by Subsection (c).

(3) This Water Efficient Landscape Ordinance does not apply to:

(A) registered local, state, or federal historical sites;

(B) ecological restoration projects that do not require a permanent irrigation system;

(C) mined-land reclamation projects that do not require a permanent irrigation system; or

(D) plant collections, as part of botanical gardens and arboretums open to the public.

(4) Implementation Procedures shall be as follows:

(A) Prior to installation, a Landscape Documentation Package shall be submitted to the City for review and approval of all landscape projects subject to the provisions of this Water Efficient Landscape Ordinance. Any Landscape Documentation Package submitted to the City shall comply with the provisions of the Guidelines adopted by separate resolution.

(B) The Landscape Documentation Package shall include a certification by a professional appropriately licensed in the State of California stating that the landscape design and water use calculations have been prepared by or under the supervision of the licensed professional and are certified to be in compliance with the provisions of this Chapter 21.20 and the Guidelines.

(i) Landscape and irrigation plans shall be submitted to the City for review and approval with appropriate water use calculations.

(ii) Water use calculations shall be consistent with calculations contained in the Guidelines and shall be provided to the local water purveyor, as appropriate, under procedures determined by the City.

(iii) Verification of compliance of the landscape installation with the approved plans shall be obtained through a Certification of Completion in conjunction with a Certificate of Use and Occupancy or Permit Final process; as provided in the Guidelines.

(5) Landscape Water Use Standards.

(A) For applicable landscape installation or rehabilitation projects subject to Subsection (c) above, the Estimated Applied Water Use allowed for the landscaped area shall not exceed the maximum allowed water allowance calculated using an evapotranspiration adjustment factor of 0.7, except for special landscaped areas where the maximum allowed water allowance is calculated using an evapotranspiration adjustment factor of 1.0; or the design of the landscaped area shall otherwise be shown to be equivalently water-efficient in a manner acceptable to the City; as provided in the Guidelines.

(B) Irrigation of all landscaped areas shall be conducted in a manner conforming to the rules and requirements, and shall be subject to penalties and incentives for water conservation and water waste prevention as determined and implemented by the local water purveyor or as mutually agreed by local water purveyor and the local agency.

(6) Delegation.

The City may delegate to, or into a contract with, a local agency to implement, administer, and/or enforce any of the provisions of the Water Efficient Landscape Ordinance on behalf of the City.

21.20.060 Maintenance. Landscaping shall be properly maintained at all times.

(1) Irrigation equipment shall be in continuously maintained in good working condition and to avoid overspray.

(2) Litter shall be removed from all landscaped areas in a timely fashion.

(3) Turf areas shall be mowed on a regular basis and be kept green.

Accumulation of leaves, twigs, bark, and other similar materials shall be removed on a regular basis. Planting areas shall be kept in a weed-free fashion at all times. Synthetic turf shall be maintained so as to replicate live turf and shall be replaced when worn.

(4) Landscaping maintenance shall include pruning, cultivating, weeding, fertilizing, replacement of plants, and watering on a regular basis.

(5) Landscape maintenance shall include the removal of dead, decayed, diseased, or hazardous trees, weeds and debris constituting unsightly appearance, dangerous to public safety and welfare or detrimental to neighboring properties or property values. Compliance shall be by removal, replacement, or maintenance.

(6) All landscaping (trees, shrubs, ground cover, turf, etc.) which, due to accident, damage, disease, lack of maintenance, or other cause, fail to show a healthy appearance and growth, shall be replaced. Replacement plants shall conform to all standards that govern the original planting installation, approved landscaping plan, or as approved by the Director of Planning.

21.20.070 Synthetic turf standards.

(a) The use of synthetic turf, as defined in Section 21.20.030, shall be permitted as follows:

(1) **Materials.** Synthetic turf shall be of a type known as cut pile and shall be manufactured from nylon, polypropylene, or polyethylene or a blend thereof, stitched onto a mesh or hole-punched backing. An eight year minimum no-fade product warranty shall be required as well.

(2) **Installation.** Synthetic turf shall be installed by a licensed contractor, pursuant to manufacturer specifications and shall be anchored at all edges and seams. A proper drainage system must be installed to prevent excessive run-off or pooling. Synthetic turf shall be separated from flower beds by a bender board or similar material, to prevent the intrusion of living plants into the artificial turf.

21.20.080 Violations of landscaping standards. It is unlawful for any owner, operator, tenant or other person in control of property within the city for which the standards set forth in this chapter apply, to fail to install or maintain landscaping or the landscape plan as required by this chapter.”

Section 3. If any section, subsection, sentence, clause or phrase of this ordinance is for any reason held to be invalid or unconstitutional by a decision of any court of competent jurisdiction, such decision shall not affect the validity of the remaining portions of the ordinance. The City Council declares that it would have passed this ordinance and each and every section, subsection, sentence, clause or phrase not declared invalid or unconstitutional without regard to whether any portion of the ordinance would be subsequently declared invalid or unconstitutional.

Section 4. The City Clerk shall certify to the adoption of this Ordinance and cause it to be published as required by law.

PASSED AND ADOPTED by the City Council of the City of Fountain Valley at a regular adjourned meeting this 15th day of December, 2009.

ATTEST:

Kathleen Heard

Kathleen Heard
Deputy City Clerk

Larry R. Crandall

Larry Crandall
Mayor

APPROVED AS TO FORM:

Alan Burns

Alan Burns
City Attorney

VOTE

STATE OF CALIFORNIA }
COUNTY OF ORANGE } ss.
CITY OF FOUNTAIN VALLEY }

I, Kathleen Heard, Deputy City Clerk of the City of Fountain Valley, do hereby certify that the foregoing Ordinance was introduced to the Council at its regular meeting held on the 1st day of December 2009, and was adopted at its regular meeting held on the 15th of December 2009, by the Council by the following roll call vote, to wit:

AYES: Council Members: Nagel, Crandall, Collins, Brothers, Carrozzo
NAYES: Council Members: None
ABSTAIN: Council Members: None


Kathleen Heard
Deputy City Clerk

AFFIDAVIT

STATE OF CALIFORNIA }
COUNTY OF ORANGE } ss.
CITY OF FOUNTAIN VALLEY }

I, Kathleen Heard, Deputy City Clerk of the City of Fountain Valley, California, do hereby certify that I did cause the foregoing ordinance to be posted and published in an adjudicated paper of general circulation pursuant to law.

WITNESS my hand and seal this 15th day of December 2009.


Kathleen Heard
Deputy City Clerk

RESOLUTION NO. 9235

**A RESOLUTION OF THE CITY COUNCIL OF THE CITY OF
FOUNTAIN VALLEY ADOPTING GUIDELINES FOR THE
CITY'S WATER CONSERVATION IN LANDSCAPING
PROVISIONS**

WHEREAS, the State Legislature has enacted the Water Conservation in Landscaping Act (A.B. 1881) which is set forth at Government Code Section 65591 *et seq.* (Article 10.7 Water Conservation in Landscaping); and

WHEREAS, said legislation was adopted after the Legislature made findings about the importance of water and water conservation to California's economy and which determined that landscaping design, installation, maintenance and management should be water efficient; and

WHEREAS, the City Council does also adopt those findings as set forth in Government Code Section 65993; and

WHEREAS, said legislation required that the State adopt a model water efficiency ordinance and that all local agencies adopt said ordinance or a similar ordinance by January 1, 2010; and

WHEREAS, the state model ordinance is quite lengthy and contains many technical provisions that are inappropriate for a codified ordinance; and

WHEREAS, the Municipal Water District of Orange County (MWDOC) and the Orange County Council of Governments (OCCOG) has met with stakeholders and developed a more user-friendly ordinance which adopts the more technical requirements in a Guideline publication; and

WHEREAS, the City Council does hereby further find that:

- (1) Orange County has an established, large reclaimed water infrastructure system;
- (2) Allocation-based and tiered water rate structures allow public agencies to document water use in landscapes;
- (3) Incentive-based water use efficiency programs have been actively implemented within Orange County since before 1991;
- (4) Current local design practices in new landscapes typically achieve the State Model Water Efficient Landscape Ordinance water use goals;
- (5) All water services within the City are metered;
- (6) Orange County is a leader in researching and promoting the use of smart automatic irrigation controllers with more than 4,500 installations as of June 2009;
- (7) All new irrigation controllers sold after 2012 within Orange County will be smart controllers;
- (8) Landscape plan submittal and review has been a long-standing practice in Fountain Valley;
- (9) The average rainfall in Orange County is approximately 12 inches per year;
- (10) The City, as the local water purveyor, is implementing enforcement of water waste prohibitions for all existing metered landscaped areas within its jurisdiction; and

WHEREAS, consistent with these findings, the purpose of the City's water efficient landscape ordinance is to establish an alternative model acceptable under AB 1881 as

being at least as effective as the State Model Water Efficient Landscape Ordinance in the context of conditions in the City in order to:

- (1) promote the benefits of consistent landscape ordinances with neighboring local and regional agencies;
- (2) promote the values and benefits of landscapes while recognizing the need to invest water and other resources as efficiently as possible;
- (3) establish a structure for planning, designing, installing, and maintaining and managing water efficient landscapes in new construction and rehabilitated projects;
- (4) establish provisions for water management practices and water waste prevention for existing landscapes;
- (5) use water efficiently without waste by setting a Maximum Applied Water Allowance as an upper limit for water use and reduce water use to the lowest practical amount;
- (6) encourage the use of economic incentives that promote the efficient use of water, such as implementing a budget-based tiered-rate structure; and


WHEREAS, the OCCOG recommends, and the City Council does hereby agree, that the OCCOG ordinance is the better regulation and meets the requirements of the law while being user friendly, especially in allowing self-certification, and will provide consistency throughout Orange County; and


WHEREAS, the City Council does further state its intention to adopt the OCCOG Guidelines by resolution and to integrate that document into this ordinance;

NOW, THEREFORE, THE CITY COUNCIL OF THE CITY OF FOUNTAIN VALLEY DOES HEREBY RESOLVE to adopt the attached Guidelines (Exhibit "A") to complement its ordinance adopting water conservation in landscaping and to set forth the technical aspects of the program.

PASSED AND ADOPTED by the City Council of the City of Fountain Valley at a regular adjourned meeting this 1 day of December, 2009.

ATTEST:


Kathleen Heard
Deputy City Clerk


Larry Crandall
Mayor

APPROVED AS TO FORM:


Alan Burns
City Attorney

GUIDELINES
FOR IMPLEMENTATION OF THE
CITY OF FOUNTAIN VALLEY
WATER EFFICIENT LANDSCAPE
ORDINANCE

TABLE OF CONTENTS

<u>Section</u>	<u>Page No.</u>
1. Purpose and Applicability.....	1
1.1 Purpose.....	1
1.2 Applicability	2
2. Submittal Requirements for New Landscape Installations or Landscape Rehabilitation Projects.....	3
2.1 Elements of the Landscape Documentation Package	3
2.2 Water Efficient Landscape Calculations and Alternatives	4
2.3 Soil Management Report	6
2.4 Landscape Design Plan.....	7
2.5 Irrigation Design Plan	10
2.6 Grading Design Plan.....	14
2.7 Certification of Completion.....	15
2.8 Post-Installation Irrigation Scheduling.....	16
2.9 Post-Installation Landscape and Irrigation Maintenance.....	16
3. Provisions for Existing Landscapes.....	16
Appendix A – Example Certification of Design.....	A-1
Appendix B – Water Efficient Landscape Worksheet.....	B-1
Appendix C – Reference Evapotranspiration (ET _o) Table.....	C-1
Appendix D – Example Installation Certificate of Completion.....	D-1
Appendix E - Definitions	E-1

1. Purpose and Applicability

1.1 Purpose

- (a) The primary purpose of these Guidelines is to provide procedural and design guidance for *project applicants* proposing landscape installation or rehabilitation projects that are subject to the requirements of the *Water Efficient Landscape Ordinance*. This document is also intended for use and reference by City staff in reviewing and approving designs and verifying compliance with the *Water Efficient Landscape Ordinance*. The general purpose of the *Water Efficient Landscape Ordinance* is to promote the design, installation, and maintenance of landscaping in a manner that conserves regional water resources by ensuring that landscaping projects are not unduly water-needy and that irrigation systems are appropriately implemented to minimize water waste.
- (b) Other regulations affecting landscape design and maintenance practices are potentially applicable and should be consulted for additional requirements. These regulations include but may not be limited to:
 - (1) State of California Assembly Bill 1881;
 - (2) National Pollutant Discharge Elimination Permit for the Municipal Separate Storm Sewer System;
 - (3) Water Conservation and Drought Response Regulations of the Local Water Purveyor;
 - (4) Regulations of the Local Water Purveyor governing use of Recycled Water;
 - (5) Zoning Code;
 - (6) Building Code;
 - (7) Specific Plans, Master Plans, General Plan, or similar land use and planning documents; and
 - (8) Conditions of approval for a specific project

1.2 Applicability

- (a) The Water Efficient Landscape Ordinance and these Guidelines apply to all of the following landscape projects:
 - (1) New landscape installations or landscape rehabilitation projects by public agencies or private non-residential developers with a landscaped area, including pools or other water features but excluding hardscape, equal to or greater than 2,500 square feet, and which are otherwise subject to a discretionary approval of a landscape plan or which otherwise require a ministerial permit for a landscape or water feature.

- (2) New landscape installations or landscape rehabilitation projects by developers or property managers of single-family and multi-family residential projects or complexes with a landscaped area, including pools or other water features but excluding hardscape, equal to or greater than 2,500 square feet, and which are otherwise subject to a discretionary approval of a landscape plan or which otherwise require a ministerial permit for a landscape or water feature
 - (3) New landscape installation projects by individual homeowners on single-family or multi-family residential lots with a project landscaped area, including pools or other water features but excluding hardscape, equal to or greater than 5,000 square feet, and which are otherwise subject to a discretionary approval of a landscape plan or which otherwise require a ministerial permit for a landscape or water feature.
- (b) A landscape rehabilitation project is subject to the requirements of the Ordinance and these Guidelines where (i) the modified landscaped area is greater than 2,500 square feet and represents at least 50% of the total landscaped area; and (ii) the modifications are planned to occur within one year. The requirements of the Guidelines may be partially or wholly waived, at the discretion of the city or its designee, for landscape rehabilitation projects that are limited to replacement plantings with equal or lower water needs and where the irrigation system is found to be designed, operable and programmed consistent with minimizing water waste in accordance with local water purveyor regulations.
- (c) Unless otherwise determined by the *City*, the Water Efficient Landscape Ordinance and these Guidelines do not apply to:
- (1) registered local, state, or federal historical sites;
 - (2) ecological restoration projects that do not require a permanent irrigation system;
 - (3) mined-land reclamation projects that do not require a permanent irrigation system; or
 - (4) plant collections, as part of botanical gardens and arboretums open to the public.

2. Submittal Requirements for New Landscape Installations or Landscape Rehabilitation Projects

- (a) Discretionary approval is typically required for landscape projects that are subject to site plan reviews, or where a variance from a local building code is requested, or other procedural processes apply such that standard or special conditions of approval may be required by the City. Discretionary projects with conditions of approval may be approved administratively by city staff, or acted on formally by the Planning Commission, City Council, or other jurisdictional authority. A typical standard condition of approval reads:

“Landscaping for the project shall be designed to comply with the City’s Water Efficient Landscape Ordinance and with the Guidelines for Implementation of the Water Efficient Landscape Ordinance.”

Landscape or water features that typically require a ministerial permit (i.e., a building, plumbing, electrical, or other similar permit), thereby triggering compliance with the Water Efficient Landscape Ordinance requirements independently of the need for discretionary approval include, but are not limited to, swimming pools, fountains or ponds, retaining walls, and overhead trellises.

2.1 Elements of the Landscape Documentation Package

- (a) A *Landscape Documentation Package* is required to be submitted by the *project applicant* for review and approval prior to the issuance of ministerial permits for landscape or water features by the City, and prior to start of construction. Unless otherwise directed by the City, the *Landscape Documentation Package* shall include the following elements either on plan sheets or supplemental pages as directed by the City:
 - (1) Project Information, including, but not limited to, the following:
 - (a) date;
 - (b) project name;
 - (c) project address, parcel, and/or lot number(s);
 - (d) total landscaped area (square feet) and rehabilitated landscaped area (if applicable);
 - (e) project type (e.g., new, rehabilitated, public, private, cemetery, homeowner-installed);
 - (f) water supply type (e.g., potable, recycled, or well) and identification of the local retail water purveyor if the *project applicant* is not served by a private well;
 - (g) checklist or index of all documents in the *Landscape Documentation Package*;
 - (h) project contacts, including contact information for the *project applicant* and *property owner*;
 - (i) a *Certification of Design* in accordance with **Exhibit A** of these *Guidelines* that includes a *landscape professional’s* professional stamp, as applicable, signature, contact information (including email and telephone number), license number, and date, certifying the statement that “The design of this project complies with the requirements of the City’s *Water Efficient Landscape Ordinance*”

and shall bear the signature of the *landscape professional* as required by law; and

- (j) any other information the City deems relevant for determining whether the landscape project complies with the *Water Efficient Landscape Ordinance* and these *Guidelines*.
- (2) *Maximum Applied Water Allowance (MAWA)* and *Estimated Applied Water Use (EAWU)* expressed as annual totals including, but not limited to, the following:
- (a) a *Water Efficient Landscape Worksheet* (optional at discretion of the City) for the landscape project;
 - (b) *hydrozone* information table (optional at the discretion of the City) for the landscape project; and
 - (c) water budget calculations (optional at the discretion of the City) for the landscape project.
- (3) A soil management report or specifications, or specification provision requiring soil testing and amendment recommendations and implementation to be accomplished during construction of the landscape project.
- (4) A landscape design plan for the landscape project.
- (5) An irrigation design plan for the landscape project.
- (6) A grading design plan, unless grading information is included in the landscape design plan for the landscape project or unless the landscape project is limited to replacement planting and/or irrigation to rehabilitate an existing landscaped area.

[Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.]

2.2 Water Efficient Landscape Calculations and Alternatives

- (a) The *project applicant* shall provide the calculated *Maximum Applied Water Allowance (MAWA)* and *Estimated Applied Water Use (EAWU)* for the *landscaped area* as part of the *Landscape Documentation Package* submittal to the City. The *MAWA* and *EAWU* shall be calculated based on completing the *Water Efficient Landscape Worksheets* (in accordance with the sample worksheets in **Appendix B**).
- (b) The *EAWU* allowable for the *landscaped area* shall not exceed the *MAWA*. The *MAWA* shall be calculated using an *evapotranspiration adjustment factor (ETAF)* of 0.7 except for the portion of the *MAWA* applicable to any *special landscaped areas* within the landscape project, which shall be calculated using an *ETAF* of

1.0. Where the design of the *landscaped area* can otherwise be shown to be equivalently water-efficient, the *project applicant* may submit alternative or abbreviated information supporting the demonstration that the annual *EAWU* is less than the *MAWA*, at the discretion of and for the review and approval of the local agency.

(c) Water budget calculations shall adhere to the following requirements:

- (1) The *MAWA* shall be calculated using the *Water Efficient Landscape Worksheets* and equation presented in **Appendix B** on page B-1. The example calculation on page B-1 is a hypothetical example to demonstrate proper use of the equation.
- (2) The *EAWU* shall be calculated using the *Water Efficient Landscape Worksheets* and equation presented in **Appendix B** on page B-2. The example calculation on page B-2 is a hypothetical example.
- (3) For the calculation of the *MAWA* and *EAWU*, a *project applicant* shall use the *ETo* values from the closest location listed the Reference Evapotranspiration Table in **Appendix C**. For geographic areas not covered in **Appendix C**, data from other cities located nearby in the same reference evapotranspiration zone may be used, as found in the CIMIS Reference Evapotranspiration Zones Map, Department of Water Resources, 1999.
- (4) For calculation of the *EAWU*, the *plant water use factor* shall be determined as appropriate to the project location from the *Water Use Efficiency of Landscape Species (WUCOLS)* Species Evaluation List. The *plant factor* is 0.1 for very low water use plants, 0.2 to 0.3 for low water use plants, 0.4 to 0.6 for moderate water use plants, and 0.7 to 1.0 for high water use plants.
- (5) For calculating the *EAWU*, the plant water use factor shall be determined for each valve *hydrozone* based on the highest-water-use plant species within the zone. The *plant factor* for each hydrozone may be required to be further refined as a "landscape coefficient," according to protocols defined in detail in the *WUCOLS* document, to reflect planting density and microclimate effects on water need at the option of the *project applicant* or the *City*.
- (6) For calculation of the *EAWU*, the area of a water feature shall be defined as a high water use hydrozone with a *plant factor* of 1.0.
- (7) For calculation of the *EAWU*, a temporarily irrigated hydrozone area, such as an area of highly drought-tolerant native plants that are not intended to be irrigated after they are fully established, shall be defined as a very low water use hydrozone with a *plant factor* of 0.1.

- (8) For calculation of the *MAWA*, the *ETAF* for *special landscaped areas* shall be set at 1.0. For calculation of the *EAWU*, the *ETAF* for *special landscaped areas* shall be calculated as the *special landscaped area (SLA) plant factor* divided by the *SLA irrigation efficiency factor*.
- (9) *Irrigation efficiency* shall be calculated using the worksheet and equation presented in **Appendix B** on page B-2.
- (d) The *Maximum Applied Water Allowance* shall adhere to the following requirements:
 - (1) The *Maximum Applied Water Allowance* shall be calculated using the equation presented in **Appendix B**. The example calculation in **Appendix B** is hypothetical to demonstrate proper use of the equation and does not represent an existing and/or planned landscape project. The *reference evapotranspiration (ET_o)* values used in this calculation are from the *Reference Evapotranspiration Table* in **Appendix C** and are for planning purposes only. For actual irrigation scheduling, automatic irrigation controllers are required and shall use current *ET_o* data, such as from the California Irrigation Management Information System (CIMIS), other equivalent data, or soil moisture sensor data.

2.3 Soil Management Report

- (a) In order to reduce *runoff* and encourage healthy plant growth, a soil management report shall be completed by the *project applicant*, or his/her designee, as follows:
 - (1) Submit soil samples to a certified agronomic soils laboratory for analysis and recommendations.
 - (a) Soil sampling shall be conducted in accordance with laboratory protocol, including protocols regarding adequate sampling depth for the intended plants.
 - (b) The soil analysis may include, but is not limited to:
 1. soil texture;
 2. infiltration rate determined by laboratory test or soil texture infiltration rate table;
 3. pH;
 4. total soluble salts;
 5. sodium;
 6. percent organic matter; and

7. recommendations.

- (2) The *project applicant*, or his/her designee, shall comply with one of the following:
- (a) if significant mass grading is not planned, the soil analysis report shall be submitted to the local agency as part of the Landscape Documentation Package; or
 - (b) If significant mass grading is planned, the soil analysis report shall be submitted to the *City* as part of the *Certification of Completion*.
 - (c) The soil analysis report shall be made available, in a timely manner, to the professionals preparing the landscape design plans and irrigation design plans in order to make any necessary adjustments to the design plans.
 - (d) The *project applicant*, or his/her designee, shall submit documentation verifying implementation of soil analysis report recommendations to the local agency with the *Certification of Completion*.

[Note: Authority Cited: Section 65595, Government Code.
Reference: Section 65596, Government Code.]

2.4 Landscape Design Plan

- (a) For the efficient use of water, a landscape shall be carefully designed and planned for the intended function of the project. At the landscape design plan meeting, the following design criteria shall be submitted as part of the *Landscape Documentation Package*.

(1) Plant Material

- (a) Any plant may be selected for the *landscaped area* provided the *EAWU* in the *landscaped area* does not exceed the *MAWA*. To encourage the efficient use of water, the following is highly recommended:
1. protection and preservation of non-invasive *water-conserving plant species* and *water-conserving turf*;
 2. selection of *water-conserving plant species* and *water-conserving turf*;
 3. selection of plants based on disease and pest resistance;
 4. selection of trees based on applicable City and local tree ordinances or tree shading guidelines; and

5. selection of plants from local and regional landscape program plant lists.

- (b) Each *hydrozone* shall have plant materials with similar water use, with the exception of *hydrozones* with plants of mixed water use, as specified in Section 2.5(a)(2)(D) of these *Guidelines*.
- (c) Plants shall be selected and planted appropriately based upon their adaptability to the climatic, geologic, and topographical conditions of the project site. To encourage the efficient use of water, the following is highly recommended for inclusion in the landscape design plan:
 - (1) use the Sunset Western Climate Zone System which takes into account temperature, humidity, elevation, terrain, latitude, and varying degrees of continental and marine influence on local climate;
 - (2) recognize the horticultural attributes of plants (i.e., mature plant size, invasive surface roots) to minimize damage to property or infrastructure (e.g., buildings, sidewalks, and power lines); and
 - (3) consider the solar orientation for plant placement to maximize summer shade and winter solar gain.
- (d) *Turf* is discouraged on slopes greater than 25% where the toe of the slope is adjacent to an impermeable hardscape and where 25% means 1 foot of vertical elevation change for every 4 feet of horizontal length (rise divided by run x 100 = slope percent).
- (e) A landscape design plan for projects in fire-prone areas and fuel modification zones shall comply with requirements of the local Fire Authority, where applicable. When conflicts between water conservation and fire safety design elements exist, the fire safety requirements shall have priority.
- (f) The use of *invasive plant species* and/or *noxious plant species* is strongly discouraged.
- (g) The architectural guidelines of a *common interest development*, which include community apartment projects, condominiums, planned developments, and stock cooperatives, shall not prohibit or include conditions that have the effect of prohibiting the use of *water efficient plant species* as a group.
 - (1) Water Features
 - (a) Recirculating water systems shall be used for water features.
 - (b) Where available and consistent with public health guidelines, recycled water shall be used as a source for decorative water features.

- (c) The surface area of a water feature shall be included in the high water use *hydrozone* area of the water budget calculation.
 - (d) Pool and spa covers are highly recommended.
- (2) *Mulch* and Amendments
- (a) A minimum two inch (2") layer of *mulch* shall be applied on all exposed soil surfaces of planting areas except in turf areas, creeping or rooting groundcovers, or direct seeding applications where *mulch* is contraindicated.
 - (b) Stabilizing mulching products shall be used on slopes.
 - (c) The mulching portion of the seed/*mulch* slurry in hydro-seeded applications shall meet the mulching requirement.
 - (d) Soil amendments shall be incorporated according to recommendations of the soil report and what is appropriate for the plants selected (see Section 2.3 of these *Guidelines*).
- (h) The landscape design plan, at a minimum, shall:
- (1) delineate and label each *hydrozone* by number, letter, or other method;
 - (2) identify each *hydrozone* as low, moderate, high water, or mixed water use. Temporarily irrigated areas of the *landscaped area* shall be included in the low water use *hydrozone* for the water budget calculation;
 - (3) identify recreational areas;
 - (4) identify areas permanently and solely dedicated to edible plants;
 - (5) identify areas irrigated with recycled water;
 - (6) identify type of *mulch* and application depth;
 - (7) identify soil amendments, type, and quantity;
 - (8) identify type and surface area of water features;
 - (9) identify *hardscapes* (*pervious* and *non-pervious*);
 - (10) identify location and installation details of any applicable storm water best management practices that encourage on-site retention and infiltration of storm water. Storm water best management practices are encouraged in the landscape design plan and examples include, but are not limited to:
 - (a) infiltration beds, swales, and basins that allow water to collect and soak into the ground;

- (b) constructed wetlands and retention ponds that retain water, handle excess flow, and filter pollutants; and
 - (c) *pervious* or porous surfaces (e.g., permeable pavers or blocks, *pervious* or porous concrete, etc.) that minimize *runoff*.
- (11) identify any applicable rain harvesting or catchment technologies (e.g., rain gardens, cisterns, etc.);
 - (12) contain the following statement: "I have complied with the criteria of the *Water Efficient Landscape Ordinance* and applied them for the efficient use of water in the landscape design plan;" and
 - (13) bear the signature of a California-licensed *landscape professional*.

[Note: Authority Cited: Section 65595, Reference: Section 65596, Government Code and Section 1351, Civil Code.]

2.5 Irrigation Design Plan

- (a) For the efficient use of water, an irrigation system shall meet all the requirements listed in this section and the manufacturer's recommendations. The irrigation system and its related components shall be planned and designed to allow for proper installation, management, and maintenance. An irrigation design plan meeting the following design criteria shall be submitted as part of the *Landscape Documentation Package*.
 - (1) System
 - (a) Dedicated landscape water meters are highly recommended on *landscaped areas* smaller than 5,000 square feet to facilitate water management.
 - (b) Automatic irrigation controllers utilizing either evapotranspiration or soil moisture sensor data shall be required for irrigation scheduling in all irrigation systems.
 - (c) The irrigation system shall be designed to ensure that the dynamic pressure at each emission device is within the manufacturer's recommended pressure range for optimal performance.
 - 1. If the static pressure is above or below the required dynamic pressure of the irrigation system, pressure-regulating devices such as inline pressure regulators, booster pumps, or other devices shall be installed to meet the required dynamic pressure of the irrigation system.
 - 2. *Static water pressure*, dynamic or *operating pressure*, and flow reading of the water supply shall be measured at the point of connection. These pressure and flow measurements shall be

conducted at the design stage. If the measurements are not available at the design stage, the measurements shall be conducted at installation.

- (d) *Sensors* (rain, freeze, wind, etc.), either integral or auxiliary, that suspend or alter irrigation operation during unfavorable weather conditions shall be required on all irrigation systems, as appropriate for local climatic conditions. Irrigation should be avoided during windy or freezing weather or during rain.
- (e) Manual shut-off *valves* (such as a *gate valve*, *ball valve*, or *butterfly valve*) shall be required as close as possible to the point of connection of the water supply to minimize water loss in case of an emergency (such as a *main line* break) or routine repair.
- (f) *Backflow prevention devices* shall be required to protect the water supply from contamination by the irrigation system. A *project applicant* shall refer to the applicable City code (i.e., public health) for additional backflow prevention requirements.
- (g) High flow sensors that detect and report high flow conditions created by system damage or malfunction are recommended.
- (h) The irrigation system shall be designed to prevent *runoff*, low head drainage, *overspray*, or other similar conditions where irrigation water flows onto non-targeted areas, such as adjacent property, non-irrigated areas, *hardscapes*, roadways, or structures.
- (i) Relevant information from the soil management plan, such as soil type and *infiltration rate*, shall be utilized when designing irrigation systems.
- (j) The design of the irrigation system shall conform to the hydrozones of the landscape design plan.
- (k) Average irrigation efficiency for the project shall be determined in accordance with the EAWU calculation sheet in **Appendix B**. Unless otherwise indicated by the irrigation equipment manufacturer's specifications or demonstrated by the *project applicant*, the *irrigation efficiency* of the irrigation heads used within each hydrozone shall be assumed to be:

Pop-up stream rotator heads = 75%

Stream rotor heads = 75%

Microspray = 75%

Bubbler = 80%

Drip emitter = 85%

Subsurface irrigation = 90%

- (l) It is highly recommended that the *project applicant* or local agency inquire with the local water purveyor about peak water operating demands (on the water supply system) or water restrictions that may impact the effectiveness of the irrigation system.
- (m) In *mulched* planting areas, the use of *low volume irrigation* is required to maximize water infiltration into the root zone.
- (n) *Sprinkler heads* and other emission devices shall have matched *precipitation rates*, unless otherwise directed by the manufacturer's recommendations.
- (o) Head to head coverage is recommended. However, sprinkler spacing shall be designed to achieve the highest possible *distribution uniformity* using the manufacturer's recommendations.
- (p) *Swing joints* or other riser-protection components are required on all risers subject to damage that are adjacent to high traffic areas.
- (q) *Check valves* or *anti-drain valves* are required for all irrigation systems.
- (r) Narrow or irregularly shaped areas, including turf, less than eight (8) feet in width in any direction shall be irrigated with subsurface irrigation or a *low volume irrigation* system.
- (s) *Overhead* irrigation shall not be permitted within 24 inches of any non-permeable surface. Allowable irrigation within the setback from non-permeable surfaces may include drip, drip line, or other low flow non-spray technology. The setback area may be planted or unplanted. The surfacing of the setback may be *mulch*, gravel, or other porous material. These restrictions may be modified if:
 1. the *landscaped area* is adjacent to permeable surfacing and no *runoff* occurs; or
 2. the adjacent non-permeable surfaces are designed and constructed to drain entirely to landscaping; or
 3. the irrigation designer for the landscape project specifies an alternative design or technology, as part of the *Landscape Documentation Package*, and clearly demonstrates strict adherence to the irrigation system design criteria in Section 2.5 (a)(1)(H) hereof. Prevention of overspray and runoff must be confirmed during an irrigation audit.
 4. Slopes greater than 25% shall not be irrigated with an irrigation system with a *precipitation rate* exceeding 0.75 inches per hour. This restriction may be modified if the landscape designer of the landscape project specifies an alternative design

or technology, as part of the *Landscape Documentation Package*, and clearly demonstrates no *runoff* or erosion will occur. Prevention of *runoff* and erosion must be confirmed during the *irrigation audit*.

(2) **Hydrozone**

- (a) Each *valve* shall irrigate a *hydrozone* with similar site, slope, sun exposure, soil conditions, and plant materials with similar water use.
- (b) *Sprinkler heads* and other emission devices shall be selected based on what is appropriate for the plant type within that *hydrozone*.
- (c) Where feasible, trees shall be placed on separate valves from shrubs, groundcovers, and *turf*.
- (d) Individual *hydrozones* that mix plants of moderate and low water use or moderate and high water use may be allowed if:
 - 1. the *plant factor* calculation is based on the proportions of the respective plant water uses and their respective *plant factors*;
or
 - 2. the *plant factor* of the higher water using plant is used for the calculations.
- (e) Individual *hydrozones* that mix high and low water use plants shall not be permitted.
- (f) On the landscape design plan and irrigation design plan, *hydrozone* areas shall be designated by number, letter, or other designation. On the irrigation design plan, designate the areas irrigated by each *valve* and assign a number to each *valve*.
- (g) The irrigation design plan, at a minimum, shall contain:
 - 1. the location and size of separate water meters for landscape;
 - 2. the location, type, and size of all components of the irrigation system, including controllers, main and *lateral lines*, *valves*, *sprinkler heads*, *moisture sensing devices*, rain switches, quick couplers, pressure regulators, and *backflow prevention devices*;
 - 3. *static water pressure* at the point of connection to the public water supply;
 - 4. *flow rate* (gallons per minute), application rate (inches per hour), and design *operating pressure* (pressure per square inch) for each *station*;

5. irrigation schedule parameters necessary to program smart timers specified in the landscape design;
6. the following statement: "I have complied with the criteria of the *Water Efficient Landscape Ordinance* and applied them accordingly for the efficient use of water in the irrigation design plan;" and
7. the signature of a California-licensed *landscape professional*.

[Note: Authority Cited: Section 65595, Government Code.
Reference: Section 65596, Government Code.]

2.6 Grading Design Plan

- (a) For the efficient use of water, grading of a landscape project site shall be designed to minimize soil erosion, *runoff*, and water waste. Finished grading configuration of the *landscaped area*, including pads, slopes, drainage, post-construction erosion control, and storm water control Best Management Practices, as applicable, shall be shown on the Landscape Plan unless this information is fully included in separate Grading Plans for the project, or unless the project is limited to replacement planting and/or irrigation to rehabilitate an existing *landscaped area*.
- (b) The *project applicant* shall submit a landscape grading plan that indicates finished configurations and elevations of the *landscaped area* including:
 - (1) height of graded slopes;
 - (2) drainage patterns;
 - (3) pad elevations;
 - (4) finish grade; and
 - (5) storm water retention improvements, if applicable.
- (c) To prevent excessive erosion and *runoff*, it is highly recommended that the *project applicant*:
 - (1) grade so that all irrigation and normal rainfall remains within property lines and does not drain on to non-permeable *hardscapes*;
 - (2) avoid disruption of natural drainage patterns and undisturbed soil; and
 - (3) avoid soil compaction in *landscaped areas*.
- (d) The Grading Design Plan shall contain the following statement: "I have complied with the criteria of the ordinance and applied them accordingly for the efficient

use of water in the grading design plan” and shall bear the signature of the *landscape professional*, as required by law.

[Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.]

2.7 Certification of Completion

- (a) Landscape project installation shall not proceed until the *Landscape Documentation Package* has been approved by the City and any ministerial permits required are issued.
- (b) The *project applicant* shall notify the City at the beginning of the installation work and at intervals, as necessary, for the duration of the landscape project work to schedule all required inspections.
- (c) *Certification of Completion* of the landscape project shall be obtained through a Certificate of Use and Occupancy or a *Permit Final*. The requirements for the Final Inspection and *Permit Closure* include submittal of:
 - (1) *A Landscape Installation Certificate of Completion* in the form included as **Appendix D** of these *Guidelines*, which shall include: (i) certification by a *landscape professional* that the *landscape project* has been installed per the approved *Landscape Documentation Package*; and (ii) the following statement: “The landscaping has been installed in substantial conformance to the design plans, and complies with the provisions of the *Water Efficient Landscape Ordinance* for the efficient use of water in the landscape.”
 - (2) Documentation of the irrigation scheduling parameters used to set the *controller(s)*;
 - (3) An irrigation audit report from a certified irrigation auditor, documentation of enrollment in regional or local water purveyor’s water conservation programs, and/or documentation that the MAWA and EAWU information for the *landscape project* has been submitted to the local water purveyor, may be required at the option of the City.

[Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.]

2.8 Post-Installation Irrigation Scheduling

- (a) For the efficient use of water, all irrigation schedules shall be developed, managed, and evaluated to utilize the minimum amount of water required to maintain plant health. Irrigation schedules shall meet the following criteria:
 - (1) Irrigation scheduling shall be regulated by automatic irrigation controllers.

- (2) *Overhead* irrigation shall be scheduled in accordance with the local water purveyor's Water Conservation Ordinance. Operation of the irrigation system outside the normal *watering window* is allowed for auditing and system maintenance.

[Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.]

2.9 Post-Installation Landscape and Irrigation Maintenance

- (a) Landscapes shall be maintained to ensure water use efficiency in accordance with existing local agency code.

3. Provisions for Existing Landscapes

- (a) Irrigation of all *landscaped areas* shall be conducted in a manner conforming to the rules and requirements and shall be subject to penalties and incentives for water conservation and water waste prevention, as determined and implemented by the *local water purveyor* and as may be mutually agreed by the *City*.
- (b) The City and/or the regional or *local water purveyor* may administer programs such as irrigation water use analyses, irrigation surveys and/or irrigation audits, tiered water rate structures, water budgeting by parcel, or other approaches to achieve landscape water use efficiency community-wide to a level equivalent to or less than would be achieved by applying a *MAWA* calculated with an ETAF of 0.8 to all *landscaped areas* in the *City* over one acre in size.
- (c) The architectural guidelines of a *common interest development*, including apartments, condominiums, planned developments, and stock cooperatives, shall not prohibit or include conditions that have the effect of prohibiting the use of low-water use plants as a group.

CERTIFICATION OF LANDSCAPE DESIGN

I hereby certify that:

(1) I am a professional appropriately licensed in the State of California to provide professional landscape design services.

(2) The landscape design and water use calculations for the property located at _____
(provide street address or parcel number(s)) were prepared by me or under my supervision.

(3) The landscape design and water use calculations for the identified property comply with the requirements of the City of _____ Water Efficient Landscape Ordinance (Municipal Code Sections _____) and the City of _____ Guidelines for Implementation of the City of _____ Water Efficient Landscape Ordinance.

(4) The information I have provided in this Certificate of Landscape Design is true and correct and is hereby submitted in compliance with the City of _____ Guidelines for Implementation of the City of _____ Water Efficient Landscape Ordinance.

Print Name

Date

Signature


License Number

Address

Telephone

E-mail Address

Landscape Design Professional's Stamp
(If applicable)



A-1

EXAMPLE WATER EFFICIENT LANDSCAPE WORKSHEET

This worksheet is filled out by the project applicant for each Point of Connection. Please complete all sections of the worksheet.

Point of Connection # 1

Maximum Applied Water Allowance (MAWA)

Total MAWA = (ETo x 0.7 x LA in Sq. Ft. x 0.62) + (ETo x 1.0 x SLA in Sq. Ft. x 0.62) = Gallons per year for LA+SLA

where:

- MAWA = Maximum Applied Water Allowance (gallons per year)
- ETo = Reference Evapotranspiration Appendix C (inches per year)
- 0.7 = Evapotranspiration Adjustment Factor (ETAF)
- 1.0 = ETAF for Special Landscaped Area
- LA = Landscaped Area (square feet)
- 0.62 = Conversion factor (to gallons per square foot)
- SLA = Special Landscaped Area (square feet)

Example Calculation: a hypothetical landscape project in Santa Ana, CA with an irrigated landscaped area of 40,000 square feet with 10,000 square feet of Special Landscaped Area. To calculate MAWA, the annual reference evapotranspiration value for Santa Ana is 48.2 inches as listed in the Reference Evapotranspiration Table in Appendix C.

ETo		ETAF		LA or SLA (ft ²)		Conversion		MAWA (Gallons Per Year)
MAWA for LA =	48.2	x	0.7	x	40,000	x	0.62	= 836,752
MAWA for SLA =	48.2	x	1.0	x	10,000	x	0.62	= 298,840
Total MAWA =				50,000				1,135,592 Gallons per year for LA+SLA

Estimated Applied Water Use

$$EAWU = ETo \times K_L \times LA \times 0.62 \div IE = \text{Gallons per year}$$

where:

- $EAWU$ = Estimated Applied Water Use (gallons per year)
- ETo = Reference Evapotranspiration Appendix C (inches per year)
- K_L = Landscape Coefficient
- LA = Landscaped Area (square feet)
- 0.62 = Conversion factor (to gallons per square foot)
- IE = Irrigation Efficiency = $IME \times DU$ (See definition in Appendix E for example IE percentages)
- IME = Irrigation Management Efficiency (90%)
- DU = Distribution Uniformity of Irrigation head

Example Calculation:

	ETo	K _L	LA	Conversion	IE	EAWU (Gallons per year)
Special Landscaped Area	48.2	x 1.00	x 10,000	x 0.62	÷ 0.75	= 398,453
Cool Season Turf	48.2	x 1.00	x 0	x 0.62	÷ 0.71	= 0
Warm Season Turf	48.2	x 0.65	x 0	x 0.62	÷ 0.71	= 0
High Water Using Shrub	48.2	x 0.70	x 0	x 0.62	÷ 0.71	= 0
Medium Water Using Shrub	48.2	x 0.50	x 15,000	x 0.62	÷ 0.65	= 344,815
Low Water Using Shrub	48.2	x 0.30	x 25,000	x 0.62	÷ 0.75	= 298,840
Very Low Water Using Shrub	48.2	x 0.20	x 0	x 0.62	÷ 0.71	= 0
Other	48.2	x 0.50	x 0	x 0.62	÷ 0.71	= 0
Other	48.2	x 0.50	x 0	x 0.62	÷ 0.71	= 0
Total EAWU =			50,000			1,042,109 Gallons per year

Compare EAWU with MAWA.

The EAWU (1,042,109 gallons per year) is less than MAWA (1,135,592 gallons per year). For this example, the water budget complies with the MAWA.

$$K_L = K_s \times K_d \times K_{mc}$$

- K_s = species factor (range = 0.1-0.9) (see WUCOLS list for values)
- K_d = density factor (range = 0.5-1.3) (see WUCOLS for density value ranges)
- K_{mc} = microclimate factor (range = 0.5-1.4) (see WUCOLS)

WUCOLS – www.owue.water.ca.gov/docs/wucols00.pdf

List sprinkler heads, microspray, and drip emitters here along with average precipitation rate and Distribution Uniformity of Irrigation Head.

<u>Sprinkler Head Types</u>	<u>Average Precipitation Rate</u>	<u>Distribution Uniformity of Irrigation Head</u>
Drip		
Microspray		
Bubbler		
Low precipitation rotating nozzles		
Stream rotors		

WATER EFFICIENT LANDSCAPE WORKSHEET

This worksheet is filled out by the *project applicant* for each Point of Connection. Please complete all sections of the worksheet.

Point of Connection # _____

Maximum Applied Water Allowance (MAWA)

Total MAWA = (ETo x 0.7 x LA in Sq. Ft. x 0.62) + (ETo x 1.0 x SLA in Sq. Ft. x 0.62) = Gallons per year for LA+SLA

where:

- MAWA = Maximum Applied Water Allowance (gallons per year)
- ETo = Reference Evapotranspiration Appendix C (inches per year)
- 0.7 = Evapotranspiration Adjustment Factor (ETAF)
- 1.0 = ETAF for Special Landscaped Area
- LA = Landscaped Area (square feet)
- 0.62 = Conversion factor (to gallons per square foot)
- SLA = Special Landscaped Area (square feet)

MAWA Calculation:

ETo	ETAF	LA or SLA (ft ²)	Conversion	MAWA (Gallons Per Year)
	x 0.7	x	x 0.62	=
MAWA for LA =	x 1.0	x	x 0.62	=
MAWA for SLA =				
Total MAWA =				

Estimated Applied Water Use

$EAWU = ETo \times K_L \times LA \times 0.62 \div IE = \text{Gallons per year}$

where:

$EAWU = \text{Estimated Applied Water Use (gallons per year)}$

$ETo = \text{Reference Evapotranspiration Appendix C (inches per year)}$

$K_L = \text{Landscape Coefficient}$

$LA = \text{Landscaped Area (square feet)}$

$0.62 = \text{Conversion factor (to gallons per square foot)}$

$IE = \text{Irrigation Efficiency} = IME \times DU$

$IME = \text{Irrigation Management Efficiency (90\%)}$

$DU = \text{Distribution Uniformity of irrigation head}$

$EAWU$ Calculation:

$K_L = K_s \times K_d \times K_{mc}$

$K_s = \text{species factor (range = 0.1-0.9) (see WUCOLS list for values)}$

$K_d = \text{density factor (range = 0.5-1.3) (see WUCOLS for density value ranges)}$

$K_{mc} = \text{microclimate factor (range = 0.5-1.4) (see WUCOLS)}$

$WUCOLS - \text{www.owue.water.ca.gov/docs/wucols00.pdf}$

	ETo	K _L	LA	Conversion	IE	EAWU (Gallons Per Year)
Special Landscaped Area	x			x 0.62	÷	=
Cool Season Turf	x			x 0.62	÷	=
Warm Season Turf	x			x 0.62	÷	=
High Water Using Shrub	x			x 0.62	÷	=
Medium Water Using Shrub	x			x 0.62	÷	=
Low Water Using Shrub	x			x 0.62	÷	=
Very Low Water Using Shrubs	x			x 0.62	÷	=
Other	x			x 0.62	÷	=
Total EAWU =						

List sprinkler heads, microspray, and drip emitters here along with average precipitation rate and Distribution Uniformity of Irrigation Head.

<u>Sprinkler Head Types</u>	<u>Average Precipitation Rate</u>	<u>Distribution Uniformity of Irrigation Head</u>
Drip		
Microspray		
Bubbler		
Low precipitation rotating nozzles		
Stream rotors		

Reference Evapotranspiration (ET_o) Table

Appendix C - Reference Evapotranspiration (ET _o) Table*													
County and City	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Annual ET _o
Orange													
Irvine	2.2	2.5	3.7	4.7	5.2	5.9	6.3	6.2	4.6	3.7	2.6	2.3	49.6
Laguna Beach	2.2	2.7	3.4	3.8	4.6	4.6	4.9	4.9	4.4	3.4	2.4	2.0	43.2
Santa Ana	2.2	2.7	3.7	4.5	4.6	5.4	6.2	6.1	4.7	3.7	2.5	2.0	48.2
* The values in this table were derived from: 1) California Irrigation Management Information System (CIMIS) 2) Reference EvapoTranspiration Zones Map, UC Dept. of Land, Air & Water Resources and California Dept of Water Resources 1999, 3) Reference Evapotranspiration for California, University of California, Department of Agriculture and Natural Resources (1987) Bulletin 1922 4) Determining Daily Reference Evapotranspiration, Cooperative Extension UC Division of Agriculture and Natural Resources (1987), Publication Leaflet 21426													

LANDSCAPE INSTALLATION CERTIFICATE OF COMPLETION

I hereby certify that:

(1) I am a professional appropriately licensed in the State of California to provide professional landscape design services.

(2) The landscape project for the property located at _____ (provide street address or parcel number(s)) was installed by me or under my supervision.

(3) The landscaping for the identified property has been installed in substantial conformance with the approved Landscape Documentation Package and complies with the requirements of the City of _____ Water Efficient Landscape Ordinance (Municipal Code Sections _____) and the City of _____ Guidelines for Implementation of the City of _____ Water Efficient Landscape Ordinance for the efficient use of water in the landscape.

(4) The information I have provided in this Landscape Installation Certificate of Completion is true and correct and is hereby submitted in compliance with the City of _____ Guidelines for Implementation of the City of _____ Water Efficient Landscape Ordinance.

Print Name

Date

Signature


License Number

Address

Telephone

E-mail Address

Landscape Design Professional's Stamp
(If Appropriate)



D-1

Definitions

The terms used in these *Guidelines* have the meaning set forth below:

“*Backflow prevention device*” means a safety device used to prevent pollution or contamination of the water supply due to the reverse flow of water from the irrigation system.

“*Conversion factor*” means the number that converts acre-inches per acre per year to gallons per square foot per year.

“*Check valve*” or “*anti-drain valve*” means a valve located under a *sprinkler head*, or other location in the irrigation system, to hold water in the system to prevent drainage from *sprinkler heads* when the sprinkler is off.

“*Certified Landscape Irrigation Auditor*” means _____.

“*Certification of Design*” means the certification included as Exhibit E of these Guidelines that must be included in the *Landscape Documentation Package* pursuant to Section 2.1 of these Guidelines.

“*City*” means the City of _____ or its authorized designee.

“*Common interest developments*” means community apartment projects, condominium projects, planned developments, and stock cooperatives per Civil Code Section 1351

“*Distribution Uniformity*” or “*DU*” is a measure of how uniformly an irrigation head applies water to a specific target area and theoretically ranges from zero to 100 percent.

“*Drip irrigation*” means any non-spray *low volume irrigation* system utilizing emission devices with a *flow rate* measured in gallons per hour. *Low volume irrigation* systems are specifically designed to apply small volumes of water slowly at or near the root zone of plants.

“*Emitter*” means a *drip irrigation* emission device that delivers water slowly from the system to the soil.

“*Estimated Applied Water Use*” or “*EAU*” means the annual total amount of water estimated to keep plants in a healthy state. It is based on factors such as reference *evapotranspiration rate*, the size of the *landscaped area*, *plant water use factors*, and the *irrigation efficiency* within each hydrozone.

“*Evapotranspiration adjustment factor*” or “*ETAF*” means _____.

“*Evapotranspiration rate*” means the quantity of water evaporated from adjacent soil and other surfaces and transpired by plants during a specified time.

“*Flow rate*” means the rate at which water flows through pipes, *valves* and emission devices, measured in gallons per minute, gallons per hour, or cubic feet per second.

“*Hardscapes*” means any durable material or feature (*pervious* and *non-pervious*) installed in or around a *landscaped area*, such as pavements or walls. Pools and other water features are considered part of the *landscaped area* and not considered *hardscapes* for purposes of these Guidelines.

“*Hydrozone*” means a portion of the *landscaped area* having plants with similar water needs and typically irrigated by one *valve/controller* station. A *hydrozone* may be irrigated or non-irrigated.

“*Infiltration rate*” means the rate of water entry into the soil expressed as a depth of water per unit of time (e.g., inches per hour).

“*Invasive plants species*” or “*noxious*” means species of plants not historically found in California that spread outside cultivated areas and can damage environmental or economic resources. *Invasive plant species* may be regulated by county agricultural agencies as *noxious species*.

“*Irrigation audit*” means an in-depth evaluation of the performance of an irrigation system conducted by a *Certified Landscape Irrigation Auditor*. An *irrigation audit* includes, but is not limited to: inspection, system tune-up, system test with *distribution uniformity* or emission uniformity, reporting *overspray* or *runoff* that causes overland flow, and preparation of an irrigation schedule.

“*Irrigation Management Efficiency*” or “*IME*” means the measurement used to calculate the *irrigation efficiency* of the irrigation system for a landscaped project. A 90% IME can be achieved by using evapotranspiration controllers, soil moisture sensors, and other methods that will adjust irrigation run times to meet plant water needs.

“*Irrigation efficiency*” or “*IE*” means the measurement of the amount of water beneficially used divided by the amount of water applied to a *landscaped area*. *Irrigation efficiency* is derived from measurements and estimates of irrigation system characteristics and management practices. The minimum average *irrigation efficiency* for purposes of these *Guidelines* is 0.71. Greater *irrigation efficiency* can be expected from well designed and maintained systems. The following irrigation efficiency may be obtained for the listed irrigation heads with an IME of 90%:

- a. Pop-up stream rotator heads = 75%
- b. Stream rotor heads = 75%
- c. Microspray = 75%
- d. Bubbler = 80%
- e. Drip emitter = 85%
- f. Subsurface irrigation = 90%

"*Landscape coefficient*" (K_L) is the product of a *plant factor* multiplied by a density factor and a *microclimate* factor. The *landscape coefficient* is derived to estimate water loss from irrigated *landscaped areas* and *special landscaped areas*.

"*Landscape Documentation Package*" means the package of documents that a *project applicant* is required to submit to the *City* pursuant to Section 2.1 of these Guidelines.

"*Landscape Installation Certificate of Completion*" means the certificate included as Exhibit F of these *Guidelines* that must be submitted to the *City* pursuant to Section 2.7(a)(1) of hereof.

"*Landscape professional*" means a licensed *landscape architect*, licensed landscape contractor, or any other *person* authorized to design a landscape pursuant to Sections 5500.1, 5615, 5641, 5641.1, 5641.2, 5641.3, 5641.4, 5641.5, 5641.6, 6701, 7027.5 of the California Business and Professions Code, Section 832.27 of Title 16 of the California Code of Regulations, and Section 6721 of the California Food and Agriculture Code.

"*Landscaped area*" means all the planting areas, *turf* areas, and *water features* in a landscape design plan subject to the *Maximum Applied Water Allowance* and *Estimated Applied Water Use* calculations. The *landscaped area* does not include footprints of buildings or structures, sidewalks, driveways, parking lots, decks, patios, gravel or stone walks, other *pervious* or *non-pervious hardscapes*, and other non-irrigated areas designated for non-development (e.g., open spaces and existing native vegetation).

"*Lateral line*" means the water delivery pipeline that supplies water to the *emitters* or sprinklers from the *valve*.

"*Low volume irrigation*" means the application of irrigation water at low pressure through a system of tubing or *lateral lines* and low-volume *emitters* such as drip, drip lines, and bubblers. *Low volume irrigation* systems are specifically designed to apply small volumes of water slowly at or near the root zone of plants.

"*Main line*" means the pressurized pipeline that delivers water from the water source to the *valve* or outlet.

"*Maximum Applied Water Allowance*" or "*MAWA*" means the upper limit of annual applied water for the established *landscaped area*, as specified in Section 2.2 of these *Guidelines*. It is based upon the area's *reference evapotranspiration*, the *ETAF*, and the size of the *landscaped area*. The *Estimated Applied Water Use* shall not exceed the *Maximum Applied Water Allowance*.

"*Microclimate*" means the climate of a small, specific area that may contrast with the climate of the overall landscaped area due to factors such as wind, sun exposure, plant density, or proximity to reflective surfaces.

"*Mulch*" means any organic material such as leaves, bark, straw or compost, or inorganic mineral materials such as rocks, gravel, or decomposed granite left loose and applied to the soil surface for the beneficial purposes of reducing evaporation, suppressing weeds, moderating soil temperature, and preventing soil erosion.

"*Non-pervious*" means any surface or natural material that does not allow for the passage of water through the material and into the underlying soil.

"*Operating pressure*" means the pressure at which the parts of an irrigation system of sprinklers are designed to operate at by the manufacturer

"*Overspray*" means the irrigation water which is delivered beyond the target area.

"*Person*" means any natural person, firm, joint venture, joint stock company, partnership, public or private association, club, company, corporation, business trust, organization, public or private agency, government agency or institution, school district, college, university, any other user of water provided by the *City* or the *local water purveyor*, or the manager, lessee, agent, servant, officer, or employee of any of them or any other entity which is recognized by law as the subject of rights or duties.

"*Pervious*" means any surface or material that allows the passage of water through the material and into the underlying soil.

"*Plant factor*" or "*plant water use factor*" is a factor, when multiplied by *ETo*, that estimates the amount of water needed by plants. For purposes of this *Water Efficient Landscape Ordinance*, the *plant factor* range for low water use plants is 0 to 0.3; the *plant factor* range for moderate water use plants is 0.4 to 0.6; and the *plant factor* range for high water use plants is 0.7 to 1.0. *Plant factors* cited in these *Guidelines* are derived from the Department of Water Resources 2000 publication "Water Use Classification of Landscape Species."

"*Precipitation rate*" means the rate of application of water measured in inches per hour.

"*Project applicant*" means the person submitting a *Landscape Documentation Package* required under Section 2.1 to request a permit, plan check, or design review from the local agency. A *project applicant* may be the property owner or his or her designee.

"*Property owner*" or "*owner*" means the record owner of real property as shown on the most recently issued equalized assessment roll.

"*Reference evapotranspiration*" or "*ETo*" means a standard measurement of environmental parameters which affect the water use of plants. *ETo* is given expressed in inches per day, month, or year as represented in Appendix C of these *Guidelines*, and is an estimate of the evapotranspiration of a large field of four to seven-inch tall, cool-season grass that is well watered. *Reference evapotranspiration* is used as the basis of determining the *Maximum Applied Water Allowances*.

"*Recycled water*" or "*reclaimed water*" means treated or recycled waste water of a quality suitable for non-potable uses such as landscape irrigation and *water features*. This water is not intended for human consumption.

"*Runoff*" means water which is not absorbed by the soil or landscape to which it is applied and flows from the landscaped area. For example, *runoff* may result from water that is applied at too great a rate (application rate exceeds *infiltration rate*) or when there is a slope.

"*Special Landscaped Areas*" or "*SLA*" means an area of the landscape dedicated solely to edible plants such as orchards and vegetable gardens, areas irrigated with *recycled water*, *water features* using *recycled water*, and areas dedicated to active play such as parks, sports fields, golf courses, and where *turf* provides a playing surface.

"*Sprinkler head*" means a device which delivers water through a nozzle.

"*Static water pressure*" means the pipeline or municipal water supply pressure when water is not flowing.

"*Station*" means an area served by one *valve* or by a set of *valves* that operate simultaneously.

"*Swing joint*" means an irrigation component that provides a flexible, leak-free connection between the emission device and lateral pipeline to allow movement in any direction and to prevent equipment damage.

"*Turf*" means a ground cover surface of mowed grass. Annual bluegrass, Kentucky bluegrass, Perennial ryegrass, Red fescue, and Tall fescue are cool-season grasses. Bermudagrass, Kikuyugrass, Seashore Paspalum, St. Augustinegrass, Zoysiagrass, and Buffalo grass are warm-season grasses.

"*Valve*" means a device used to control the flow of water in an irrigation system

"*Water Efficient Landscape Ordinance*" means Ordinance No. _____, adopted by the City Council on _____, 2009, and codified in the Municipal Code in [chapter/title/division/sections _____].

"*Water Efficient Landscape Worksheets*" means the worksheets required to be completed pursuant to Section 2.2 of these *Guidelines* and which are included in Appendix B hereof.

"*Water feature*" means a design element where open water performs an aesthetic or recreational function. *Water features* include ponds, lakes, waterfalls, fountains, artificial streams, spas, and swimming pools (where water is artificially supplied). The surface area of *water features* is included in the high water use *hydrozone* of the *landscaped area*. Constructed wetlands used for on-site wastewater treatment, habitat protection, or storm water best management practices that are not irrigated and used solely for water treatment or storm water retention are not *water features* and, therefore, are not subject to the water budget calculation.

"*Watering window*" means the time of day irrigation is allowed.

"*WUCOLS*" means the Water Use Classification of Landscape published by the University of California Cooperative Extension, the Department of Water Resources, and the Bureau of Reclamation, 2000. www.owue.water.ca.gov/docs/wucols00