



SUTTER COUNTY
COMMUNITY SERVICES DEPARTMENT

Planning – Lisa Wilson, Planning Division Chief
Animal Control
Building Inspection
Environmental Health

Director – Larry Bagley
Assistant Director – Randy Cagle
Fire Services – Dan Yager
Emergency Services – John DeBeaux

January 13, 2010

Mr. Simon Eching
California Department of Water Resource
Water Use and Efficiency Branch
Post Office Box 942836
Sacramento CA 94236-0001

Re: Adopted Water Efficiency Landscape Ordinance

Dear Mr. Eching,

This letter is to provide the required timely response that Sutter County has adopted a modified version of the State's MWEL. The Sutter County Board of Supervisors adopted a modified version of the MWEL on December 29, 2009. The modifications are:

- Formatted to comply with the Sutter County Code numbering system.
- Modified to eliminate references to a "landscape permit" since we do not have such a permit.
- Deleted §492.17 Environmental Review since our design review permit process is subject to CEQA.
- Appendix "A"-Reference ETo Table was shortened to reflect only this County and contiguous jurisdictions.

If you have any questions, please let me know.

Sincerely,

A handwritten signature in cursive script that reads "Lisa".

Lisa Wilson
Planning Division Chief


LW:kf
Enclosure: Ordinance #1524

P:\Planning\Projects\2009\09-030 (Sutter County water ord)\Correspondence\DWR letter of our adoption.doc

JAN 04 2010

ORDINANCE NO. 1524

**AN ORDINANCE OF THE COUNTY OF SUTTER
AMENDING CHAPTER 15 OF THE ORDINANCE CODE BY ADDING DIVISION 87
THE WATER EFFICIENT LANDSCAPE REQUIREMENTS**

DONNA M. JOHNSON, County Clerk and
ex-officio Clerk of the Board of Supervisors of the
State of California and for the County of Sutter
By  Deputy

WHEREAS, The State Legislature has found the waters of the state are of limited supply, subject to ever increasing demands and California's economic prosperity is dependent on the availability of adequate supplies of water for future uses. It is the policy of the State to promote the conservation and efficient use of water and to prevent the waste of this valuable resource; and that landscape design, installation, maintenance and management can and should be water efficient; and

WHEREAS, consistent with the Legislature, the purpose of this ordinance is to: recognize the need to invest water and other resources as efficiently as possible; establish a structure for planning, designing, installing, maintaining and managing water efficient landscapes in new construction and rehabilitated projects; establish provisions for water management practices and water waste prevention for existing landscapes; use water efficiently without waste by setting a Maximum Applied Water Allowance as an upper limit for water use and reduce water use to the lowest practical amount; and encourage the efficient use of water; and

WHEREAS, the California Department of Water Resources released a Model Water Efficient Landscape Ordinance for cities and counties to adopt as-is or to use as a reference for an equally or more restrictive ordinance; and

WHEREAS, if a city or county does not adopt its own ordinance, the State's Model Water Efficient Landscape Ordinance shall become a local agency's ordinance. In adopting its own ordinance, cities and counties are restricted to only making the State's Model Water Efficient Landscape Ordinance more restrictive, not less; and

WHEREAS, Chapter 15, Division 2 of the Sutter County Code provides the process and procedures for all zoning amendments in Sutter County; and

WHEREAS, The Board of Supervisors has reviewed and considered the proposed ordinance and finds that it is covered by the general rule of the California Environmental Quality Act (CEQA), Section 15061b(3) of the Guidelines that states that CEQA only applies to projects that have the potential for causing a significant effect on the environment. Where it can be seen with certainty there is no possibility that an activity in question may have a significant effect on the environment, the activity is not subject to CEQA. This proposed ordinance will encourage the efficient use of water in new construction and rehabilitated projects to reduce water consumption as determined by the legislature. As a result, this Water Efficient Landscape Ordinance will not have any impact upon the environment and therefore is not subject to CEQA; and

WHEREAS, on December 16, 2009, the Planning Commission conducted a public hearing to consider adopting the proposed Amendment to the County Code and, upon the conclusion of the public hearing, recommended the Board of Supervisors adopt the Amendment to the County Code; and

WHEREAS, on December 29, 2009, the Board of Supervisors conducted a public hearing to consider adopting the proposed Amendment to the County Zoning Code, a notice of which was given as required by sections 65090-65092 of the Government Code.

NOW, THEREFORE, THE BOARD OF SUPERVISORS OF THE COUNTY OF SUTTER ORDAINS AS FOLLOWS:

Section 1: The preceding recitals are true and correct.

Section 2: Chapter 15, Division 87, of the Sutter County Code – Water Efficient Landscape Requirements is established as more particularly described in the attached EXHIBIT A.

Section 3: If any section, subsequent subdivision, paragraph, sentence, clause or phrase of this Ordinance is for any reason held to be unconstitutional or otherwise invalid, such a decision shall not affect the validity of the remaining portions of this Ordinance. The Board of Supervisors hereby declares that it would have passed each section, subsection, subdivision, paragraph, sentence, clause or phrase of this Ordinance irrespective of the unconstitutionality or invalidity of any section, subsection, subdivision, paragraph, sentence, clause or phrase.

Section 4: This Ordinance shall take legal effect and be in force thirty (30) days from and after the date of its passage.

Section 5: Within fifteen days of the adoption of this Ordinance, the County Clerk shall cause a copy of this Ordinance or summary thereof, to be published once in the Appeal Democrat, a newspaper of general circulation, published in Sutter County, State of California, along with a notice setting forth the date of adoption and the title of this Ordinance, and with the names of the members of the Sutter County Board of Supervisors voting for and against the same.

THIS ORDINANCE was regularly introduced at a meeting of the Board of Supervisors of the County of Sutter on the 29th day of December, 2009, and was PASSED AND ADOPTED at a regular meeting of the Board of Supervisors of the County of Sutter on this 29th day of December 2009, by the following vote:

AYES: Supervisors Montna, Cleveland, Munger, and Gallagher

NOES: Supervisor Whiteaker

ABSENT: None

ABSTAIN: None

ATTEST:

DONNA M. JOHNSTON, CLERK

By: Lisa B...
Deputy



Jim Whiteaker
Jim Whiteaker, Chairman of the Board

FILED

DEC 31 2009

BOARD OF SUPERVISORS
DONNA M. JOHNSTON
Clerk of the Board

By: Lisa B... Deputy

Ord. 1524

Page 39

December 29, 2009

Exhibit A of Ordinance No. 1524

DIVISION 87 WATER EFFICIENT LANDSCAPE REQUIREMENTS

1500-8710 Purpose:

The State Legislature has found the waters of the state are of limited supply, subject to ever increasing demands and California's economic prosperity is dependent on the availability of adequate supplies of water for future uses. It is the policy of the State to promote the conservation and efficient use of water and to prevent the waste of this valuable resource; and that landscape design, installation, maintenance and management can and should be water efficient.

Consistent with the Legislature, the purpose of this ordinance is to: recognize the need to invest water and other resources as efficiently as possible; establish a structure for planning, designing, installing, maintaining and managing water efficient landscapes in new construction and rehabilitated projects; establish provisions for water management practices and water waste prevention for existing landscapes; use water efficiently without waste by setting a Maximum Applied Water Allowance as an upper limit for water use and reduce water use to the lowest practical amount; and encourage the efficient use of water.

1500-8715 Applicability:

This ordinance shall apply to all of the following landscape projects:

- (a) New construction and rehabilitated landscapes for public agency projects and private development projects with a landscape area equal to or greater than 2,500 square feet requiring a building permit or design review;
- (b) New construction and rehabilitated landscapes which are developer-installed in single-family and multi-family projects with a landscape area equal to or greater than 2,500 square feet requiring a building permit, or design review;
- (c) New construction landscapes which are homeowner-provided and/or homeowner-hired in single-family and multi-family residential projects with a total project landscape area equal to or greater than 5,000 square feet requiring a building permit, design review;
- (d) Existing landscapes limited to Sections 1500-8810 and 1500-8815; and
- (e) Cemeteries. Recognizing the special landscape management needs of cemeteries, new and rehabilitated cemeteries are limited to Sections 1500-8745, 1500-8780 and 1500-8785; 1500-8810 and 1500-8815.

This ordinance does not apply to: Registered local, state or federal historical sites; ecological restoration projects that do not require a permanent irrigation system; mined-land reclamation projects that do not require a permanent irrigation system; or plant collections, as part of botanical gardens and arboretums open to the public.

1500-8720 Definitions:

The terms used in this ordinance have the meaning set forth below:

- (a) "applied water" means the portion of water supplied by the irrigation system to the landscape.

- (b) "automatic irrigation controller" means an automatic timing device used to remotely control valves that operate an irrigation system. Automatic irrigation controllers schedule irrigation events using either evapotranspiration (weather-based) or soil moisture data.
- (c) "backflow prevention device" means a safety device used to prevent pollution or contamination of the water supply due to the reverse flow of water from the irrigation system.
- (d) "Certificate of Completion" means the document required under Section 1500-8770.
- (e) "certified irrigation designer" means a person certified to design irrigation systems by an accredited academic institution a professional trade organization or other program such as the US Environmental Protection Agency's WaterSense irrigation designer certification program and Irrigation Association's Certified Irrigation Designer program.
- (f) "certified landscape irrigation auditor" means a person certified to perform landscape irrigation audits by an accredited academic institution, a professional trade organization or other program such as the US Environmental Protection Agency's WaterSense irrigation auditor certification program and Irrigation Association's Certified Landscape Irrigation Auditor program.
- (g) "check valve" or "anti-drain valve" means a valve located under a sprinkler head, or other location in the irrigation system, to hold water in the system to prevent drainage from sprinkler heads when the sprinkler is off.
- (h) "common interest developments" means community apartment projects, condominium projects, planned developments, and stock cooperatives per Civil Code Section 1351.
- (i) "conversion factor (0.62)" means the number that converts acre-inches per acre per year to gallons per square foot per year
- (j) "drip irrigation" means any non-spray low volume irrigation system utilizing emission devices with a flow rate measured in gallons per hour. Low volume irrigation systems are specifically designed to apply small volumes of water slowly at or near the root zone of plants.
- (k) "ecological restoration project" means a project where the site is intentionally altered to establish a defined, indigenous, historic ecosystem.
- (l) "effective precipitation" or "usable rainfall" (Eppt) means the portion of total precipitation which becomes available for plant growth.
- (m) "emitter" means a drip irrigation emission device that delivers water slowly from the system to the soil.
- (n) "established landscape" means the point at which plants in the landscape have developed significant root growth into the soil. Typically, most plants are established after one or two years of growth.
- (o) "establishment period of the plants" means the first year after installing the plant in the landscape or the first two years if irrigation will be terminated after establishment. Typically, most plants are established after one or two years of growth.
- (p) "Estimated Total Water Use" (ETWU) means the total water used for the landscape as described in Section 492.4.
- (q) "ET adjustment factor" (ETAF) means a factor of 0.7, that, when applied to reference evapotranspiration, adjusts for plant factors and irrigation efficiency, two major influences upon the amount of water that needs to be applied to the landscape.

A combined plant mix with a site-wide average of 0.5 is the basis of the plant factor portion of this calculation. For purposes of the ETAF, the average irrigation efficiency is 0.71. Therefore, the ET Adjustment Factor is $(0.7)=(0.5/0.71)$. ETAF for a Special Landscape Area shall not exceed 1.0. ETAF for existing non-rehabilitated landscapes is 0.8.

(r) "evapotranspiration rate" means the quantity of water evaporated from adjacent soil and other surfaces and transpired by plants during a specified time.

(s) "flow rate" means the rate at which water flows through pipes, valves and emission devices, measured in gallons per minute, gallons per hour, or cubic feet per second.

(t) "hardscapes" means any durable material (pervious and non-pervious).

(u) "homeowner-provided landscaping" means any landscaping either installed by a private individual for a single family residence or installed by a licensed contractor hired by a homeowner. A homeowner, for purposes of this ordinance, is a person who occupies the dwelling he or she owns. This excludes speculative homes, which are not owner-occupied dwellings.

(v) "hydrozone" means a portion of the landscaped area having plants with similar water needs. A hydrozone may be irrigated or non-irrigated.

(w) "infiltration rate" means the rate of water entry into the soil expressed as a depth of water per unit of time (e.g., inches per hour).

(x) "invasive plant species" means species of plants not historically found in California that spread outside cultivated areas and can damage environmental or economic resources. Invasive species may be regulated by county agricultural agencies as noxious species. "Noxious weeds" means any weed designated by the Weed Control Regulations in the Weed Control Act and identified on a Regional District noxious weed control list. Lists of invasive plants are maintained at the California Invasive Plant Inventory and USDA invasive and noxious weeds database.

(y) "irrigation audit" means an in-depth evaluation of the performance of an irrigation system conducted by a Certified Landscape Irrigation Auditor. An irrigation audit includes, but is not limited to: inspection, system tune-up, system test with distribution uniformity or emission uniformity, reporting overspray or runoff that causes overland flow, and preparation of an irrigation schedule.

(z) "irrigation efficiency" (IE) means the measurement of the amount of water beneficially used divided by the amount of water applied. Irrigation efficiency is derived from measurements and estimates of irrigation system characteristics and management practices. The minimum average irrigation efficiency for purposes of this ordinance is 0.71. Greater irrigation efficiency can be expected from well designed and maintained systems.

(aa) "irrigation survey" means an evaluation of an irrigation system that is less detailed than an irrigation audit. An irrigation survey includes, but is not limited to: inspection, system test, and written recommendations to improve performance of the irrigation system.

(bb) "irrigation water use analysis" means an analysis of water use data based on meter readings and billing data.

(cc) "landscape architect" means a person who holds a license to practice landscape architecture in the state of California Business and Professions Code, Section 5615.

(dd) "landscape area" means all the planting areas, turf areas, and water features in a landscape design plan subject to the Maximum Applied Water Allowance calculation. The landscape area does not include footprints of buildings or structures, sidewalks, driveways, parking lots, decks, patios, gravel or stone walks, other pervious or non-pervious hardscapes, and other non-irrigated areas designated for non-development (e.g., open spaces and existing native vegetation).

(ee) "landscape contractor" means a person licensed by the state of California to construct, maintain, repair, install, or subcontract the development of landscape systems.

(ff) "Landscape Documentation Package" means the documents required under Section 1500-8740.

(gg) "landscape project" means total area of landscape in a project as defined in "landscape area" for the purposes of this ordinance, meeting requirements under Section 1500-8715.

(hh) "lateral line" means the water delivery pipeline that supplies water to the emitters or sprinklers from the valve.

(ii) "local agency" means a city or county, including a charter city or charter county, that is responsible for adopting and implementing the ordinance. The local agency is also responsible for the enforcement of this ordinance, including but not limited to, approval of a permit or design review of a project.

(jj) "local water purveyor" means any entity, including a public agency, city, county, or private water company that provides retail water service.

(kk) "low volume irrigation" means the application of irrigation water at low pressure through a system of tubing or lateral lines and low-volume emitters such as drip, drip lines, and bubblers. Low volume irrigation systems are specifically designed to apply small volumes of water slowly at or near the root zone of plants.

(ll) "main line" means the pressurized pipeline that delivers water from the water source to the valve or outlet.

(mm) "Maximum Applied Water Allowance" (MAWA) means the upper limit of annual applied water for the established landscaped area as specified in Section 492.4. It is based upon the area's reference evapotranspiration, the ET Adjustment Factor, and the size of the landscape area. The Estimated Total Water Use shall not exceed the Maximum Applied Water Allowance. Special Landscape Areas, including recreation areas, areas permanently and solely dedicated to edible plants such as orchards and vegetable gardens, and areas irrigated with recycled water are subject to the MAWA with an ETAF not to exceed 1.0.

(nn) "microclimate" means the climate of a small, specific area that may contrast with the climate of the overall landscape area due to factors such as wind, sun exposure, plant density, or proximity to reflective surfaces.

(oo) "mined-land reclamation projects" means any surface mining operation with a reclamation plan approved in accordance with the Surface Mining and Reclamation Act of 1975.

(pp) "mulch" means any organic material such as leaves, bark, straw, compost, or inorganic mineral materials such as rocks, gravel, and decomposed granite left loose and applied to the soil surface for the beneficial purposes of reducing evaporation, suppressing weeds, moderating soil temperature, and preventing soil erosion.

(qq) "new construction" means, for the purposes of this ordinance, a new building with a landscape or other new landscape, such as a park, playground, or greenbelt without an associated building.

(rr) "operating pressure" means the pressure at which the parts of an irrigation system are designed by the manufacturer to operate.

(ss) "overhead sprinkler irrigation systems" means systems that deliver water through the air (e.g., spray heads and rotors).

- (tt) "overspray" means the irrigation water which is delivered beyond the target area.
- (uu) "permit" means an authorizing document issued by local agencies for new construction or rehabilitated landscapes.
- (vv) "pervious" means any surface or material that allows the passage of water through the material and into the underlying soil.
- (ww) "plant factor" or "plant water use factor" is a factor , when multiplied by ETo, estimates the amount of water needed by plants. For purposes of this ordinance, the plant factor range for low water use plants is 0 to 0.3, the plant factor range for moderate water use plants is 0.4 to 0.6, and the plant factor range for high water use plants is 0.7 to 1.0. Plant factors cited in this ordinance are derived from the Department of Water Resources 2000 publication "Water Use Classification of Landscape Species".
- (xx) "precipitation rate" means the rate of application of water measured in inches per hour.
- (yy) "project applicant" means the individual or entity submitting a Landscape Documentation Package required under Section 1500-8740, to request a permit, or design review from the local agency. A project applicant may be the property owner or his or her designee.
- (zz) "rain sensor" or "rain sensing shutoff device" means a component which automatically suspends an irrigation event when it rains.
- (aaa) "record drawing" or "as-builts" means a set of reproducible drawings which show significant changes in the work made during construction and which are usually based on drawings marked up in the field and other data furnished by the contractor.
- (bbb) "recreational area" means areas dedicated to active play such as parks, sports fields, and golf courses where turf provides a playing surface.
- (ccc) "recycled water", "reclaimed water", or "treated sewage effluent water" means treated or recycled waste water of a quality suitable for non-potable uses such as landscape irrigation and water features. This water is not intended for human consumption.
- (ddd) "reference evapotranspiration" or "ETo" means a standard measurement of environmental parameters which affect the water use of plants. ETo is expressed in inches per day, month, or year as represented in Appendix A, and is an estimate of the evapotranspiration of a large field of four- to seven-inch tall, cool-season grass that is well watered. Reference evapotranspiration is used as the basis of determining the Maximum Applied Water Allowance so that regional differences in climate can be accommodated.
- (eee) "rehabilitated landscape" means any re-landscaping project that requires a permit , plan check, or design review, meets the requirements of Section 1500-8715, and the modified landscape area is equal to or greater than 2,500 square feet, is 50% of the total landscape area, and the modifications are completed within one year.
- (fff) "runoff" means water which is not absorbed by the soil or landscape to which it is applied and flows from the landscape area. For example, runoff may result from water that is applied at too great a rate (application rate exceeds infiltration rate) or when there is a slope.
- (ggg) "soil moisture sensing device" or "soil moisture sensor" means a device that measures the amount of water in the soil. The device may also suspend or initiate an irrigation event.
- (hhh) "soil texture" means the classification of soil based on its percentage of sand, silt, and clay.
- (iii) "Special Landscape Area" (SLA) means an area of the landscape dedicated solely to edible plants, areas irrigated with recycled water, water features using recycled water and areas

dedicated to active play such as parks, sports fields, golf courses, and where turf provides a playing surface.

(jjj) "sprinkler head" means a device which delivers water through a nozzle.

(kkk) "static water pressure" means the pipeline or municipal water supply pressure when water is not flowing.

(lll) "station" means an area served by one valve or by a set of valves that operate simultaneously.

(mmm) "swing joint" means an irrigation component that provides a flexible, leak-free connection between the emission device and lateral pipeline to allow movement in any direction and to prevent equipment damage.

(nnn) "turf" means a ground cover surface of mowed grass. Annual bluegrass, Kentucky bluegrass, Perennial ryegrass, Red fescue, and Tall fescue are cool-season grasses. Bermudagrass, Kikuyugrass, Seashore Paspalum, St. Augustinegrass, Zoysiagrass, and Buffalo grass are warm-season grasses.

(ooo) "valve" means a device used to control the flow of water in the irrigation system.

(ppp) "water conserving plant species" means a plant species identified as having a low plant factor.

(qqq) "water feature" means a design element where open water performs an aesthetic or recreational function. Water features include ponds, lakes, waterfalls, fountains, artificial streams, spas, and swimming pools (where water is artificially supplied). The surface area of water features is included in the high water use hydrozone of the landscape area. Constructed wetlands used for on-site wastewater treatment or stormwater best management practices that are not irrigated and used solely for water treatment or stormwater retention are not water features and, therefore, are not subject to the water budget calculation.

(rrr) "watering window" means the time of day irrigation is allowed.

(sss) "WUCOLS" means the Water Use Classification of Landscape Species published by the University of California Cooperative Extension, the Department of Water Resources and the Bureau of Reclamation, 2000.

1500-8725 Provisions for New Construction or Rehabilitated Landscapes:

A local agency may designate another agency, such as a water purveyor, to implement some or all of the requirements contained in this ordinance. Local agencies may collaborate with water purveyors to define each entity's specific responsibilities relating to this ordinance.

1500-8730 Compliance with Landscape Documentation Package:

(a) Prior to construction, the local agency shall:

- (1) provide the project applicant with the ordinance and procedures for permits, plan checks, or design reviews;
- (2) review the Landscape Documentation Package submitted by the project applicant;
- (3) approve or deny the Landscape Documentation Package;
- (4) issue a permit or approve the plan check or design review for the project applicant;
- (5) upon approval of the Landscape Documentation Package, submit a copy of the Water Efficient Landscape Worksheet to the local water purveyor.

(b) Prior to construction, the project applicant shall submit a Landscape Documentation Package to the local agency.

(c) Upon approval of the Landscape Documentation Package by the local agency, the project applicant shall:

- (1) receive a permit or approval of the design review and record the date of the permit in the Certificate of Completion;
- (2) submit a copy of the approved Landscape Documentation Package along with the record drawings, and any other information to the property owner or his/her designee; and
- (3) submit a copy of the Water Efficient Landscape Worksheet to the local water purveyor.

1500-8735 Penalties:

The local agency may establish and administer penalties to the project applicant for non-compliance with the ordinance to the extent permitted by law.

1500-8740 Elements of the Landscape Documentation Package:

The Landscape Documentation Package shall include the following six (6) elements:

- (1) Project information;
 - (A) date
 - (B) project applicant
 - (C) project address (if available, parcel and/or lot number(s))
 - (D) total landscape area (square feet)
 - (E) project type (e.g., new, rehabilitated, public, private, cemetery, homeowner-installed)
 - (F) water supply type (e.g., potable, recycled, well) and identify the local retail water purveyor if the applicant is not served by a private well
 - (G) checklist of all documents in Landscape Documentation Package
 - (H) project contacts to include contact information for the project applicant and property owner
 - (I) applicant signature and date with statement, "I agree to comply with the requirements of the water efficient landscape ordinance and submit a complete Landscape Documentation Package".
- (2) Water Efficient Landscape Worksheet;
 - (A) hydrozone information table
 - (B) water budget calculations
 1. Maximum Applied Water Allowance (MAWA)
 2. Estimated Total Water Use (ETWU)
- (3) Soil management report;
- (4) Landscape design plan;
- (5) Irrigation design plan; and
- (6) Grading design plan.

1500-8745 Water Efficient Landscape Worksheet:

(a) A project applicant shall complete the Water Efficient Landscape Worksheet which contains two sections (see sample worksheet in Appendix B):

- (1) a hydrozone information table (see Appendix B, Section A) for the landscape project; and
- (2) a water budget calculation (see Appendix B, Section B) for the landscape project. For the calculation of the Maximum Applied Water Allowance and Estimated Total Water Use, a project applicant shall use the ETo values from the Reference Evapotranspiration Table in Appendix A. For geographic areas not covered in Appendix A, use data from other

cities located nearby in the same reference evapotranspiration zone, as found in the CIMIS Reference Evapotranspiration Zones Map, Department of Water Resources, 1999.

(b) Water budget calculations shall adhere to the following requirements:

- (1) The plant factor used shall be from WUCOLS. The plant factor ranges from 0 to 0.3 for low water use plants, from 0.4 to 0.6 for moderate water use plants, and from 0.7 to 1.0 for high water use plants.
- (2) All water features shall be included in the high water use hydrozone and temporarily irrigated areas shall be included in the low water use hydrozone.
- (3) All Special Landscape Areas shall be identified and their water use calculated as described below.
- (4) ETAF for Special Landscape Areas shall not exceed 1.0.

(c) Maximum Applied Water Allowance

The Maximum Applied Water Allowance shall be calculated using the equation:

$$\text{MAWA} = (\text{ETo}) (0.62) [(0.7 \times \text{LA}) + (0.3 \times \text{SLA})]$$

The example calculations below are hypothetical to demonstrate proper use of the equations and do not represent an existing and/or planned landscape project. The ETo values used in these calculations are from the Reference Evapotranspiration Table in Appendix A, for planning purposes only. For actual irrigation scheduling, automatic irrigation controllers are required and shall use current reference evapotranspiration data, such as from the California Irrigation Management Information System (CIMIS), other equivalent data, or soil moisture sensor data.

(1) Example MAWA calculation: a hypothetical landscape project in Fresno, CA with an irrigated landscape area of 50,000 square feet without any Special Landscape Area (SLA= 0, no edible plants, recreational areas, or use of recycled water). To calculate MAWA, the annual reference evapotranspiration value for Fresno is 51.1 inches as listed in the Reference Evapotranspiration Table in Appendix A.

$$\begin{aligned} \text{MAWA} &= (\text{ETo}) (0.62) [(0.7 \times \text{LA}) + (0.3 \times \text{SLA})] \\ \text{MAWA} &= \text{Maximum Applied Water Allowance (gallons per year)} \\ \text{ETo} &= \text{Reference Evapotranspiration (inches per year)} \\ 0.62 &= \text{Conversion Factor (to gallons)} \\ 0.7 &= \text{ET Adjustment Factor (ETAF)} \\ \text{LA} &= \text{Landscape Area including SLA (square feet)} \\ 0.3 &= \text{Additional Water Allowance for SLA} \\ \text{SLA} &= \text{Special Landscape Area (square feet)} \\ \text{MAWA} &= (51.1 \text{ inches}) (0.62) [(0.7 \times 50,000 \text{ square feet}) + (0.3 \times 0)] \\ &= 1,108,870 \text{ gallons per year} \\ &\text{To convert from gallons per year to hundred-cubic-feet per year:} \\ &= 1,108,870/748 = 1,482 \text{ hundred-cubic-feet per year} \\ &(100 \text{ cubic feet} = 748 \text{ gallons}) \end{aligned}$$

(2) In this next hypothetical example, the landscape project in Fresno, CA has the same ETo value of 51.1 inches and a total landscape area of 50,000 square feet. Within the 50,000 square foot project, there is now a 2,000 square foot area planted with edible plants. This 2,000 square foot area is considered to be a Special Landscape Area.

$$\begin{aligned} \text{MAWA} &= (\text{ETo}) (0.62) [(0.7 \times \text{LA}) + (0.3 \times \text{SLA})] \\ \text{MAWA} &= (51.1 \text{ inches}) (0.62) [(0.7 \times 50,000 \text{ square feet}) + (0.3 \times 2,000 \text{ square feet})] \\ &= 31.68 \times [35,000 + 600] \text{ gallons per year} \\ &= 31.68 \times 35,600 \text{ gallons per year} \\ &= 1,127,808 \text{ gallons per year or } 1,508 \text{ hundred-cubic-feet per year} \end{aligned}$$

(d) **Estimated Total Water Use.**

The Estimated Total Water Use shall be calculated using the equation below. The sum of the Estimated Total Water Use calculated for all hydrozones shall not exceed MAWA.

$$ETWU = (ETo)(0.62) \left(\frac{PF \times HA}{IE} + SLA \right)$$

Where:

- ETWU = Estimated Total Water Use per year (gallons)
- ETo = Reference Evapotranspiration (inches)
- PF = Plant Factor from WUCOLS (see Section 491)
- HA = Hydrozone Area [high, medium, and low water use areas] (square feet)
- SLA = Special Landscape Area (square feet)
- 0.62 = Conversion Factor
- IE = Irrigation Efficiency (minimum 0.71)

- (1) **Example ETWU calculation: landscape area is 50,000 square feet; plant water use type, plant factor, and hydrozone area are shown in the table below. The ETo value is 51.1 inches per year. There are no Special Landscape Areas (recreational area, area permanently and solely dedicated to edible plants, and area irrigated with recycled water) in this example.**

Hydrozone	Plant Water Use Type(s)	Plant Factor (PF)*	Hydrozone Area (HA) (square feet)	PF x HA (square feet)
1	High	0.8	7,000	5,600
2	High	0.7	10,000	7,000
3	Medium	0.5	16,000	8,000
4	Low	0.3	7,000	2,100
5	Low	0.2	10,000	2,000
			Sum	24,700

*Plant Factor from WUCOLS

$$ETWU = (51.1)(0.62) \left(\frac{24,700}{0.71} + 0 \right)$$

= 1,102,116 gallons per year

Compare ETWU with MAWA: For this example MAWA = (51.1) (0.62) [(0.7 x 50,000) + (0.3 x 0)] = 1,108,870 gallons per year. The ETWU (1,102,116 gallons per year) is less than MAWA (1,108,870 gallons per year). In this example, the water budget complies with the MAWA.

- (2) **Example ETWU calculation: total landscape area is 50,000 square feet, 2,000 square feet of which is planted with edible plants. The edible plant area is considered a Special Landscape Area (SLA). The reference evapotranspiration value is 51.1 inches per year. The plant type, plant factor, and hydrozone area are shown in the table below.**

Hydrozone	Plant Water Use Type(s)	Plant Factor (PF)*	Hydrozone Area (HA) (square feet)	PF x HA (square feet)
1	High	0.8	7,000	5,600
2	High	0.7	9,000	6,300
3	Medium	0.5	15,000	7,500
4	Low	0.3	7,000	2,100
5	Low	0.2	10,000	2,000
			Sum	23,500
6	SLA	1.0	2,000	2,000

*Plant Factor from WUCOLS

$$ETWU = (51.1)(0.62) \left(\frac{23,500}{0.71} + 2,000 \right)$$

$$= (31.68) (33,099 + 2,000)$$

$$= 1,111,936 \text{ gallons per year}$$

Compare ETWU with MAWA. For this example:

$$MAWA = (51.1) (0.62) [(0.7 \times 50,000) + (0.3 \times 2,000)]$$

$$= 31.68 \times [35,000 + 600]$$

$$= 31.68 \times 35,600$$

$$= 1,127,808 \text{ gallons per year}$$

The ETWU (1,111,936 gallons per year) is less than MAWA (1,127,808 gallons per year). For this example, the water budget complies with the MAWA.

1500-8750 Soil Management Report:

In order to reduce runoff and encourage healthy plant growth, a soil management report shall be completed by the project applicant, or his/her designee, as follows:

- (a) Submit soil samples to a laboratory for analysis and recommendations.
 - (1) Soil sampling shall be conducted in accordance with laboratory protocol, including protocols regarding adequate sampling depth for the intended plants.
 - (2) The soil analysis may include:
 - A. soil texture;
 - B. infiltration rate determined by laboratory test or soil texture infiltration rate table;
 - C. pH;
 - D. total soluble salts;
 - E. sodium;
 - F. percent organic matter; and
 - G. recommendations.
- (b) The project applicant, or his/her designee, shall comply with one of the following:

- (1) If significant mass grading is not planned, the soil analysis report shall be submitted to the local agency as part of the Landscape Documentation Package;
or
- (2) If significant mass grading is planned, the soil analysis report shall be submitted to the local agency as part of the Certificate of Completion.

(c) The soil analysis report shall be made available, in a timely manner, to the professionals preparing the landscape design plans and irrigation design plans to make any necessary adjustments to the design plans.

(d) The project applicant, or his/her designee, shall submit documentation verifying implementation of soil analysis report recommendations to the local agency with Certificate of Completion.

1500-8755 Landscape Design Plan:

(a) For the efficient use of water, a landscape shall be carefully designed and planned for the intended function of the project. A landscape design plan meeting the following design criteria shall be submitted as part of the Landscape Documentation Package.

(1) **Plant Material:**

(A) Any plant may be selected for the landscape, providing the Estimated Total Water Use in the landscape area does not exceed the Maximum Applied Water Allowance. To encourage the efficient use of water, the following is highly recommended:

1. Protection and preservation of native species and natural vegetation;
2. Selection of water-conserving plant and turf species;
3. Selection of plants based on disease and pest resistance;
4. Selection of trees based on applicable local tree ordinances or tree shading guidelines; and
5. Selection of plants from local and regional landscape program plant

lists.

(B) Each hydrozone shall have plant materials with similar water use, with the exception of hydrozones with plants of mixed water use, as specified in Section 1500-8760(a)(2)(D).

(C) Plants shall be selected and planted appropriately based upon their adaptability to the climatic, geologic, and topographical conditions of the project site. To encourage the efficient use of water, the following is highly recommended:

1. Use the Sunset Western Climate Zone System which takes into account temperature, humidity, elevation, terrain, latitude, and varying degrees of continental and marine influence on local climate;
2. Recognize the horticultural attributes of plants (i.e., mature plant size, invasive surface roots) to minimize damage to property or infrastructure [e.g., buildings, sidewalks, power lines]; and
3. Consider the solar orientation for plant placement to maximize summer shade and winter solar gain.

(D) Turf is not allowed on slopes greater than 25% where the toe of the slope is adjacent to an impermeable hardscape and where 25% means 1 foot of vertical elevation change for every 4 feet of horizontal length (rise divided by run x 100 = slope percent).

(E) A landscape design plan for projects in fire-prone areas shall address fire safety and prevention. A defensible space or zone around a building or structure is required per Public Resources Code Section 4291(a) and (b). Avoid fire-prone plant materials and highly flammable mulches.

(F) The use of invasive and/or noxious plant species is strongly discouraged.

(G) The architectural guidelines of a common interest development, which include community apartment projects, condominiums, planned developments, and stock cooperatives, shall not prohibit or include conditions that have the effect of prohibiting the use of low-water use plants as a group.

(2) Water Features

(A) Recirculating water systems shall be used for water features.

(B) Where available, recycled water shall be used as a source for decorative water features.

(C) Surface area of a water feature shall be included in the high water use hydrozone area of the water budget calculation.

(D) Pool and spa covers are highly recommended.

(3) Mulch and Amendments

(A) A minimum two inch (2") layer of mulch shall be applied on all exposed soil surfaces of planting areas except in turf areas, creeping or rooting groundcovers, or direct seeding applications where mulch is contraindicated.

(B) Stabilizing mulching products shall be used on slopes.

(C) The mulching portion of the seed/mulch slurry in hydro-seeded applications shall meet the mulching requirement.

(D) Soil amendments shall be incorporated according to recommendations of the soil report and what is appropriate for the plants selected (see Section 1500-8750).

(b) The landscape design plan, at a minimum, shall:

(1) Delineate and label each hydrozone by number, letter, or other method;

(2) Identify each hydrozone as low, moderate, high water, or mixed water use. Temporarily irrigated areas of the landscape shall be included in the low water use hydrozone for the water budget calculation;

(3) Identify recreational areas;

(4) Identify areas permanently and solely dedicated to edible plants;

(5) Identify areas irrigated with recycled water;

(6) Identify type of mulch and application depth;

(7) Identify soil amendments, type, and quantity;

(8) Identify type and surface area of water features;

(9) Identify hardscapes (pervious and non-pervious);

(10) Identify location and installation details of any applicable stormwater best management practices that encourage on-site retention and infiltration of stormwater. Stormwater best management practices are encouraged in the landscape design plan and examples include, but are not limited to:

(A) Infiltration beds, swales, and basins that allow water to collect and soak into the ground;

(B) Constructed wetlands and retention ponds that retain water, handle excess flow, and filter pollutants; and

(C) Pervious or porous surfaces (e.g., permeable pavers or blocks, pervious or porous concrete, etc.) that minimize runoff.

- (11) Identify any applicable rain harvesting or catchment technologies (e.g., rain gardens, cisterns, etc.);
- (12) Contain the following statement: "I have complied with the criteria of the ordinance and applied them for the efficient use of water in the landscape design plan"; and
- (13) Bear the signature of a licensed landscape architect, licensed landscape contractor, or any other person authorized to design a landscape. (See Sections 5500.1, 5615, 5641, 5641.1, 5641.2, 5641.3, 5641.4, 5641.5, 5641.6, 6701, 7027.5 of the Business and Professions Code, Section 832.27 of Title 16 of the California Code of Regulations, and Section 6721 of the Food and Agriculture Code.)

1500-8760 Irrigation Design Plan:

(a) For the efficient use of water, an irrigation system shall meet all the requirements listed in this section and the manufacturers' recommendations. The irrigation system and its related components shall be planned and designed to allow for proper installation, management, and maintenance. An irrigation design plan meeting the following design criteria shall be submitted as part of the Landscape Documentation Package.

(1) **System**

(A) Dedicated landscape water meters are highly recommended on landscape areas smaller than 5,000 square feet to facilitate water management.

(B) Automatic irrigation controllers utilizing either evapotranspiration or soil moisture sensor data shall be required for irrigation scheduling in all irrigation systems.

(C) The irrigation system shall be designed to ensure that the dynamic pressure at each emission device is within the manufacturer's recommended pressure range for optimal performance.

1. If the static pressure is above or below the required dynamic pressure of the irrigation system, pressure-regulating devices such as inline pressure regulators, booster pumps, or other devices shall be installed to meet the required dynamic pressure of the irrigation system.

2. Static water pressure, dynamic or operating pressure, and flow reading of the water supply shall be measured at the point of connection. These pressure and flow measurements shall be conducted at the design stage. If the measurements are not available at the design stage, the measurements shall be conducted at installation.

(D) Sensors (rain, freeze, wind, etc.), either integral or auxiliary, that suspend or alter irrigation operation during unfavorable weather conditions shall be required on all irrigation systems, as appropriate for local climatic conditions. Irrigation should be avoided during windy or freezing weather or during rain.

(E) Manual shut-off valves (such as a gate valve, ball valve, or butterfly valve) shall be required, as close as possible to the point of connection of the water supply, to minimize water loss in case of an emergency (such as a main line break) or routine repair.

(F) Backflow prevention devices shall be required to protect the water supply from contamination by the irrigation system. A project applicant shall refer to the applicable local agency code (i.e., public health) for additional backflow prevention requirements.

(G) High flow sensors that detect and report high flow conditions created by system damage or malfunction are recommended.

(H) The irrigation system shall be designed to prevent runoff, low head drainage, overspray, or other similar conditions where irrigation water flows onto non-targeted areas, such as adjacent property, non-irrigated areas, hardscapes, roadways, or structures.

(I) Relevant information from the soil management plan, such as soil type and infiltration rate, shall be utilized when designing irrigation systems.

(J) The design of the irrigation system shall conform to the hydrozones of the landscape design plan.

(K) The irrigation system must be designed and installed to meet, at a minimum, the irrigation efficiency criteria as described in Section 1500-8745 regarding the Maximum Applied Water Allowance.

(L) It is highly recommended that the project applicant or local agency inquire with the local water purveyor about peak water operating demands (on the water supply system) or water restrictions that may impact the effectiveness of the irrigation system.

(M) In mulched planting areas, the use of low volume irrigation is required to maximize water infiltration into the root zone.

(N) Sprinkler heads and other emission devices shall have matched precipitation rates, unless otherwise directed by the manufacturer's recommendations.

(O) Head to head coverage is recommended. However, sprinkler spacing shall be designed to achieve the highest possible distribution uniformity using the manufacturer's recommendations.

(P) Swing joints or other riser-protection components are required on all risers subject to damage that are adjacent to high traffic areas.

(Q) Check valves or anti-drain valves are required for all irrigation systems.

(R) Narrow or irregularly shaped areas, including turf, less than eight (8) feet in width in any direction shall be irrigated with subsurface irrigation or low volume irrigation system.

(S) Overhead irrigation shall not be permitted within 24 inches of any non-permeable surface. Allowable irrigation within the setback from non-permeable surfaces may include drip, drip line, or other low flow non-spray technology. The setback area may be planted or unplanted. The surfacing of the setback may be mulch, gravel, or other porous material. These restrictions may be modified if:

1. The landscape area is adjacent to permeable surfacing and no runoff occurs; or
2. The adjacent non-permeable surfaces are designed and constructed to drain entirely to landscaping; or
3. The irrigation designer specifies an alternative design or technology, as part of the Landscape Documentation Package and clearly demonstrates strict adherence to irrigation system design criteria in Section 1500-8760 (a)(1)(H). Prevention of overspray and runoff must be confirmed during the irrigation audit.

(T) Slopes greater than 25% shall not be irrigated with an irrigation system with a precipitation rate exceeding 0.75 inches per hour. This restriction may be modified if the landscape designer specifies an alternative design or technology, as part of the Landscape Documentation Package, and clearly demonstrates no runoff or erosion will occur. Prevention of runoff and erosion must be confirmed during the irrigation audit.

(2) Hydrozone

(A) Each valve shall irrigate a hydrozone with similar site, slope, sun exposure, soil conditions, and plant materials with similar water use.

(B) Sprinkler heads and other emission devices shall be selected based on what is appropriate for the plant type within that hydrozone.

(C) Where feasible, trees shall be placed on separate valves from shrubs, groundcovers, and turf.

(D) Individual hydrozones that mix plants of moderate and low water use, or moderate and high water use, may be allowed if:

1. Plant factor calculation is based on the proportions of the respective plant water uses and their plant factor; or
2. The plant factor of the higher water using plant is used for calculations.

(E) Individual hydrozones that mix high and low water use plants shall not be permitted.

(F) On the landscape design plan and irrigation design plan, hydrozone areas shall be designated by number, letter, or other designation. On the irrigation design plan, designate the areas irrigated by each valve, and assign a number to each valve. Use this valve number in the Hydrozone Information Table (see Appendix B Section A). This table can also assist with the irrigation audit and programming the controller.

(b) The irrigation design plan, at a minimum, shall contain:

- (1) Location and size of separate water meters for landscape;
- (2) Location, type and size of all components of the irrigation system, including controllers, main and lateral lines, valves, sprinkler heads, moisture sensing devices, rain switches, quick couplers, pressure regulators, and backflow prevention devices;
- (3) Static water pressure at the point of connection to the public water supply;
- (4) Flow rate (gallons per minute), application rate (inches per hour), and design operating
- (5) Recycled water irrigation systems as specified in Section 1500-8795;
- (6) The following statement: "I have complied with the criteria of the ordinance and applied them accordingly for the efficient use of water in the irrigation design plan"; and
- (7) The signature of a licensed landscape architect, certified irrigation designer, licensed landscape contractor, or any other person authorized to design an irrigation system. (See Sections 5500.1, 5615, 5641, 5641.1, 5641.2, 5641.3, 5641.4, 5641.5, 5641.6,

6701, 7027.5 of the Business and Professions Code, Section 832.27 of Title 16 of the California Code of Regulations, and Section 6721 of the Food and Agricultural Code.)

1500-8765 Grading Design Plan:

(a) For the efficient use of water, grading of a project site shall be designed to minimize soil erosion, runoff, and water waste. A grading plan shall be submitted as part of the Landscape Documentation Package.

(1) The project applicant shall submit a landscape grading plan that indicates finished configurations and elevations of the landscape area including:

- (A) height of graded slopes;
- (B) drainage patterns;
- (C) pad elevations;
- (D) finish grade; and
- (E) stormwater retention improvements, if applicable.

(2) To prevent excessive erosion and runoff, it is highly recommended that project applicants:

- (A) Grade so that all irrigation and normal rainfall remains within property lines and does not drain on to non-permeable hardscapes;
- (B) Avoid disruption of natural drainage patterns and undisturbed soil; and
- (C) Avoid soil compaction in landscape areas.

(3) The grading design plan shall contain the following statement: "I have complied with the criteria of the ordinance and applied them accordingly for the efficient use of water in the grading design plan" and shall bear the signature of a licensed professional as authorized by law.

1500-8770 Certificate of Completion:

(a) The Certificate of Completion (see Appendix C for a sample certificate) shall include the following six (6) elements:

(1) Project information sheet that contains:

- (A) Date;
- (B) Project name;
- (C) Project applicant name, telephone, and mailing address;
- (D) Project address and location; and
- (E) Property owner name, telephone, and mailing address;

(2) Certification by either the signer of the landscape design plan, the signer of the irrigation design plan, or the licensed landscape contractor that the landscape project has been installed per the approved Landscape Documentation Package;

(A) Where there have been significant changes made in the field during construction, these "as-built" or record drawings shall be included with the certification;

(3) Irrigation scheduling parameters used to set the controller (see Section 1500-8775);

(4) Landscape and irrigation maintenance schedule (see Section 1500-8780);

(5) Irrigation audit report (see Section 1500-8785); and

(6) Soil analysis report, if not submitted with Landscape Documentation Package, and documentation verifying implementation of soil report recommendations (see Section 1500-8750).

(b) The project applicant shall:

- (1) Submit the signed Certificate of Completion to the local agency for review;
- (2) Ensure that copies of the approved Certificate of Completion are submitted to the local water purveyor and property owner or his or her designee.

(c) The local agency shall:

- (1) Receive the signed Certificate of Completion from the project applicant;
- (2) Approve or deny the Certificate of Completion. If the Certificate of Completion is denied, the local agency shall provide information to the project applicant regarding reapplication, appeal, or other assistance.

1500-8775 Irrigation Scheduling:

(a) For the efficient use of water, all irrigation schedules shall be developed, managed, and evaluated to utilize the minimum amount of water required to maintain plant health. Irrigation schedules shall meet the following criteria:

- (1) Irrigation scheduling shall be regulated by automatic irrigation controllers.
- (2) Overhead irrigation shall be scheduled between 8:00 p.m. and 10:00 a.m. unless weather conditions prevent it. If allowable hours of irrigation differ from the local water purveyor, the stricter of the two shall apply. Operation of the irrigation system outside the normal watering window is allowed for auditing and system maintenance.
- (3) For implementation of the irrigation schedule, particular attention must be paid to irrigation run times, emission device, flow rate, and current reference evapotranspiration, so that applied water meets the Estimated Total Water Use. Total annual applied water shall be less than or equal to Maximum Applied Water Allowance (MAWA). Actual irrigation schedules shall be regulated by automatic irrigation controllers using current reference evapotranspiration data (e.g., CIMIS) or soil moisture sensor data.
- (4) Parameters used to set the automatic controller shall be developed and submitted for each of the following:
 - (A) The plant establishment period;
 - (B) The established landscape; and
 - (C) Temporarily irrigated areas.
- (5) Each irrigation schedule shall consider for each station all of the following that apply:
 - (A) Irrigation interval (days between irrigation);
 - (B) Irrigation run times (hours or minutes per irrigation event to avoid runoff);
 - (C) Number of cycle starts required for each irrigation event to avoid runoff;
 - (D) Amount of applied water scheduled to be applied on a monthly basis;
 - (E) Application rate setting;
 - (F) Root depth setting;
 - (G) Plant type setting;
 - (H) Soil type;

- (I) Slope factor setting;
- (J) Shade factor setting; and
- (K) Irrigation uniformity or efficiency setting.

1500-8780 Landscape and Irrigation Maintenance Schedule:

- (a) Landscapes shall be maintained to ensure water use efficiency. A regular maintenance schedule shall be submitted with the Certificate of Completion.
- (b) A regular maintenance schedule shall include, but not be limited to, routine inspection; adjustment and repair of the irrigation system and its components; aerating and dethatching turf areas; replenishing mulch; fertilizing; pruning; weeding in all landscape areas, and removing and obstruction to emission devices. Operation of the irrigation system outside the normal watering window is allowed for auditing and system maintenance.
- (c) Repair of all irrigation equipment shall be done with the originally installed components or their equivalents.
- (d) A project applicant is encouraged to implement sustainable or environmentally-friendly practices for overall landscape maintenance.

1500-8785 Irrigation Audit, Irrigation Survey. And Irrigation Water Use Analysis:

- (a) All landscape irrigation audits shall be conducted by a certified landscape irrigation auditor.
- (b) For new construction and rehabilitated landscape projects installed after January 1, 2010, as described in Section 490.1:
 - (1) The project applicant shall submit an irrigation audit report with the Certificate of Completion to the local agency that may include, but is not limited to: inspection, system tune-up, system test with distribution uniformity, reporting overspray or run off that causes overland flow, and preparation of an irrigation schedule;
 - (2) The local agency shall administer programs that may include, but not be limited to, irrigation water use analysis, irrigation audits, and irrigation surveys for compliance with the Maximum Applied Water Allowance.

1500-8790 Irrigation Efficiency:

- (a) For the purpose of determining Maximum Applied Water Allowance, average irrigation efficiency is assumed to be 0.71. Irrigation systems shall be designed, maintained, and managed to meet or exceed an average landscape irrigation efficiency of 0.71.

1500-8795 Recycled Water:

- (a) The installation of recycled water irrigation systems shall allow for the current and future use of recycled water, unless a written exemption has been granted as described in Section 1500-8795(b).
- (b) Irrigation systems and decorative water features shall use recycled water unless a written exemption has been granted by the local water purveyor stating that recycled water meeting all public health codes and standards is not available and will not be available for the foreseeable future.
- (c) All recycled water irrigation systems shall be designed and operated in accordance with all applicable local and State laws.

(d) Landscapes using recycled water are considered Special Landscape Areas. The ET Adjustment Factor for Special Landscape Areas shall not exceed 1.0.

1500-8800 Stormwater Management:

(a) Stormwater management practices minimize runoff and increase infiltration which recharges groundwater and improves water quality. Implementing stormwater best management practices into the landscape and grading design plans to minimize runoff and to increase on-site retention and infiltration are encouraged.

(b) Project applicants shall refer to the local agency or Regional Water Quality Control Board for information on any applicable stormwater ordinances and stormwater management plans.

(c) Rain gardens, cisterns, and other landscapes features and practices that increase rainwater capture and create opportunities for infiltration and/or onsite storage are recommended.

1500-8805 Public Education:

(a) Publications. Education is a critical component to promote the efficient use of water in landscapes. The use of appropriate principles of design, installation, management and maintenance that save water is encouraged in the community.

(1) A local agency shall provide information to owners of new, single-family residential homes regarding the design, installation, management, and maintenance of water efficient landscapes.

(b) Model Homes. All model homes that are landscaped shall use signs and written information to demonstrate the principles of water efficient landscapes described in this ordinance.

(1) Signs shall be used to identify the model as an example of a water efficient landscape featuring elements such as hydrozones, irrigation equipment, and others that contribute to the overall water efficient theme.

(2) Information shall be provided about designing, installing, managing, and maintaining water efficient landscapes.

1500-8810 Irrigation Audit, Irrigation Survey, and Irrigation Use Analysis:

(a) This section shall apply to all existing landscapes that were installed before January 1, 2010 and are over one acre in size.

(1) For all landscapes that have a water meter, the local agency shall administer programs that may include, but not be limited to, irrigation water use analyses, irrigation surveys, and irrigation audits to evaluate water use and provide recommendations as necessary to reduce landscape water use to a level that does not exceed the Maximum Applied Water Allowance for existing landscapes. The Maximum Applied Water Allowance for existing landscapes shall be calculated as: $MAWA = (0.8) (ET_o)(LA)(0.62)$.

(2) For all landscapes that do not have a meter, the local agency shall administer programs that may include, but not be limited to, irrigation surveys and irrigation audits to evaluate water use and provide recommendations as necessary in order to prevent water waste.

(b) All landscape irrigation audits shall be conducted by a certified landscape irrigation auditor.

1500-8815 Water Waste Prevention:

(a) Runoff shall be prohibited from leaving the target landscape due to low head drainage, overspray, or other similar conditions where water flows onto adjacent property, non-irrigated areas, walks, roadways, parking lots, or structures. Penalties for violation of these prohibitions shall be established locally.

(b) Restrictions regarding overspray and runoff may be modified if:

(1) The landscape area is adjacent to permeable surfacing and no runoff occurs; or

(2) The adjacent non-permeable surfaces are designed and constructed to drain entirely to landscaping.

1500-8820 Effective Precipitation:

(a) A local agency may consider Effective Precipitation (25% of annual precipitation) in tracking water use and may use the following equation to calculate Maximum Applied Water Allowance:

$$\text{MAWA} = (\text{ET}_o - \text{Eppt}) (0.62) [(0.7 \times \text{LA}) + (0.3 \times \text{SLA})].$$

Appendix A

Reference Evapotranspiration (ET_o) Table Sutter County and Adjacent Counties.

Appendix A - Reference Evapotranspiration (ET_o) Table*

County and City	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Annual ET _o
BUTTE													
Chico	1.2	1.8	2.9	4.7	6.1	7.4	8.5	7.3	5.4	3.7	1.7	1.0	51.7
Durham	1.1	1.8	3.2	5.0	6.5	7.4	7.8	6.9	5.3	3.6	1.7	1.0	51.1
Gridley	1.2	1.8	3.0	4.7	6.1	7.7	8.5	7.1	5.4	3.7	1.7	1.0	51.9
Oroville	1.2	1.7	2.8	4.7	6.1	7.6	8.5	7.3	5.3	3.7	1.7	1.0	51.5
COLUSA													
Colusa	1.0	1.7	3.4	5.0	6.4	7.6	8.3	7.2	5.4	3.8	1.8	1.1	52.8
Williams	1.2	1.7	2.9	4.5	6.1	7.2	8.5	7.3	5.3	3.4	1.6	1.0	50.8
PLACER													
Auburn	1.2	1.7	2.8	4.4	6.1	7.4	8.3	7.3	5.4	3.4	1.6	1.0	50.6
Blue Canyon	0.7	1.1	2.1	3.4	4.8	6.0	7.2	6.1	4.6	2.9	0.9	0.6	40.5
Colfax	1.1	1.5	2.6	4.0	5.8	7.1	7.9	7.0	5.3	3.2	1.4	0.9	47.9
Roseville	1.1	1.7	3.1	4.7	6.2	7.7	8.5	7.3	5.6	3.7	1.7	1.0	52.2
Soda Springs	0.7	0.7	1.8	3.0	4.3	5.3	6.2	5.5	4.1	2.5	0.7	0.7	35.4
Tahoe City	0.7	0.7	1.7	3.0	4.3	5.4	6.1	5.6	4.1	2.4	0.8	0.6	35.5
Truckee	0.7	0.7	1.7	3.2	4.4	5.4	6.4	5.7	4.1	2.4	0.8	0.6	36.2
SACRAMENTO													
Fair Oaks	1.0	1.6	3.4	4.1	6.5	7.5	8.1	7.1	5.2	3.4	1.5	1.0	50.5
Sacramento	1.0	1.8	3.2	4.7	6.4	7.7	8.4	7.2	5.4	3.7	1.7	0.9	51.9
Twitchell Island	1.2	1.8	3.9	5.3	7.4	8.8	9.1	7.8	5.9	3.8	1.7	1.2	57.9
SUTTER													
Nicolaus	0.9	1.6	3.2	4.9	6.3	7.5	8.0	6.9	5.2	3.4	1.5	0.9	50.2
Yuba City	1.3	2.1	2.8	4.4	5.7	7.2	7.1	6.1	4.7	3.2	1.2	0.9	46.7
YOLO													
Bryte	0.9	1.7	3.3	5.0	6.4	7.5	7.9	7.0	5.2	3.5	1.6	1.0	51.0
Davis	1.0	1.9	3.3	5.0	6.4	7.6	8.2	7.1	5.4	4.0	1.8	1.0	52.5
Esparto	1.0	1.7	3.4	5.5	6.9	8.1	8.5	7.5	5.8	4.2	2.0	1.2	55.8
Winters	1.7	1.7	2.9	4.4	5.8	7.1	7.9	6.7	5.3	3.3	1.6	1.0	49.4
Woodland	1.0	1.8	3.2	4.7	6.1	7.7	8.2	7.2	5.4	3.7	1.7	1.0	51.6
Zamora	1.1	1.9	3.5	5.2	6.4	7.4	7.8	7.0	5.5	4.0	1.9	1.2	52.8
YUBA													
Browns Valley	1.0	1.7	3.1	4.7	6.1	7.5	8.5	7.6	5.7	4.1	2.0	1.1	52.9
Brownsville	1.1	1.4	2.6	4.0	5.7	6.8	7.9	6.8	5.3	3.4	1.5	0.9	47.4

* The values in this table were derived from:

- 1) California Irrigation Management Information System (CIMIS);
- 2) Reference EvapoTranspiration Zones Map, UC Dept. of Land, Air & Water Resources and California Dept of Water Resources 1999; and
- 3) Reference Evapotranspiration for California, University of California, Department of Agriculture and Natural Resources (1987) Bulletin 1922, 4) Determining Daily Reference Evapotranspiration, Cooperative Extension UC Division of Agriculture and Natural Resources (1987), Publication Leaflet 21426

Appendix B

WATER EFFICIENT LANDSCAPE WORKSHEET

This worksheet is filled out by the project applicant and it is a required element of the Landscape Documentation Package. Please complete all sections (A and B) of the worksheet.

SECTION A. HYDROZONE INFORMATION TABLE

Please complete the hydrozone table(s) for each hydrozone. Use as many tables as necessary to provide the square footage of landscape area per hydrozone.

Hydrozone*	Zone or Valve	Irrigation Method**	Area (Sq. Ft.)	% of Landscape Area
Total				100%

*** Hydrozone**
HW = High Water Use Plants
MW = Moderate Water Use Plants
LW = Low Water Use Plants

****Irrigation Method**
MS = Micro-spray
S = Spray
R = Rotor
B= Bubbler
D= Drip
O = Other

Appendix B

SECTION B. WATER BUDGET CALCULATIONS

Section B1. Maximum Applied Water Allowance (MAWA)

The project's Maximum Applied Water Allowance shall be calculated using this equation:

$$\text{MAWA} = (\text{ETo}) (0.62) [(0.7 \times \text{LA}) + (0.3 \times \text{SLA})]$$

where:

- MAWA = Maximum Applied Water Allowance (gallons per year)
- ETo = Reference Evapotranspiration from Appendix A (inches per year)
- 0.7 = ET Adjustment Factor (ETAF)
- LA = Landscaped Area includes Special Landscape Area (square feet)
- 0.62 = Conversion factor (to gallons per square foot)
- SLA = Portion of the landscape area identified as Special Landscape Area (square feet)
- 0.3 = the additional ET Adjustment Factor for Special Landscape Area (1.0 - 0.7 = 0.3)

Maximum Applied Water Allowance = _____ gallons per year

Show calculations.

Effective Precipitation (Eppt)

If considering Effective Precipitation, use 25% of annual precipitation. Use the following equation to calculate Maximum Applied Water Allowance:

$$\text{MAWA} = (\text{ETo} - \text{Eppt}) (0.62) [(0.7 \times \text{LA}) + (0.3 \times \text{SLA})]$$

Maximum Applied Water Allowance = _____ gallons per year

Show calculations.

Section B2. Estimated Total Water Use (ETWU)

The project's Estimated Total Water Use is calculated using the following formula:

$$ETWU = (ETo)(0.62) \left(\frac{PF \times HA}{IE} + SLA \right)$$

where:

- ETWU = Estimated total water use per year (gallons per year)
- ETo = Reference Evapotranspiration (inches per year)
- PF = Plant Factor from WUCOLS (see Definitions)
- HA = Hydrozone Area [high, medium, and low water use areas] (square feet)
- SLA = Special Landscape Area (square feet)
- 0.62 = Conversion Factor (to gallons per square foot)
- IE = Irrigation Efficiency (minimum 0.71)

Hydrozone Table for Calculating ETWU

Please complete the hydrozone table(s). Use as many tables as necessary.

Hydrozone	Plant Water Use Type(s)	Plant Factor (PF)	Area (HA) (square feet)	PF x HA (square feet)
			Sum	
	SLA			

Estimated Total Water Use = _____ gallons

Show calculations.

Appendix C

CERTIFICATE OF COMPLETION

This certificate is filled out by the project applicant upon completion of the landscape project.

PART 1. PROJECT INFORMATION SHEET

Date		
Project Name		
Name of Project Applicant	Telephone No.	
	Fax No.	
Title	Email Address	
Company	Street Address	
City	State	Zip Code

Project Address and Location:

Street Address	Parcel, tract or lot number, if available.	
City	Latitude/Longitude (optional)	
State	Zip Code	

Property Owner or his/her designee:

Name	Telephone No.	
	Fax No.	
Title	Email Address	
Company	Street Address	
City	State	Zip Code

Property Owner

"I/we certify that I/we have received copies of all the documents within the Landscape Documentation Package and the Certificate of Completion and that it is our responsibility to see that the project is maintained in accordance with the Landscape and Irrigation Maintenance Schedule."

Property Owner Signature Date

Please answer the questions below:

1. Date the Landscape Documentation Package was submitted to the local agency _____
2. Date the Landscape Documentation Package was approved by the local agency _____
3. Date that a copy of the Water Efficient Landscape Worksheet (including the Water Budget Calculation) was submitted to the local water purveyor _____

PART 2. CERTIFICATION OF INSTALLATION ACCORDING TO THE LANDSCAPE DOCUMENTATION PACKAGE

"I/we certify that based upon periodic site observations, the work has been substantially completed in accordance with the ordinance and that the landscape planting and irrigation installation conform with the criteria and specifications of the approved Landscape Documentation Package."

Signature*	Date	
Name (print)	Telephone No.	
	Fax No.	
Title	Email Address	
License No. or Certification No.		
Company	Street Address	
City	State	Zip Code

*Signer of the landscape design plan, signer of the irrigation plan, or a licensed landscape contractor.

PART 3. IRRIGATION SCHEDULING

Attach parameters for setting the irrigation schedule on controller per Section 1500-8775.

PART 4. SCHEDULE OF LANDSCAPE AND IRRIGATION MAINTENANCE

Attach schedule of Landscape and Irrigation Maintenance per Section 1500-8780.

PART 5. LANDSCAPE IRRIGATION AUDIT REPORT

Attach Landscape Irrigation Audit Report per Section 1500-8785.

PART 6. SOIL MANAGEMENT REPORT

Attach soil analysis report, if not previously submitted with the Landscape Documentation Package per Section 1500-8750.

Attach documentation verifying implementation of recommendations from soil analysis report per Section 1500-8750.