



Humboldt BAYKEEPER  
 Klamath RIVERKEEPER  
 Russian RIVERKEEPER  
 San Francisco BAYKEEPER  
 Monterey COASTKEEPER  
 San Luis Obispo COASTKEEPER  
 Santa Barbara CHANNELKEEPER  
 Ventura COASTKEEPER  
 Los Angeles WATERKEEPER  
 Orange County COASTKEEPER  
 Inland Empire WATERKEEPER  
 San Diego COASTKEEPER



June 26, 2015

Julie Saare-Edmonds  
 Senior Environmental Scientist  
 California Department of Water Resources  
 Urban Water Use Efficiency Unit  
 P.O. Box 942836  
 Sacramento, CA 94236-0001

*Sent via email to: Julie.Saare-Edmonds@water.ca.gov*

Attention Ms. Julie Saare-Edmonds,

On behalf of the Natural Resources Defense Council (NRDC) and other signatories of this letter, I submit these comments on the June 12, 2015 Draft Model Water Efficient Landscape Ordinance (Model Ordinance or MWELO). The proposed revisions to the Model Ordinance mark the beginning of the policy changes needed to end the waste of water in new landscapes, but fall short of what the Governor directed in his recent Executive Order<sup>1</sup>.

In this comment letter and revised draft MWELO language (attached), we have provided recommendations for simple modifications to the June 12, 2015 draft that allow the Model Ordinance to meet the requirements in the Governor’s Executive Order, harmonize with existing regulations, and provide multiple water quality and quantity benefits throughout the state.

**Applicability.** We strongly support the expansion of the coverage of the Model Ordinance to all new landscapes of more than 500 square feet. Lot and yard sizes have trended downward in many areas in recent years, therefore MWELO applicability thresholds need to be lowered. Since even small spaces can waste significant amounts of water, exemptions for new landscapes based on size alone should be truly minimal.

The current version of the draft does not meet the Governor’s Executive Order which directs that the Model Ordinance be updated to “increase water efficiency standards for new and existing landscapes...” Because the draft fails to increase standards for existing landscapes, it misses a huge opportunity to make steady inroads on the number of inefficient existing landscapes.

<sup>1</sup> [http://gov.ca.gov/docs/4.1.15\\_Executive\\_Order.pdf](http://gov.ca.gov/docs/4.1.15_Executive_Order.pdf)

***Recommendation:*** Existing landscapes should be upgraded to MWELO requirements whenever major building renovations and additions requiring a permit take place.

**Separate Water Meters for Outdoor Use.** We strongly support the requirements for landscape water use to be metered, either with a dedicated utility service meter or a private submeter. Water measurement is an essential tool for effective water management. All landscapes on a water budget should be metered to confirm or correct their operation within the budget. Residential landscapes of less than 5,000 square feet *not* be excluded from this requirement. Multi-family residential properties have many of the same design elements and management arrangements as comparably sized commercial buildings. Even single-family landscapes would benefit from the ability to measure water applied to the landscape, identify potential leaks, and manage to maintain the water budget upon which its permit was based.

***Recommendation:*** Require separate outdoor water meters for all properties covered by MWELO, i.e. for any property, residential or commercial, with 500 square feet or more of landscaped area.

**Rainwater Retention.** We strongly support the requirements for soil preparation for all new landscapes to maximize water retention and infiltration. The avoidance of waste requires the treatment of rainwater and stormwater as resources. On-site retention is a key tenet of the “New Normal” for California landscapes, which embraces a broader and more holistic view for conserving water and other natural resources, as well as protecting water quality. Friable soil is an essential building block for this strategy. However, the current text of the Model Ordinance encourages, but does not require, rainwater catchment and stormwater retention.

Stormwater retention is increasingly addressed for various types of projects in regional stormwater management plans and permits. MWELO presents the opportunity to ensure that new landscapes will be designed to meet a minimum statewide standard for retention and infiltration that will help ameliorate both the water quality and water availability challenges facing the state.

***Recommendation:*** The standard identified in section 492.16(e) should be required, rather than recommended.

**More Stringent Water Budgets.** We strongly support the revision of the evapotranspiration adjustment factors (ETAF). The changes proposed in the draft will require both improvements in irrigation efficiency and greater use of

low and moderate water use plants. The net effect is to reduce potable water use by 25% in new residential landscapes and by 40% in new commercial landscapes, compared to allowances under the current Model Ordinance. While the ETAF revisions proposed in the draft are acceptable for an ordinance that takes effect within 6 months, the revised level for residential landscapes would still allow for 25% of a landscape to be ornamental turf or other high water use plants. Such a use of potable water is wasteful when practical alternatives exist. Some additional time may be needed for the landscape industry to further expand product availability, therefore more stringent ETAF requirements could go into effect at a future date. Furthermore, the extra water allowance for “special landscape areas” has remained unchanged since the original model ordinance, notwithstanding improvements in irrigation technologies and plant varieties.

***Recommendation:*** (1) The ETAF for new residential landscapes should be lowered to 0.4 with an effective date no later than 2018. (2) The ETAF for special landscape areas should be reduced from 1.0 to 0.8.

**Authority to Collect Fees.** Effective implementation of the Model Ordinance requires qualified staff and budgetary support. A reasonable fee should be allowed to enable effective plan check, design review, inspection, and enforcement.

***Recommendation:*** The Model Ordinance should include default language allowing for the collection of reasonable fees by the permitting agency.

**Pool and Spa Covers.** A typical pool in Los Angeles can lose up to 40,000 gallons per year to evaporation. The draft MWELO highly recommends but does not require covers for pools and spas.

***Recommendation:*** Pool and spa covers should be required, not highly recommended.

**Harmonization with CALGreen.** We strongly support the harmonization of the Model Ordinance with the CALGreen state building code. The Building Standards Commission took an important step on May 29 by adopting a rule bringing water budget requirements into the mandatory sections of CALGreen for the first time. DWR has indicated that further coordination will take place as the Model Ordinance is revised.

**Recommendation:** All key metrics in the revised Model Ordinance should be added to CALGreen to improve the consistent application and the enforceability of these important provisions.

Attached please find a revised version of the June 12, 2015 draft MWELo with edits that address the issues and recommendations summarized in this letter. Our edits have been highlighted in yellow and can be found on pages 3,4,6,7,9,14,15,20, and 22 of the attached document.

Thank you for the opportunity to provide these recommendations.

Best regards,



Tracy Quinn, P.E.  
Natural Resources Defense Council



Paul Herzog  
Surfrider Foundation



Sara Aminzadeh  
California Coastkeeper Alliance



Rita Kampalath  
Heal the Bay



Linda Eremita  
TreePeople



Melanie Winters  
The River Project



Pamela Berstler  
G3-Green Gardens Group

**Model Water Efficient Landscape Ordinance**  
**September 10, 2009**  
**June 12, 2015 (Public Draft)**

California Code of Regulations  
Title 23. Waters  
Division 2. Department of Water Resources  
Chapter 2.7. Model Water Efficient Landscape Ordinance

**§ 490. Purpose.**

(a) The State Legislature has found:

- (1) that the waters of the state are of limited supply and are subject to ever increasing demands;
- (2) that the continuation of California's economic prosperity is dependent on the availability of adequate supplies of water for future uses;
- (3) that it is the policy of the State to promote the conservation and efficient use of water and to prevent the waste of this valuable resource;
- (4) that landscapes are essential to the quality of life in California by providing areas for active and passive recreation and as an enhancement to the environment by cleaning air and water, preventing erosion, offering fire protection, and replacing ecosystems lost to development; ~~and~~
- (5) that landscape design, installation, maintenance and management can and should be water efficient; and
- (6) that Section 2 of Article X of the California Constitution specifies that the right to use water is limited to the amount reasonably required for the beneficial use to be served and the right does not and shall not extend to waste or unreasonable method of use.

(b) Consistent with these legislative findings, the purpose of this model ordinance is to:

- (1) promote the values and benefits of landscaping practices that integrate and transcend the conservation and efficient use of water; landscapes while recognizing the need to invest water and other resources as efficiently as possible;
- (2) establish a structure for planning, designing, installing, maintaining and managing water efficient landscapes in new construction and rehabilitated projects by using a whole system watershed approach in landscapes of any size and scale that requires cross-sector collaboration to achieve the many benefits possible;
- (3) establish provisions for water management practices and water waste prevention for existing landscapes;
- (4) use water efficiently without waste by setting a Maximum Applied Water Allowance as an upper limit for water use and reduce water use to the lowest practical amount;
- (5) promote the benefits of consistent landscape ordinances with neighboring local and regional agencies;
- (6) encourage local agencies and water purveyors to use economic incentives that promote the efficient use of water, such as implementing a tiered-rate structure; and
- (7) encourage local agencies to designate the necessary authority that implements and enforces the provisions of the Model Water Efficient Landscape Ordinance or its local landscape ordinance.

(c) Regenerative landscape systems that are planned, designed, installed, managed and maintained with the watershed based approach can improve California's environmental conditions and achieve sustainability goals. Consistent with the legislative findings and purpose of the Ordinance, achievable goals include:

- (1) Increasing carbon storage, water retention and productive plant growth by improving soils through reducing compaction, incorporating organic matter and minimizing cut and fill grading.
- (2) Minimizing energy use by reducing irrigation water requirements, reducing reliance on petroleum based fertilizers and pesticides, and planting long lived climate appropriate shade trees in urban areas.

- (3) Conserving water by capturing and reusing rainwater and graywater wherever possible and selecting climate appropriate plants that need minimal supplemental water.
- (4) Protecting air and water quality by reducing power equipment use and landfill trips, selecting locally sourced materials, and using mulch and -efficient irrigation equipment to prevent erosion.
- (5) Protecting existing habitat and creating new habitat by choosing local native plants wherever possible and including climate appropriate non-native plants when necessary, and avoiding pesticides and invasive plants.

Note: Authority cited: Section 65593, Government Code. Reference: Sections 65591, 65593, 65596, Government Code.

**§ 490.1 Applicability**

(a) After ~~January 1, 2010~~ November 1, 2015, this ordinance shall apply to all of the following landscape projects:

- (1) new construction projects with a landscape area greater than 500 square feet requiring a building or landscape permit, plan check or design review;
- (2) rehabilitated landscape projects with an aggregated landscape area equal to or greater than 2,500 square feet requiring a building or landscape permit, plan check, or design review;
- (3) existing landscapes with a landscape alteration greater than 500 square feet associated with any building additions or renovations with a valuation exceeding \$200,000.00 requiring a building permit.
- ~~(1) new construction and rehabilitated landscapes for public agency projects and private development projects with a landscape area equal to or greater than 2,500 square feet requiring a building or landscape permit, plan check or design review;~~
- ~~(2) new construction and rehabilitated landscapes which are developer installed in single family and multi family projects with a landscape area equal to or greater than 2,500 square feet requiring a building or landscape permit, plan check, or design review;~~
- ~~(3) new construction landscapes which are homeowner provided and/or homeowner hired in single family and multi family residential projects with a total project landscape area equal to or greater than 5,000 square feet requiring a building or landscape permit, plan check or design review;~~
- (4) (3) (4) existing landscapes limited to Sections 493, 493.1 and 493.2; and
- (5) (4) (5) cemeteries. Recognizing the special landscape management needs of cemeteries, new and rehabilitated cemeteries are limited to Sections 492.4, 492.11 and 492.12; and existing cemeteries are limited to Sections 493, 493.1 and 493.2.

(b) This ordinance does not apply to:

- (1) registered local, state or federal historical sites;
- (2) ecological restoration projects that do not require a permanent irrigation system;
- (3) mined-land reclamation projects that do not require a permanent irrigation system; or
- (4) existing plant collections, as part of botanical gardens and arboretums open to the public.

Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.

**§ 491. Definitions.**

The terms used in this ordinance have the meaning set forth below:

- (a) “applied water” means the portion of water supplied by the irrigation system to the landscape.
- (b) “automatic irrigation controller” means an automatic timing device used to remotely control valves that operate an irrigation system. Automatic irrigation controllers schedule irrigation events using either evapotranspiration (weather-based) or soil moisture data.

- (c) “backflow prevention device” means a safety device used to prevent pollution or contamination of the water supply due to the reverse flow of water from the irrigation system.
- (d) “Certificate of Completion” means the document required under Section 492.9.
- (e) “certified irrigation designer” means a person certified to design irrigation systems by an accredited academic institution, a professional trade organization or other program such as the US Environmental Protection Agency’s WaterSense irrigation designer certification program and Irrigation Association’s Certified Irrigation Designer program.
- (f) “certified landscape irrigation auditor” means a person certified to perform landscape irrigation audits by an accredited academic institution, a professional trade organization or other program such as the US Environmental Protection Agency’s WaterSense irrigation auditor certification program and Irrigation Association’s Certified Landscape Irrigation Auditor program.
- (g) “check valve” or “anti-drain valve” means a valve located under a sprinkler head, or other location in the irrigation system, to hold water in the system to prevent drainage from sprinkler heads when the sprinkler is off.
- (h) “common interest developments” means community apartment projects, condominium projects, planned developments, and stock cooperatives per Civil Code Section 1351.
- (i) “conversion factor (0.62)” means the number that converts acre-inches per acre per year to gallons per square foot per year.
- (j) “drip irrigation” means any non-spray low volume irrigation system utilizing emission devices with a flow rate measured in gallons per hour. Low volume irrigation systems are specifically designed to apply small volumes of water slowly at or near the root zone of plants.
- (k) “ecological restoration project” means a project where the site is intentionally altered to establish a defined, indigenous, historic ecosystem.
- (l) “effective precipitation” or “usable rainfall” (Eppt) means the portion of total precipitation which becomes available for plant growth.
- (m) “emitter” means a drip irrigation emission device that delivers water slowly from the system to the soil.
- (n) “established landscape” means the point at which plants in the landscape have developed significant root growth into the soil. Typically, most plants are established after one or two years of growth.
- (o) “establishment period of the plants” means the first year after installing the plant in the landscape or the first two years if irrigation will be terminated after establishment. Typically, most plants are established after one or two years of growth.
- (p) “Estimated Total Water Use” (ETWU) means the total water used for the landscape as described in Section 492.4.
- (q) “ET adjustment factor” (ETAF) means a factor of 0.75 for residential areas and 0.4 for non-residential areas, that, when applied to reference evapotranspiration, adjusts for plant factors and irrigation efficiency, two major influences upon the amount of water that needs to be applied to the landscape. A combined plant mix with a site-wide average of ~~0.5~~ 0.425 for residential areas and 0.37 for other areas is the basis of the plant factor portion of this calculation. For purposes of the ETAF, the average irrigation efficiency is ~~0.74~~ 0.85 for residential and 0.92 for non-residential areas. Therefore, the ~~ETAF Adjustment Factor for residential and non-residential is (0.75)=(0.425/0.8574) and (0.4)=(0.37/0.92), respectively. The ETAF for a new and existing Special Landscape Areas shall not exceed 1.0~~ 0.8. The ETAF for existing non-rehabilitated landscapes is 0.8. Effective January 1, 2018, the ETAF shall mean a factor of 0.4 for both residential and non-residential areas.
- (r) “evapotranspiration rate” means the quantity of water evaporated from adjacent soil and other surfaces and transpired by plants during a specified time.
- (s) “flow rate” means the rate at which water flows through pipes, valves and emission devices, measured in gallons per minute, gallons per hour, or cubic feet per second.

(t) “friable” means a soil condition that is easily crumbled or loosely compacted down to a minimum depth per planting material requirements, whereby the root structure of newly planted material will be allowed to spread unimpeded.

(u) “graywater” means untreated wastewater that has not been contaminated by any toilet discharge, has not been affected by infectious, contaminated, or unhealthy bodily wastes, and does not present a threat from contamination by unhealthful processing, manufacturing, or operating wastes. “Graywater” includes, but is not limited to, wastewater from bathtubs, showers, bathroom washbasins, clothes washing machines, and laundry tubs, but does not include wastewater from kitchen sinks or dishwashers. Pursuant to Health and Safety Code Section 17922.12.

(v) ~~(t)~~ “hardscapes” means any durable material (pervious and non-pervious).

(w) ~~(u)~~ “homeowner-provided landscaping” means any landscaping either installed by a private individual for a single family residence or installed by a licensed contractor hired by a homeowner. A homeowner, for purposes of this ordinance, is a person who occupies the dwelling he or she owns. This excludes speculative homes, which are not owner-occupied dwellings.

(x) ~~(v)~~ “hydrozone” means a portion of the landscaped area having plants with similar water needs. A hydrozone may be irrigated or non-irrigated.

(y) ~~(w)~~ “infiltration rate” means the rate of water entry into the soil expressed as a depth of water per unit of time (e.g., inches per hour).

(z) ~~(x)~~ “invasive plant species” means species of plants not historically found in California that spread outside cultivated areas and can damage environmental or economic resources. Invasive species may be regulated by county agricultural agencies as noxious species. “Noxious weeds” means any weed designated by the Weed Control Regulations in the Weed Control Act and identified on a Regional District noxious weed control list. Lists of invasive plants are maintained at the California Invasive Plant Inventory and USDA invasive and noxious weeds database.

(aa) ~~(y)~~ “irrigation audit” means an in-depth evaluation of the performance of an irrigation system conducted by a Certified Landscape Irrigation Auditor. An irrigation audit includes, but is not limited to: inspection, system tune-up, system test with distribution uniformity or emission uniformity, reporting overspray or runoff that causes overland flow, and preparation of an irrigation schedule. The audit must be conducted in a manner consistent with the Irrigation Association’s Landscape Irrigation Auditor Certification program.

(bb) ~~(z)~~ “irrigation efficiency” (IE) means the measurement of the amount of water beneficially used divided by the amount of water applied. Irrigation efficiency is derived from measurements and estimates of irrigation system characteristics and management practices. The minimum average irrigation efficiency for purposes of this ordinance is 0.857+ for residential areas and 0.92 for non-residential areas, averaged on a site-wide basis. Greater irrigation efficiency can be expected from well designed and maintained systems.

(cc) ~~(aa)~~ “irrigation survey” means an evaluation of an irrigation system that is less detailed than an irrigation audit. An irrigation survey includes, but is not limited to: inspection, system test, and written recommendations to improve performance of the irrigation system.

(dd) ~~(bb)~~ “irrigation water use analysis” means a review of water use data based on meter readings and billing data.

(ee) ~~(cc)~~ “landscape architect” means a person who holds a license to practice landscape architecture in the state of California Business and Professions Code, Section 5615.

(ff) ~~(dd)~~ “landscape area” means all the planting areas, turf areas, and water features in a landscape design plan subject to the Maximum Applied Water Allowance calculation. The landscape area does not include footprints of buildings or structures, sidewalks, driveways, parking lots, decks, patios, gravel or stone walks, other pervious or non-pervious hardscapes, and other non-irrigated areas designated for non-development (e.g., open spaces and existing native vegetation).

(gg) ~~(ee)~~ “landscape contractor” means a person licensed by the state of California to construct, maintain, repair, install, or subcontract the development of landscape systems.

(hh) “landscape designer” means a person permitted by the Business and Profession Code to prepare plans, drawings, and specifications for the selection, placement, or use of plants for single family dwellings. They may prepare drawings for the conceptual design and placement of tangible objects and landscape features. A landscape designer may not prepare construction documents, details, or specifications for tangible landscape objects or landscape features or prepare grading and drainage plans for the alteration of sites.

(ii) ~~(ff)~~ “Landscape Documentation Package” means the documents required under Section 492.3.

(jj) ~~(gg)~~ “landscape project” means total area of landscape in a project as defined in “landscape area” for the purposes of this ordinance, meeting requirements under Section 490.1.

(kk) ~~(hh)~~ “lateral line” means the water delivery pipeline that supplies water to the emitters or sprinklers from the valve.

(ll) ~~(ii)~~ “local agency” means a city or county, including a charter city or charter county, that is responsible for adopting and implementing the ordinance. The local agency is also responsible for the enforcement of this ordinance, including but not limited to, approval of a permit and plan check or design review of a project.

(mm) ~~(jj)~~ “local water purveyor” means any entity, including a public agency, city, county, or private water company that provides retail water service.

(nn) ~~(kk)~~ “low volume irrigation” means the application of irrigation water at low pressure through a system of tubing or lateral lines and low-volume emitters such as drip, drip lines, and bubblers. Low volume irrigation systems are specifically designed to apply small volumes of water slowly at or near the root zone of plants.

(oo) ~~(ll)~~ “main line” means the pressurized pipeline that delivers water from the water source to the valve or outlet.

(pp) “master valve” is an electric valve installed at the supply point which controls water flow into the main piping system. When this valve is closed water will not be supplied to the irrigation system. A master valve will greatly reduce any water loss due to a leaky station valve.

(qq) ~~(mm)~~ “Maximum Applied Water Allowance” (MAWA) means the upper limit of annual applied water for the established landscaped area as specified in Section 492.4. It is based upon the area’s reference evapotranspiration, the ET Adjustment Factor, and the size of the landscape area. The Estimated Total Water Use shall not exceed the Maximum Applied Water Allowance. Special Landscape Areas, including recreation areas, areas permanently and solely dedicated to edible plants such as orchards and vegetable gardens, and areas irrigated with recycled water are subject to the MAWA with an ETAF not to exceed **1.0-0.8**.

(rr) “median” is an area between opposing lanes of traffic that may be unplanted or planted with trees, shrubs, perennials, and ornamental grasses.

(ss) ~~(nn)~~ “microclimate” means the climate of a small, specific area that may contrast with the climate of the overall landscape area due to factors such as wind, sun exposure, plant density, or proximity to reflective surfaces.

(tt) “microspray” means a microirrigation emission device with one or more orifices to convert irrigation water pressure to water discharge with a flow rate not to exceed 30 gallons per hour (113.5 litres per hour) at the largest area of coverage available for the nozzle series when operated at 30 psi (206.8kPa). Microsprays are inclusive of “microbubblers”, “microspinners” and “microspray jets.” (From ASABE/ICC 802-2014 Landscape Irrigation and Emitter Standard.)

(uu) ~~(oo)~~ “mined-land reclamation projects” means any surface mining operation with a reclamation plan approved in accordance with the Surface Mining and Reclamation Act of 1975.

(vv) ~~(pp)~~ “mulch” means any organic material such as leaves, bark, straw, compost, or inorganic mineral materials such as rocks, gravel, and decomposed granite left loose and applied to the soil surface for the beneficial purposes of reducing evaporation, suppressing weeds, moderating soil temperature, and preventing soil erosion.

~~(ww)~~ ~~(qq)~~ “new construction” means, for the purposes of this ordinance, a new building with a landscape or other new landscape, such as a park, playground, or greenbelt without an associated building.

~~(xx)~~ ~~(rr)~~ “operating pressure” means the pressure at which the parts of an irrigation system are designed by the manufacturer to operate.

~~(yy)~~ ~~(ss)~~ “overhead sprinkler irrigation systems” means systems that deliver water through the air (e.g., spray heads and rotors).

~~(zz)~~ ~~(tt)~~ “overspray” means the irrigation water which is delivered beyond the target area.

~~(aaa)~~ “parkway” means the area between a sidewalk and the curb or traffic lane. It may be planted or unplanted, and with or without pedestrian egress.

~~(bbb)~~ ~~(uu)~~ “permit” means an authorizing document issued by local agencies for new construction or rehabilitated landscapes.

~~(ccc)~~ ~~(vv)~~ “pervious” means any surface or material that allows the passage of water through the material and into the underlying soil.

~~(ddd)~~ ~~(ww)~~ “plant factor” or “plant water use factor” is a factor, when multiplied by ETo, estimates the amount of water needed by plants. For purposes of this ordinance, the plant factor range for low water use plants is 0 to 0.3, the plant factor range for moderate water use plants is 0.4 to 0.6, and the plant factor range for high water use plants is 0.7 to 1.0. Plant factors cited in this ordinance are derived from the Department of Water Resources 2000 publication “Water Use Classification of Landscape Species”. Plant factors may also be obtained from horticultural researchers from academic institutions or nursery industry professional associations as approved by the California Department of Water Resources (DWR).

~~(eee)~~ ~~(xx)~~ “precipitation rate” means the rate of application of water measured in inches per hour.

~~(fff)~~ ~~(yy)~~ “project applicant” means the individual or entity submitting a Landscape Documentation Package required under Section 492.3 to request a permit, plan check, or design review from the local agency. A project applicant may be the property owner or his or her designee.

~~(ggg)~~ ~~(zz)~~ “rain sensor” or “rain sensing shutoff device” means a component which automatically suspends an irrigation event when it rains.

~~(hhh)~~ ~~(aaa)~~ “record drawing” or “as-builts” means a set of reproducible drawings which show significant changes in the work made during construction and which are usually based on drawings marked up in the field and other data furnished by the contractor.

~~(iii)~~ ~~(bbb)~~ “recreational area” means areas, excluding private single family residential areas, dedicated to active play recreation or public assembly such as parks, sports fields, picnic grounds, amphitheaters and or golf courses tees, fairways and greens.

~~(jii)~~ ~~(eee)~~ “recycled water”, “reclaimed water”, or “treated sewage effluent water” means treated or recycled waste water of a quality suitable for non-potable uses such as landscape irrigation and water features. This water is not intended for human consumption.

~~(kkk)~~ ~~(ddd)~~ “reference evapotranspiration” or “ETo” means a standard measurement of environmental parameters which affect the water use of plants. ETo is expressed in inches per day, month, or year as represented in Appendix A Section 495.1, and is an estimate of the evapotranspiration of a large field of four- to seven-inch tall, cool-season grass that is well watered. Reference evapotranspiration is used as the basis of determining the Maximum Applied Water Allowance so that regional differences in climate can be accommodated.

~~(lll)~~ ~~(eee)~~ “rehabilitated landscape” means any re-landscaping project that requires a permit, plan check, or design review, meets the requirements of Section 490.1, and the modified landscape area is equal to or greater than 2,500 square feet, is 50% of the total landscape area, and the modifications are completed within one year.

~~(mmm)~~ ~~(fff)~~ “runoff” means water which is not absorbed by the soil or landscape to which it is applied and flows from the landscape area. For example, runoff may result from water that is applied at too great a rate (application rate exceeds infiltration rate) or when there is a slope.

~~(nnn)~~ ~~(ggg)~~ “soil moisture sensing device” or “soil moisture sensor” means a device that measures the amount of water in the soil. The device may also suspend or initiate an irrigation event.

~~(ooo)~~ ~~(hhh)~~ “soil texture” means the classification of soil based on its percentage of sand, silt, and clay.

~~(ppp)~~ ~~(iii)~~ “Special Landscape Area” (SLA) means an area of the landscape dedicated solely to edible plants, recreational areas, areas irrigated with recycled water, and water features using recycled water ~~and areas dedicated to active play such as parks, sports fields, golf courses, and where turf provides a playing surface.~~

~~(qqq)~~ ~~(jjj)~~ “sprinkler head” means a device which delivers water through a nozzle.

~~(rrr)~~ ~~(kkk)~~ “static water pressure” means the pipeline or municipal water supply pressure when water is not flowing.

~~(sss)~~ ~~(lll)~~ “station” means an area served by one valve or by a set of valves that operate simultaneously.

~~(ttt)~~ ~~(mmm)~~ “swing joint” means an irrigation component that provides a flexible, leak-free connection between the emission device and lateral pipeline to allow movement in any direction and to prevent equipment damage.

~~(uuu)~~ ~~(nnn)~~ “turf” means a ground cover surface of mowed grass. Annual bluegrass, Kentucky bluegrass, Perennial ryegrass, Red fescue, and Tall fescue are cool-season grasses. Bermudagrass, Kikuyugrass, Seashore Paspalum, St. Augustinegrass, Zoysiagrass, and Buffalo grass are warm-season grasses.

~~(vvv)~~ ~~(ooo)~~ “valve” means a device used to control the flow of water in the irrigation system.

~~(www)~~ “water budget” is a reasonable estimate of the amount of irrigation water required for a specific landscape. Basic water budget calculations require measured areas of each irrigated hydrozone and reference evapotranspiration for the area to be landscaped.

~~(xxx)~~ ~~(ppp)~~ “water conserving plant species” means a plant species identified as having a low plant factor.

~~(yyy)~~ ~~(qqq)~~ “water feature” means a design element where open water performs an aesthetic or recreational function. Water features include ponds, lakes, waterfalls, fountains, artificial streams, spas, and swimming pools (where water is artificially supplied). The surface area of water features is included in the high water use hydrozone of the landscape area. Constructed wetlands used for on-site wastewater treatment or stormwater best management practices that are not irrigated and used solely for water treatment or stormwater retention are not water features and, therefore, are not subject to the water budget calculation.

~~(zzz)~~ ~~(rrr)~~ “watering window” means the time of day irrigation is allowed.

~~(aaaa)~~ ~~(sss)~~ “WUCOLS” means the Water Use Classification of Landscape Species published by the University of California Cooperative Extension; and the Department of Water Resources ~~and the Bureau of Reclamation, 2000~~ 2014.

Note: Authority Cited: Section 65595, Government Code. Reference: Sections 65592, 65596, Government Code.

#### **§ 492. Provisions for New Construction or Rehabilitated Landscapes.**

(a) A local agency may designate another agency, such as a water purveyor, to implement some or all of the requirements contained in this ordinance. Local agencies may collaborate with water purveyors to define each entity’s specific responsibilities relating to this ordinance.

Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.

#### **§ 492.1 Compliance with Landscape Documentation Package.**

(a) Prior to construction, the local agency shall:

- (1) provide the project applicant with the ordinance and procedures for permits, plan checks, or design reviews;

- (2) review the Landscape Documentation Package submitted by the project applicant;
  - (3) approve or deny the Landscape Documentation Package;
  - (4) issue a permit or approve the plan check or design review for the project applicant; and
  - (5) upon approval of the Landscape Documentation Package, submit a copy of the Water Efficient Landscape Worksheet to the local water purveyor.
- (b) Prior to construction, the project applicant shall:
- (1) submit a Landscape Documentation Package to the local agency.
- (c) Upon approval of the Landscape Documentation Package by the local agency, the project applicant shall:
- (1) receive a permit or approval of the plan check or design review and record the date of the permit in the Certificate of Completion;
  - (2) submit a copy of the approved Landscape Documentation Package along with the record drawings, and any other information to the property owner or his/her designee; and
  - (3) submit a copy of the Water Efficient Landscape Worksheet to the local water purveyor.

Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.

**§ 492.2 Penalties.**

- (a) A local agency may establish and administer penalties to the project applicant for non-compliance with the ordinance to the extent permitted by law.

Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.

**§ 492.X Fees.** A local agency may collect a fee for implementing and enforcing this ordinance.

**§ 492.3 Elements of the Landscape Documentation Package.**

- (a) The Landscape Documentation Package shall include the following six (6) elements:
  - (1) project information;
    - (A) date
    - (B) project applicant
    - (C) project address (if available, parcel and/or lot number(s))
    - (D) total landscape area (square feet)
    - (E) project type (e.g., new, rehabilitated, public, private, cemetery, homeowner-installed)
    - (F) water supply type (e.g., potable, recycled, well) and identify the local retail water purveyor if the applicant is not served by a private well
    - (G) checklist of all documents in Landscape Documentation Package
    - (H) project contacts to include contact information for the project applicant and property owner
    - (I) applicant signature and date with statement, “I agree to comply with the requirements of the water efficient landscape ordinance and submit a complete Landscape Documentation Package”.
  - (2) Water Efficient Landscape Worksheet;
    - (A) hydrozone information table
    - (B) water budget calculations
      - 1. Maximum Applied Water Allowance (MAWA)
      - 2. Estimated Total Water Use (ETWU)
  - (3) soil management report;
  - (4) landscape design plan;
  - (5) irrigation design plan; and
  - (6) grading design plan.

Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.

#### § 492.4 Water Efficient Landscape Worksheet.

(a) A project applicant shall complete the Water Efficient Landscape Worksheet which contains two sections (see sample worksheet in Appendix B):

- (1) a hydrozone information table (see Appendix B, Section A) for the landscape project; and
- (2) a water budget calculation (see Appendix B, Section B) for the landscape project. For the calculation of the Maximum Applied Water Allowance and Estimated Total Water Use, a project applicant shall use the ETo values from the Reference Evapotranspiration Table in Appendix A. For geographic areas not covered in Appendix A, use data from other cities located nearby in the same reference evapotranspiration zone, as found in the CIMIS Reference Evapotranspiration Zones Map, Department of Water Resources, 1999.

(b) Water budget calculations shall adhere to the following requirements:

(1) The plant factor used shall be from WUCOLS. Plant factors may also be obtained from horticultural researchers with academic institutions or nursery industry professional associations as approved by the California Department of Water Resources (DWR). The plant factor ranges from 0 to 0.3 for low water use plants, from 0.4 to 0.6 for moderate water use plants, and from 0.7 to 1.0 for high water use plants.

(2) All water features shall be included in the high water use hydrozone and temporarily irrigated areas shall be included in the low water use hydrozone.

(3) All Special Landscape Areas shall be identified and their water use calculated as described below.

(4) ETAF for Special Landscape Areas shall not exceed 1.0.

(c) Maximum Applied Water Allowance

The Maximum Applied Water Allowance shall be calculated using the equation:

Residential Areas:  $MAWA = (ET_o) (0.62) [(0.57 \times LA) + (0.53 \times SLA)]$

Non-Residential:  $MAWA = (ET_o) (0.62) [(0.4 \times LA) + (0.6 \times SLA)]$

The example calculations below are hypothetical to demonstrate proper use of the equations and do not represent an existing and/or planned landscape project. The ETo values used in these calculations are from the Reference Evapotranspiration Table in Appendix A, for planning purposes only. For actual irrigation scheduling, automatic irrigation controllers are required and shall use current reference evapotranspiration data, such as from the California Irrigation Management Information System (CIMIS), other equivalent data, or soil moisture sensor data.

(1) Example MAWA calculation for a residential landscape project: a hypothetical landscape project in Fresno, CA with an irrigated landscape area of 50,000 square feet without any Special Landscape Area (SLA= 0, no edible plants, recreational areas, or use of recycled water). To calculate MAWA, the annual reference evapotranspiration value for Fresno is 51.1 inches as listed in the Reference Evapotranspiration Table in Appendix A.

$MAWA = (ET_o) (0.62) [(0.57 \times LA) + (0.53 \times SLA)]$

MAWA = Maximum Applied Water Allowance (gallons per year)

ET<sub>o</sub> = Reference Evapotranspiration (inches per year)

0.62 = Conversion Factor (to gallons per year)

0.57 = ET Adjustment Factor (ETAF)

LA = Landscape Area including SLA (square feet)

0.53 = Additional Water Allowance for SLA

SLA = Special Landscape Area (square feet)

$MAWA = (51.1 \text{ inches}) (0.62) [(0.57 \times 50,000 \text{ square feet}) + (0.53 \times 0)]$

$$= 1,108,870 \frac{792,050}{748} \text{ gallons per year}$$

To convert from gallons per year to hundred-cubic-feet per year:

$$= 1,108,870 \frac{792,050}{748} = 1,482,059 \text{ hundred-cubic-feet per year}$$

(100 cubic feet = 748 gallons)

(2) In this next hypothetical example, the residential landscape project in Fresno, CA has the same ETo value of 51.1 inches and a total landscape area of 50,000 square feet. Within the 50,000 square foot project, there is now a 2,000 square foot area planted with edible plants. This 2,000 square foot area is considered to be a Special Landscape Area.

$$\text{MAWA} = (\text{ETo}) (0.62) [(0.57 \times \text{LA}) + (0.53 \times \text{SLA})]$$

$$\text{MAWA} = (51.1 \text{ inches}) (0.62) [(0.57 \times 50,000 \text{ square feet}) + (0.53 \times 2,000 \text{ square feet})]$$

$$= 31.68 \times [235,000 + 1,0600] \text{ gallons per year}$$

$$= 31.68 \times 3526,0600 \text{ gallons per year}$$

$$= 1,127,808823,680 \text{ gallons per year or } 1,101,508 \text{ hundred-cubic-feet per year}$$

(d) Estimated Total Water Use.

The Estimated Total Water Use shall be calculated using the equation below. The sum of the Estimated Total Water Use calculated for all hydrozones shall not exceed MAWA.

$$ETWU = (\text{ETo})(0.62) \left( \frac{\text{PF} \times \text{HA}}{\text{IE}} + \text{SLA} \right)$$

Where:

ETWU = Estimated Total Water Use per year (gallons)

ETo = Reference Evapotranspiration (inches)

PF = Plant Factor from WUCOLS (see Section 491)

HA = Hydrozone Area [high, medium, and low water use areas] (square feet)

SLA = Special Landscape Area (square feet)

0.62 = Conversion Factor (to gallons per year)

IE = Irrigation Efficiency (minimum 0.8574 for residential areas and 0.92 for non-residential areas)

(1) Example ETWU calculation: landscape area is 50,000 square feet; plant water use type, plant factor, and hydrozone area are shown in the table below. The ETo value is 51.1 inches per year. There are no Special Landscape Areas (recreational area, area permanently and solely dedicated to edible plants, and area irrigated with recycled water) in this example.

Hydrozone	Plant Water Use Type(s)	Plant Factor (PF)*	Hydrozone Area (HA) (square feet)	PF x HA (square feet)
1	High	0.8	<u>17,000</u>	<u>5,6800</u>
2	High	0.7	<u>102,000</u>	<u>147,000</u>
3	Medium	0.5	<u>156,000</u>	<u>78,5000</u>
4	Low	0.3	<u>147,000</u>	<u>42,1200</u>
5	Low	0.2	<u>180,000</u>	<u>23,0600</u>
			Sum	<u>24,70017,500</u>

\*Plant Factor from WUCOLS

$$ETWU = (51.1)(0.62) \left( \frac{17,500}{0.85} + 0 \right)$$

= 1,102,116 652,276 gallons per year

Compare ETWU with MAWA: For this example MAWA = (51.1) (0.62) [(0.57 x 50,000) + (0.53 x 0)] = 1,108,870 792,050 gallons per year. The ETWU (1,102,116 652,276 gallons per year) is less than MAWA (1,108,870 792,050 gallons per year). In this example, the water budget complies with the MAWA.

(2) Example ETWU calculation: total landscape area is 50,000 square feet, 2,000 square feet of which is planted with edible plants. The edible plant area is considered a Special Landscape Area (SLA). The reference evapotranspiration value is 51.1 inches per year. The plant type, plant factor, and hydrozone area are shown in the table below.

Hydrozone	Plant Water Use Type(s)	Plant Factor (PF)*	Hydrozone Area (HA) (square feet)	PF x HA (square feet)
1	High	0.8	<u>17,000</u>	<u>85,600</u>
2	High	0.7	<u>19,000</u>	<u>6,3700</u>
3	Medium	0.5	<u>145,000</u>	<u>7,0500</u>
4	Low	0.3	<u>147,000</u>	<u>4,2100</u>
5	Low	0.2	<u>180,000</u>	<u>32,600</u>
			Sum	<u>1623,3500</u>
6	SLA	1.0	2,000	2,000

\*Plant Factor from WUCOLS

$$ETWU = (51.1)(0.62) \left( \frac{16,300}{0.85} + 2,000 \right)$$

$$= (31.68) (33,099 \ 19,176 + 2,000)$$

$$= 1,111,936 670,898 \text{ gallons per year}$$

Compare ETWU with MAWA. For this example:

$$MAWA = (51.1) (0.62) [(0.57 \times 50,000) + (0.53 \times 2,000)]$$

$$= 31.68 \times [235,000 + 1,0600]$$

$$= 31.68 \times 35,600 \ 26,000$$

$$= 1,127,808 823,680 \text{ gallons per year}$$

The ETWU (1,111,936 670,898 gallons per year) is less than MAWA (1,127,808 823,680 gallons per year). For this example, the water budget complies with the MAWA.

Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.

**§ 492.5 Soil Management Report.**

(a) In order to reduce runoff and encourage healthy plant growth, a soil management report shall be completed by the project applicant, or his/her designee, as follows:

- (1) Submit soil samples to a laboratory for analysis and recommendations.
  - (A) Soil sampling shall be conducted in accordance with laboratory protocol, including protocols regarding adequate sampling depth for the intended plants.
  - (B) The soil analysis may include:
    - 1. soil texture;
    - 2. infiltration rate determined by laboratory test or soil texture infiltration rate table;

3. pH;
  4. total soluble salts;
  5. sodium;
  6. percent organic matter; and
  7. recommendations.
- (2) The project applicant, or his/her designee, shall comply with one of the following:
- (A) If significant mass grading is not planned, the soil analysis report shall be submitted to the local agency as part of the Landscape Documentation Package; or
  - (B) If significant mass grading is planned, the soil analysis report shall be submitted to the local agency as part of the Certificate of Completion.
- (3) The soil analysis report shall be made available, in a timely manner, to the professionals preparing the landscape design plans and irrigation design plans to make any necessary adjustments to the design plans.
- (4) The project applicant, or his/her designee, shall submit documentation verifying implementation of soil analysis report recommendations to the local agency with Certificate of Completion.

Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.

**§ 492.6 Landscape Design Plan.**

(a) For the efficient use of water, a landscape shall be carefully designed and planned for the intended function of the project. A landscape design plan meeting the following design criteria shall be submitted as part of the Landscape Documentation Package.

(1) Plant Material

(A) Any plant may be selected for the landscape, providing the Estimated Total Water Use in the landscape area does not exceed the Maximum Applied Water Allowance. To encourage the efficient use of water, the following is highly recommended:

1. protection and preservation of native species and natural vegetation;
2. selection of water-conserving plant and turf species, especially local native plants;
3. selection of plants based on local climate suitability, disease and pest resistance;
4. selection of trees based on applicable local tree ordinances or tree shading guidelines, and size at maturity as appropriate for the planting area; and
5. selection of plants from local and regional landscape program plant lists.

(B) Each hydrozone shall have plant materials with similar water use, with the exception of hydrozones with plants of mixed water use, as specified in Section 492.7(a)(2)(D).

(C) Plants shall be selected and planted appropriately based upon their adaptability to the climatic, geologic, and topographical conditions of the project site. To encourage the efficient use of water, the following is highly recommended:

1. use the Sunset Western Climate Zone System which takes into account temperature, humidity, elevation, terrain, latitude, and varying degrees of continental and marine influence on local climate;
2. recognize the horticultural attributes of plants (i.e., mature plant size, invasive surface roots) to minimize damage to property or infrastructure [e.g., buildings, sidewalks, power lines]; and
3. consider the solar orientation for plant placement to maximize summer shade and winter solar gain.

(D) Turf is not allowed on slopes greater than 25% where the toe of the slope is adjacent to an impermeable hardscape and where 25% means 1 foot of vertical elevation change for every 4 feet of horizontal length (rise divided by run x 100 = slope percent).

(E) Turf is prohibited in street medians.

(F) Turf is prohibited in parkways less than 10 feet wide, unless the parkway is adjacent to a parking strip and used to enter and exit vehicles. Any turf in parkways must be irrigated by sub-surface irrigation or by other technology that creates no overspray or runoff.

(G) ~~(E)~~ A landscape design plan for projects in fire-prone areas shall address fire safety and prevention. A defensible space or zone around a building or structure is required per Public Resources Code Section 4291(a) and (b). Avoid fire-prone plant materials and highly flammable mulches.

(H) ~~(F)~~ The use of invasive and/or noxious plant species is strongly discouraged.

(I) ~~(G)~~ The architectural guidelines of a common interest development, which include community apartment projects, condominiums, planned developments, and stock cooperatives, shall not prohibit or include conditions that have the effect of prohibiting the use of low-water use plants as a group.

## (2) Water Features

(A) Recirculating water systems shall be used for water features.

(B) Where available, recycled water shall be used as a source for decorative water features.

(C) Surface area of a water feature shall be included in the high water use hydrozone area of the water budget calculation.

(D) Pool and spa covers **are highly recommended shall be provided.**

(E) Recreational water features (swimming pools, splash pads or similar) must recirculate water.

## (3) Soil Preparation, Mulch and Amendments

(A) Prior to the planting of any materials, compacted soils shall be transformed to a friable condition.

(B) Soil amendments shall be incorporated according to recommendations of the soil report and what is appropriate for the plants selected (see Section 492.5).

(C) For landscape installations, compost at a rate of a minimum of four cubic yards per 1,000 square feet of permeable area (unless contra-indicated by soil test) shall be incorporated to a depth of six inches into the soil. Soils with greater than 25% organic matter in the top 6 inches of soil are exempt from adding compost.

(D) ~~(A)~~ A minimum ~~two~~ three inch (23") layer of mulch shall be applied on all exposed soil surfaces of planting areas except in turf areas, creeping or rooting groundcovers, or direct seeding applications where mulch is contraindicated.

(E) ~~(B)~~ Stabilizing mulching products shall be used on slopes.

(F) ~~(C)~~ The mulching portion of the seed/mulch slurry in hydro-seeded applications shall meet the mulching requirement.

(G) Organic mulch materials should take precedence over inorganic materials in instances where it is suitable, ecologically possible, and the material does not pose a fire hazard. Composted organic material, in particular that which includes post-consumer material, should be considered over more compacted products such as bark, wood chips, etc.

~~(D) Soil amendments shall be incorporated according to recommendations of the soil report and what is appropriate for the plants selected (see Section 492.5).~~

(b) The landscape design plan, at a minimum, shall:

(1) delineate and label each hydrozone by number, letter, or other method;

- (2) identify each hydrozone as low, moderate, high water, or mixed water use. Temporarily irrigated areas of the landscape shall be included in the low water use hydrozone for the water budget calculation;
- (3) identify recreational areas;
- (4) identify areas permanently and solely dedicated to edible plants;
- (5) identify areas irrigated with recycled water;
- (6) identify type of mulch and application depth;
- (7) identify soil amendments, type, and quantity;
- (8) identify type and surface area of water features;
- (9) identify hardscapes (pervious and non-pervious);
- (10) identify location, installation details, and 24-hour retention or infiltration capacity of any applicable stormwater best management practices that encourage on-site retention and infiltration of stormwater. Stormwater best management practices are encouraged in the landscape design plan and examples ~~include, but are not limited to:~~ are provide in Section 492.16.
  - (A) ~~infiltration beds, swales, and basins that allow water to collect and soak into the ground;~~
  - (B) ~~constructed wetlands and retention ponds that retain water, handle excess flow, and filter pollutants; and~~
  - (C) ~~pervious or porous surfaces (e.g., permeable pavers or blocks, pervious or porous concrete, etc.) that minimize runoff.~~
- (11) identify any applicable rain harvesting or catchment technologies (~~e.g., rain gardens, eisterns, etc.~~) as discussed in Section 492.16 and their 24-hour retention or infiltration capacity;
- (12) identify any applicable graywater discharge piping, system components and area(s) of distribution;
- (13) ~~(12)~~ contain the following statement: "I have complied with the criteria of the ordinance and applied them for the efficient use of water in the landscape design plan"; and
- (14) ~~(13)~~ bear the signature of a licensed landscape architect, licensed landscape contractor, landscape designer or any other person authorized to design a landscape. (See Sections 5500.1, 5615, 5641, 5641.1, 5641.2, 5641.3, 5641.4, 5641.5, 5641.6, 6701, 7027.5 of the Business and Professions Code, Section 832.27 of Title 16 of the California Code of Regulations, and Section 6721 of the Food and Agriculture Code.)

Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code and Section 1351, Civil Code.

### § 492.7 Irrigation Design Plan.

(a) This section applies to landscaped areas requiring permanent irrigation, not areas that require temporary irrigation solely for the plant establishment period. For the efficient use of water, an irrigation system shall meet all the requirements listed in this section and the manufacturers' recommendations. The irrigation system and its related components shall be planned and designed to allow for proper installation, management, and maintenance. An irrigation design plan meeting the following design criteria shall be submitted as part of the Landscape Documentation Package.

#### (1) System

(A) ~~Dedicated landscape water meters are highly recommended on landscape areas smaller than 5,000 square feet to facilitate water management shall be required for all non-residential irrigated landscapes of 1,000 500 sq. ft. but not more than 5,000sq.ft. (the level at which Water Code 535 applies)-and residential irrigated landscapes of 5,000 500 sq. ft. or greater. A landscape water meter may be either:~~

1. a customer service meter dedicated to landscape use provided by the local water purveyor; or

2. a privately owned meter or submeter.
- (B) Automatic irrigation controllers utilizing either evapotranspiration or soil moisture sensor data and non-volatile memory shall be required for irrigation scheduling in all irrigation systems.
- (C) The installation of a pressure regulator is required ~~The irrigation systems shall be designed~~ to ensure that the dynamic pressure at each emission device is within the manufacturer's recommended pressure range for optimal performance.
1. If the static pressure is above or below the required dynamic pressure of the irrigation system, pressure-regulating devices such as inline pressure regulators, booster pumps, or other devices shall be installed to meet the required dynamic pressure of the irrigation system.
  2. Static water pressure, dynamic or operating pressure and flow reading of the water supply shall be measured at the point of connection. These pressure and flow measurements shall be conducted at the design stage. If the measurements are not available at the design stage, the measurements shall be conducted at installation.
- (D) Sensors (rain, freeze, wind, etc.), either integral or auxiliary, that suspend or alter irrigation operation during unfavorable weather conditions shall be required on all irrigation systems, as appropriate for local climatic conditions. Irrigation should be avoided during windy or freezing weather or during rain.
- (E) Manual shut-off valves (such as a gate valve, ball valve, or butterfly valve) shall be required, as close as possible to the point of connection of the water supply, to minimize water loss in case of an emergency (such as a main line break) or routine repair.
- (F) Backflow prevention devices shall be required to protect the water supply from contamination by the irrigation system. A project applicant shall refer to the applicable local agency code (i.e., public health) for additional backflow prevention requirements.
- (G) ~~High F~~ flow sensors that detect ~~and report~~ high flow conditions created by system damage or malfunction are ~~recommended~~ required.
- (H) Master valves are required on all projects.
- (I) ~~(H)~~ The irrigation system shall be designed to prevent runoff, low head drainage, overspray, or other similar conditions where irrigation water flows onto non-targeted areas, such as adjacent property, non-irrigated areas, hardscapes, roadways, or structures.
- (J) ~~(H)~~ Relevant information from the soil management plan, such as soil type and infiltration rate, shall be utilized when designing irrigation systems.
- (K) ~~(J)~~ The design of the irrigation system shall conform to the hydrozones of the landscape design plan.
- (L) ~~(K)~~ The irrigation system must be designed and installed to meet, at a minimum, the irrigation efficiency criteria as described in Section 492.4 regarding the Maximum Applied Water Allowance.
- (M) The irrigation system must be designed and installed in such a manner that a precipitation rate of 1.0 inches per hour is not exceeded in any portion of the landscape.
- (N) ~~(L)~~ It is highly recommended that the project applicant or local agency inquire with the local water purveyor about peak water operating demands (on the water supply system) or water restrictions that may impact the effectiveness of the irrigation system.
- (O) ~~(M)~~ In mulched planting areas, the use of low volume irrigation is required to maximize water infiltration into the root zone.
- (P) ~~(N)~~ Sprinkler heads and other emission devices shall have matched precipitation rates, unless otherwise directed by the manufacturer's recommendations.

~~(Q)~~ ~~(Θ)~~ Head to head coverage is recommended. However, sprinkler spacing shall be designed to achieve the highest possible distribution uniformity using the manufacturer's recommendations.

~~(R)~~ ~~(P)~~ Swing joints or other riser-protection components are required on all risers subject to damage that are adjacent to hardscapes or in high traffic areas of turfgrass.

~~(S)~~ ~~(Q)~~ Check valves or anti-drain valves are required for all irrigation systems.

~~(T)~~ ~~(R)~~ ~~Narrow or irregularly shaped~~ Areas of, including turf, less than ten~~eight~~ (10~~8~~) feet in width in any direction shall be irrigated with subsurface irrigation or ~~low volume irrigation system other technology that produces no runoff or overspray.~~

~~(U)~~ ~~(S)~~ Overhead irrigation shall not be permitted within 24 inches of any non-permeable surface. Allowable irrigation within the setback from non-permeable surfaces may include drip, drip line, or other low flow non-spray technology. The setback area may be planted or unplanted. The surfacing of the setback may be mulch, gravel, or other porous material. These restrictions may be modified if:

1. the landscape area is adjacent to permeable surfacing and no runoff occurs; or
2. the adjacent non-permeable surfaces are designed and constructed to drain entirely to landscaping; or
3. the irrigation designer specifies an alternative design or technology, as part of the Landscape Documentation Package and clearly demonstrates strict adherence to irrigation system design criteria in Section 492.7 (a)(1)~~(IH)~~. Prevention of overspray and runoff must be confirmed during the irrigation audit.

~~(V)~~ Slopes greater than 25% shall not be irrigated with an irrigation system with a precipitation rate exceeding 0.75 inches per hour. This restriction may be modified if the landscape designer specifies an alternative design or technology, as part of the Landscape Documentation Package, and clearly demonstrates no runoff or erosion will occur. Prevention of runoff and erosion must be confirmed during the irrigation audit.

## (2) Hydrozone

(A) Each valve shall irrigate a hydrozone with similar site, slope, sun exposure, soil conditions, and plant materials with similar water use.

(B) Sprinkler heads and other emission devices shall be selected based on what is appropriate for the plant type within that hydrozone.

(C) Where feasible, trees shall be placed on separate valves from shrubs, groundcovers, and turf to facilitate the appropriate irrigation of trees.

(D) Individual hydrozones that mix plants of moderate and low water use, or moderate and high water use, may be allowed if:

1. plant factor calculation is based on the proportions of the respective plant water uses and their plant factor; or
2. the plant factor of the higher water using plant is used for calculations.

(E) Individual hydrozones that mix high and low water use plants shall not be permitted.

(F) On the landscape design plan and irrigation design plan, hydrozone areas shall be designated by number, letter, or other designation. On the irrigation design plan, designate the areas irrigated by each valve, and assign a number to each valve. Use this valve number in the Hydrozone Information Table (see Appendix B Section A). This table can also assist with the irrigation audit and programming the controller.

(b) The irrigation design plan, at a minimum, shall contain:

- (1) location and size of separate water meters for landscape;
- (2) location, type and size of all components of the irrigation system, including controllers, main and lateral lines, valves, sprinkler heads, moisture sensing devices, rain switches, quick couplers, pressure regulators, and backflow prevention devices;
- (3) static water pressure at the point of connection to the public water supply;

- (4) flow rate (gallons per minute), application rate (inches per hour), and design operating pressure (pressure per square inch) for each station;
- (5) recycled water irrigation systems as specified in Section 492.14;
- (6) the following statement: “I have complied with the criteria of the ordinance and applied them accordingly for the efficient use of water in the irrigation design plan”; and
- (7) the signature of a licensed landscape architect, certified irrigation designer, licensed landscape contractor, or any other person authorized to design an irrigation system. (See Sections 5500.1, 5615, 5641, 5641.1, 5641.2, 5641.3, 5641.4, 5641.5, 5641.6, 6701, 7027.5 of the Business and Professions Code, Section 832.27 of Title 16 of the California Code of Regulations, and Section 6721 of the Food and Agricultural Code.)

Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.

**§ 492.8 Grading Design Plan.**

(a) For the efficient use of water, grading of a project site shall be designed to minimize soil erosion, runoff, and water waste. A grading plan shall be submitted as part of the Landscape Documentation Package. A comprehensive grading plan prepared by a civil engineer for other local agency permits satisfies this requirement.

- (1) The project applicant shall submit a landscape grading plan that indicates finished configurations and elevations of the landscape area including:
  - (A) height of graded slopes;
  - (B) drainage patterns;
  - (C) pad elevations;
  - (D) finish grade; and
  - (E) stormwater retention improvements, if applicable.
- (2) To prevent excessive erosion and runoff, it is highly recommended that project applicants:
  - (A) grade so that all irrigation and normal rainfall remains within property lines and does not drain on to non-permeable hardscapes;
  - (B) avoid disruption of natural drainage patterns and undisturbed soil; and
  - (C) avoid soil compaction in landscape areas.
- (3) The grading design plan shall contain the following statement: “I have complied with the criteria of the ordinance and applied them accordingly for the efficient use of water in the grading design plan” and shall bear the signature of a licensed professional as authorized by law.

Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.

**§ 492.9 Certificate of Completion.**

- (a) The Certificate of Completion (see Appendix C for a sample certificate) shall include the following six (6) elements:
  - (1) project information sheet that contains:
    - (A) date;
    - (B) project name;
    - (C) project applicant name, telephone, and mailing address;
    - (D) project address and location; and
    - (E) property owner name, telephone, and mailing address;
  - (2) certification by either the signer of the landscape design plan, the signer of the irrigation design plan, or the licensed landscape contractor that the landscape project has been installed per the approved Landscape Documentation Package;
    - (A) where there have been significant changes made in the field during construction, these “as-built” or record drawings shall be included with the certification;

- (3) irrigation scheduling parameters used to set the controller (see Section 492.10);
  - (4) landscape and irrigation maintenance schedule (see Section 492.11);
  - (5) irrigation audit report (see Section 492.12); and
  - (6) soil analysis report, if not submitted with Landscape Documentation Package, and documentation verifying implementation of soil report recommendations (see Section 492.5).
- (b) The project applicant shall:
- (1) submit the signed Certificate of Completion to the local agency for review;
  - (2) ensure that copies of the approved Certificate of Completion are submitted to the local water purveyor and property owner or his or her designee.
- (c) The local agency shall:
- (1) receive the signed Certificate of Completion from the project applicant;
  - (2) approve or deny the Certificate of Completion. If the Certificate of Completion is denied, the local agency shall provide information to the project applicant regarding reapplication, appeal, or other assistance.

Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.

**§ 492.10 Irrigation Scheduling.**

(a) For the efficient use of water, all irrigation schedules shall be developed, managed, and evaluated to utilize the minimum amount of water required to maintain plant health. Irrigation schedules shall meet the following criteria:

- (1) Irrigation scheduling shall be regulated by automatic irrigation controllers.
- (2) Overhead irrigation shall be scheduled between 8:00 p.m. and 10:00 a.m. unless weather conditions prevent it. If allowable hours of irrigation differ from the local water purveyor, the stricter of the two shall apply. Operation of the irrigation system outside the normal watering window is allowed for auditing and system maintenance.
- (3) For implementation of the irrigation schedule, particular attention must be paid to irrigation run times, emission device, flow rate, and current reference evapotranspiration, so that applied water meets the Estimated Total Water Use. Total annual applied water shall be less than or equal to Maximum Applied Water Allowance (MAWA). Actual irrigation schedules shall be regulated by automatic irrigation controllers using current reference evapotranspiration data (e.g., CIMIS) or soil moisture sensor data.
- (4) Parameters used to set the automatic controller shall be developed and submitted for each of the following:
  - (A) the plant establishment period;
  - (B) the established landscape; and
  - (C) temporarily irrigated areas.
- (5) Each irrigation schedule shall consider for each station all of the following that apply:
  - (A) irrigation interval (days between irrigation);
  - (B) irrigation run times (hours or minutes per irrigation event to avoid runoff);
  - (C) number of cycle starts required for each irrigation event to avoid runoff;
  - (D) amount of applied water scheduled to be applied on a monthly basis;
  - (E) application rate setting;
  - (F) root depth setting;
  - (G) plant type setting;
  - (H) soil type;
  - (I) slope factor setting;
  - (J) shade factor setting; and
  - (K) irrigation uniformity or efficiency setting.

Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.

**§ 492.11 Landscape and Irrigation Maintenance Schedule.**

(a) Landscapes shall be maintained to ensure water use efficiency. A regular maintenance schedule shall be submitted with the Certificate of Completion.

(b) A regular maintenance schedule shall include, but not be limited to, routine inspection; adjustment and repair of the irrigation system and its components; aerating and dethatching turf areas; replenishing mulch; fertilizing biologically-based, organic soil and plant-health building materials; pruning; weeding in all landscape areas, and removing and obstruction to emission devices. Operation of the irrigation system outside the normal watering window is allowed for auditing and system maintenance.

(c) Repair of all irrigation equipment shall be done with the originally installed components, or their equivalents, or components with greater water efficiency.

(d) A project applicant is encouraged to implement sustainable Best Practices ~~or environmentally-friendly practices~~ for overall all landscape maintenance activities.

Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.

**§ 492.12 Irrigation Audit, Irrigation Survey, and Irrigation Water Use Analysis.**

(a) All landscape irrigation audits shall be conducted by a local agency irrigation auditor or a third party certified landscape irrigation auditor that is not the designer or installer of the landscape.

(b) For new construction and rehabilitated landscape projects installed after January 1, 2010, as described in Section 490.1:

(1) the project applicant shall submit an irrigation audit report with the Certificate of Completion to the local agency that may include, but is not limited to: inspection, system tune-up, system test with distribution uniformity, reporting overspray or run off that causes overland flow, and preparation of an irrigation schedule;

(2) the local agency shall administer programs that may include, but not be limited to, irrigation water use analysis, irrigation audits, and irrigation surveys for compliance with the Maximum Applied Water Allowance.

Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.

**§ 492.13 Irrigation Efficiency.**

(a) For the purpose of determining Maximum Applied Water Allowance, average irrigation efficiency is assumed to be 0.8571 for residential areas and 0.92 for non-residential areas. Irrigation systems shall be designed, maintained, and managed to meet or exceed a site-wide ~~an~~ average landscape irrigation efficiency of 0.8571 for residential areas and 0.92 for non-residential areas.

Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.

**§ 492.14 Recycled Water.**

(a) The installation of recycled water irrigation systems shall allow for the current and future use of recycled water, unless a written exemption has been granted as described in Section 492.14(b).

(b) Irrigation systems and decorative water features shall use recycled water unless a written exemption has been granted by the local water purveyor stating that recycled water meeting all public health codes and standards is not available and will not be available for the foreseeable future.

(c) All recycled water irrigation systems shall be designed and operated in accordance with all applicable local and State laws.

(d) Landscapes using recycled water are considered Special Landscape Areas. The ET Adjustment Factor for Special Landscape Areas shall not exceed 1.0.

Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.

**§ 492.15 Graywater Systems.**

- (a) Graywater systems promote the efficient use of water and are encouraged to assist in on-site landscape irrigation. All graywater systems shall conform to the California Plumbing Code (Title 24, Part 5, Chapter 16) and any applicable local ordinance standards.

### **§ 492.165 Stormwater Management and Rainwater Retention.**

(a) Stormwater management practices minimize runoff and increase infiltration which recharges groundwater and improves water quality. Implementing stormwater best management practices into the landscape and grading design plans to minimize runoff and to increase on-site rainwater retention and infiltration are encouraged.

(b) Project applicants shall refer to the local agency or Regional Water Quality Control Board for information on any applicable stormwater ordinances and stormwater management plans.

(c) All planted landscape areas are required to have friable soil to maximize water retention and infiltration. Refer to § 492.6(a)(3).

(d) (e) It is strongly recommended that Landscape areas shall be designed such that the retention and infiltration capacity is sufficient to prevent runoff from roof surfaces and the landscape area from either the one inch, 24-hour rain event or the 85<sup>th</sup> percentile, 24-hour rain event, and such additional capacity, if any, as may be required by any applicable local, ~~or~~ regional, or state regulation, shall be provided.

(e) (d) It is recommended that project also incorporate any of the following elements to improve on-site stormwater retention:

- Grade impervious surfaces, such as driveways, during construction to drain to vegetated areas.
- Minimize the area of impervious surfaces such as paved areas, roof and concrete driveways.
- Incorporate pervious or porous surfaces (e.g., permeable pavers or blocks, pervious or porous concrete, gravel, etc.) that minimize runoff.
- Direct runoff from paved surfaces and roof areas into planting beds or landscaped areas **graded** to maximize site water retention.
- Incorporate rain gardens, **rain tanks**, cisterns, and other rain harvesting or catchment.
- Incorporate infiltration **trenches/beds**, swales, basins and drywells to retain stormwater and increase percolation into the soil.
- Consider constructed wetlands and retention ponds that retain water, handle excess flow, and filter pollutants.

~~(e) Rain gardens, cisterns, and other landscapes features and practices that increase rainwater capture and create opportunities for infiltration and/or onsite storage are recommended.~~

~~(e) It is strongly recommended that retention and infiltration capacity sufficient to prevent runoff from roof surfaces and the landscape area from either the one inch, 24-hour rain event or the 85<sup>th</sup> percentile, 24-hour rain event, and such additional capacity, if any, as may be required by any applicable local or regional regulation, be provided.~~

Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.

### **§ 492.176 Public Education.**

(a) Publications. Education is a critical component to promote the efficient use of water in landscapes. The use of appropriate principles of design, installation, management and maintenance that save water is encouraged in the community.

(1) A local agency or water supplier/purveyor shall provide information to owners of permitted renovations and new single-family residential homes regarding the design, installation, management, and maintenance of water efficient landscapes based on a water budget.

(b) Model Homes. All model homes shall be landscaped and ~~that are landscaped shall~~ use signs and written information to demonstrate the principles of water efficient landscapes described in this ordinance.

(1) Signs shall be used to identify the model as an example of a water efficient landscape featuring elements such as hydrozones, irrigation equipment, and others that contribute to the overall water efficient theme. Signage shall include information about the site water use as

designed per the local ordinance; specify who designed and installed the water efficient landscape; and demonstrate low water use approaches to landscaping such as using native plants, graywater systems, and rainwater catchment systems.

(2) Information shall be provided about designing, installing, managing, and maintaining water efficient landscapes. Information available shall include detailed specifications on how to hire trained and licensed landscape architects, contractors, designers and maintenance workers and the benefits of using such professionals.

Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.

#### **§ 492.187 Environmental Review.**

(a) The local agency must comply with the California Environmental Quality Act (CEQA), as appropriate.

Note: Authority cited: Section 21082, Public Resources Code. Reference: Sections 21080, 21082, Public Resources Code.

#### **§ 493. Provisions for Existing Landscapes.**

(a) A local agency may designate another agency, such as a water purveyor, to implement some or all of the requirements contained in this ordinance. Local agencies may collaborate with water purveyors to define each entity's specific responsibilities relating to this ordinance.

Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.

#### **§ 493.1 Irrigation Audit, Irrigation Survey, and Irrigation Water Use Analysis.**

(a) This section, 493.1, shall apply to all existing landscapes that were installed before ~~January 1, 2010~~ November 1, 2015 and are over one acre in size.

(1) For all landscapes in 493.1(a) that have a water meter, the local agency shall administer programs that may include, but not be limited to, irrigation water use analyses, irrigation surveys, and irrigation audits to evaluate water use and provide recommendations as necessary to reduce landscape water use to a level that does not exceed the Maximum Applied Water Allowance for existing landscapes. The Maximum Applied Water Allowance for existing landscapes shall be calculated as:  $MAWA = (0.8) (ET_o)(LA)(0.62)$ .

(2) For all landscapes in 493.1(a), that do not have a meter, the local agency shall administer programs that may include, but not be limited to, irrigation surveys and irrigation audits to evaluate water use and provide recommendations as necessary in order to prevent water waste.

(b) All landscape irrigation audits shall be conducted by a certified landscape irrigation auditor.

Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.

#### **§ 493.2 Water Waste Prevention.**

(a) Local agencies shall prevent water waste resulting from inefficient landscape irrigation by prohibiting runoff from leaving the target landscape due to low head drainage, overspray, or other similar conditions where water flows onto adjacent property, non-irrigated areas, walks, roadways, parking lots, or structures. Penalties for violation of these prohibitions shall be established locally.

(b) Restrictions regarding overspray and runoff may be modified if:

(1) the landscape area is adjacent to permeable surfacing and no runoff occurs; or

(2) the adjacent non-permeable surfaces are designed and constructed to drain entirely to landscaping.

Note: Authority cited: Section 65594, Government Code. Reference: Section 65596, Government Code.

**§ 494. Effective Precipitation.**

(a) A local agency may consider Effective Precipitation (25% of annual precipitation) in tracking water use and may use the following equation to calculate Maximum Applied Water Allowance:

MAWA = (ET<sub>o</sub> - Eppt) (0.62) [(0.57 x LA) + (0.53 x SLA)] for residential areas.

MAWA = (ET<sub>o</sub> - Eppt) (0.62) [(0.4 x LA) + (0.6 x SLA)] for non-residential areas.

Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.

**§ 495. Reporting.**

(a) Local agencies responsible for administering the ordinance shall report on implementation and enforcement by December 31, 2015. Subsequently, reporting will be due by January 31<sup>st</sup> of each year.

Reports should be submitted as follows.

(b) Local agencies are to address the following:

- (1) Define the reporting period. For the initial reporting, local agencies are encouraged to report as far back as records for implementation of their ordinances allow. At a minimum, the reporting period shall commence on November 1, 2015. The end of the reporting period shall be no sooner than December 15, 2015. In subsequent years, reporting will be for the calendar year.
- (2) State if using a locally modified Water Efficient Landscape Ordinance (WELO) or the MWELO. If using a locally modified WELO, how is it different than MWELO, and are there any exemptions specified?
- (3) State the entity responsible for implementing the ordinance.
- (4) State number and types of projects subject to the ordinance during the specified reporting period.
- (5) State the total area (in square feet or acres) subject to the ordinance over the reporting period, if available.
- (6) Provide the number of new housing starts, new commercial projects, and landscape retrofits during the reporting period.
- (7) Describe the procedure for review of projects subject to the ordinance.
- (8) Describe actions taken to verify compliance. Is a plan check performed; if so, by what entity? Is a site inspection performed; if so, by what entity? Is a post-installation audit required; if so, by whom?
- (9) Describe enforcement measures.
- (10) Explain challenges to implementing and enforcing the ordinance.
- (11) Describe educational and other needs to properly apply the ordinance.

**Appendices.**

**Appendix A. Reference Evapotranspiration (ET<sub>o</sub>) Table.**

<b>County and City</b>	<b>Jan</b>	<b>Feb</b>	<b>Mar</b>	<b>Apr</b>	<b>May</b>	<b>Jun</b>	<b>Jul</b>	<b>Aug</b>	<b>Sep</b>	<b>Oct</b>	<b>Nov</b>	<b>Dec</b>	<b>Annual ET<sub>o</sub></b>
<b>ALAMEDA</b>													
Fremont	1.5	1.9	3.4	4.7	5.4	6.3	6.7	6.0	4.5	3.4	1.8	1.5	47.0
Livermore	1.2	1.5	2.9	4.4	5.9	6.6	7.4	6.4	5.3	3.2	1.5	0.9	47.2
Oakland	1.5	1.5	2.8	3.9	5.1	5.3	6.0	5.5	4.8	3.1	1.4	0.9	41.8
Oakland Foothills	1.1	1.4	2.7	3.7	5.1	6.4	5.8	4.9	3.6	2.6	1.4	1.0	39.6
Pleasanton	0.8	1.5	2.9	4.4	5.6	6.7	7.4	6.4	4.7	3.3	1.5	1.0	46.2
Union City	1.4	1.8	3.1	4.2	5.4	5.9	6.4	5.7	4.4	3.1	1.5	1.2	44.2
<b>ALPINE</b>													
Markleeville	0.7	0.9	2.0	3.5	5.0	6.1	7.3	6.4	4.4	2.6	1.2	0.5	40.6
<b>AMADOR</b>													
Jackson	1.2	1.5	2.8	4.4	6.0	7.2	7.9	7.2	5.3	3.2	1.4	0.9	48.9
Shanandoah Valley	1.0	1.7	2.9	4.4	5.6	6.8	7.9	7.1	5.2	3.6	1.7	1.0	48.8
<b>BUTTE</b>													
Chico	1.2	1.8	2.9	4.7	6.1	7.4	8.5	7.3	5.4	3.7	1.7	1.0	51.7
Durham	1.1	1.8	3.2	5.0	6.5	7.4	7.8	6.9	5.3	3.6	1.7	1.0	51.1
Gridley	1.2	1.8	3.0	4.7	6.1	7.7	8.5	7.1	5.4	3.7	1.7	1.0	51.9
Oroville	1.2	1.7	2.8	4.7	6.1	7.6	8.5	7.3	5.3	3.7	1.7	1.0	51.5
<b>CALAVERAS</b>													
San Andreas	1.2	1.5	2.8	4.4	6.0	7.3	7.9	7.0	5.3	3.2	1.4	0.7	48.8
<b>COLUSA</b>													
Colusa	1.0	1.7	3.4	5.0	6.4	7.6	8.3	7.2	5.4	3.8	1.8	1.1	52.8
Williams	1.2	1.7	2.9	4.5	6.1	7.2	8.5	7.3	5.3	3.4	1.6	1.0	50.8
<b>CONTRA COSTA</b>													
<del>Benicia</del>	<del>1.3</del>	<del>1.4</del>	<del>2.7</del>	<del>3.8</del>	<del>4.9</del>	<del>5.0</del>	<del>6.4</del>	<del>5.5</del>	<del>4.4</del>	<del>2.9</del>	<del>1.2</del>	<del>0.7</del>	<del>40.3</del>
Brentwood	1.0	1.5	2.9	4.5	6.1	7.1	7.9	6.7	5.2	3.2	1.4	0.7	48.3
Concord	1.1	1.4	2.4	4.0	5.5	5.9	7.0	6.0	4.8	3.2	1.3	0.7	43.4
Courtland	0.9	1.5	2.9	4.4	6.1	6.9	7.9	6.7	5.3	3.2	1.4	0.7	48.0
Martinez	1.2	1.4	2.4	3.9	5.3	5.6	6.7	5.6	4.7	3.1	1.2	0.7	41.8
Moraga	1.2	1.5	3.4	4.2	5.5	6.1	6.7	5.9	4.6	3.2	1.6	1.0	44.9
Pittsburg	1.0	1.5	2.8	4.1	5.6	6.4	7.4	6.4	5.0	3.2	1.3	0.7	45.4
Walnut Creek	0.8	1.5	2.9	4.4	5.6	6.7	7.4	6.4	4.7	3.3	1.5	1.0	46.2
<b>DEL NORTE</b>													
Crescent City	0.5	0.9	2.0	3.0	3.7	3.5	4.3	3.7	3.0	2.0	0.9	0.5	27.7
<b>EL DORADO</b>													
Camino	0.9	1.7	2.5	3.9	5.9	7.2	7.8	6.8	5.1	3.1	1.5	0.9	47.3
<b>FRESNO</b>													
Clovis	1.0	1.5	3.2	4.8	6.4	7.7	8.5	7.3	5.3	3.4	1.4	0.7	51.4
Coalinga	1.2	1.7	3.1	4.6	6.2	7.2	8.5	7.3	5.3	3.4	1.6	0.7	50.9
Firebaugh	1.0	1.8	3.7	5.7	7.3	8.1	8.2	7.2	5.5	3.9	2.0	1.1	55.4
FivePoints	1.3	2.0	4.0	6.1	7.7	8.5	8.7	8.0	6.2	4.5	2.4	1.2	60.4
Fresno	0.9	1.7	3.3	4.8	6.7	7.8	8.4	7.1	5.2	3.2	1.4	0.6	51.1
Fresno State	0.9	1.6	3.2	5.2	7.0	8.0	8.7	7.6	5.4	3.6	1.7	0.9	53.7
Friant	1.2	1.5	3.1	4.7	6.4	7.7	8.5	7.3	5.3	3.4	1.4	0.7	51.3
Kerman	0.9	1.5	3.2	4.8	6.6	7.7	8.4	7.2	5.3	3.4	1.4	0.7	51.2
Kingsburg	1.0	1.5	3.4	4.8	6.6	7.7	8.4	7.2	5.3	3.4	1.4	0.7	51.6
Mendota	1.5	2.5	4.6	6.2	7.9	8.6	8.8	7.5	5.9	4.5	2.4	1.5	61.7
Orange Cove	1.2	1.9	3.5	4.7	7.4	8.5	8.9	7.9	5.9	3.7	1.8	1.2	56.7

## Appendix A. Reference Evapotranspiration (ET<sub>o</sub>) Table.

County and City	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Annual ET <sub>o</sub>
Panoche	1.1	2.0	4.0	5.6	7.8	8.5	8.3	7.3	5.6	3.9	1.8	1.2	57.2
Parlier	1.0	1.9	3.6	5.2	6.8	7.6	8.1	7.0	5.1	3.4	1.7	0.9	52.0
Reedley	1.1	1.5	3.2	4.7	6.4	7.7	8.5	7.3	5.3	3.4	1.4	0.7	51.3
Westlands	0.9	1.7	3.8	6.3	8.0	8.6	8.6	7.8	5.9	4.3	2.1	1.1	58.8
<b>GLENN</b>													
Orland	1.1	1.8	3.4	5.0	6.4	7.5	7.9	6.7	5.3	3.9	1.8	1.4	52.1
Willows	1.2	1.7	2.9	4.7	6.1	7.2	8.5	7.3	5.3	3.6	1.7	1.0	51.3
<b>HUMBOLDT</b>													
Eureka	0.5	1.1	2.0	3.0	3.7	3.7	3.7	3.7	3.0	2.0	0.9	0.5	27.5
Ferndale	0.5	1.1	2.0	3.0	3.7	3.7	3.7	3.7	3.0	2.0	0.9	0.5	27.5
Garberville	0.6	1.2	2.2	3.1	4.5	5.0	5.5	4.9	3.8	2.4	1.0	0.7	34.9
Hoopa	0.5	1.1	2.1	3.0	4.4	5.4	6.1	5.1	3.8	2.4	0.9	0.7	35.6
<b>IMPERIAL</b>													
Brawley	2.8	3.8	5.9	8.0	10.4	11.5	11.7	10.0	8.4	6.2	3.5	2.1	84.2
Calipatria/Mulberry	2.4	3.2	5.1	6.8	8.6	9.2	9.2	8.6	7.0	5.2	3.1	2.3	70.7
El Centro	2.7	3.5	5.6	7.9	10.1	11.1	11.6	9.5	8.3	6.1	3.3	2.0	81.7
Holtville	2.8	3.8	5.9	7.9	10.4	11.6	12.0	10.0	8.6	6.2	3.5	2.1	84.7
Meloland	2.5	3.2	5.5	7.5	8.9	9.2	9.0	8.5	6.8	5.3	3.1	2.2	71.6
Palo Verde II	2.5	3.3	5.7	6.9	8.5	8.9	8.6	7.9	6.2	4.5	2.9	2.3	68.2
Seeley	2.7	3.5	5.9	7.7	9.7	10.1	9.3	8.3	6.9	5.5	3.4	2.2	75.4
Westmoreland	2.4	3.3	5.3	6.9	8.7	9.6	9.6	8.7	6.9	5.0	3.0	2.2	71.4
Yuma	2.5	3.4	5.3	6.9	8.7	9.6	9.6	8.7	6.9	5.0	3.0	2.2	71.6
<b>INYO</b>													
Bishop	1.7	2.7	4.8	6.7	8.2	10.9	7.4	9.6	7.4	4.8	2.5	1.6	68.3
Death Valley Jct	2.2	3.3	5.4	7.7	9.8	11.1	11.4	10.1	8.3	5.4	2.9	1.7	79.1
Independence	1.7	2.7	3.4	6.6	8.5	9.5	9.8	8.5	7.1	3.9	2.0	1.5	65.2
Lower Haiwee Res.	1.8	2.7	4.4	7.1	8.5	9.5	9.8	8.5	7.1	4.2	2.6	1.5	67.6
Oasis	2.7	2.8	5.9	8.0	10.4	11.7	11.6	10.0	8.4	6.2	3.4	2.1	83.1
<b>KERN</b>													
Arvin	1.2	1.8	3.5	4.7	6.6	7.4	8.1	7.3	5.3	3.4	1.7	1.0	51.9
Bakersfield	1.0	1.8	3.5	4.7	6.6	7.7	8.5	7.3	5.3	3.5	1.6	0.9	52.4
Bakersfield/Bonanza	1.2	2.2	3.7	5.7	7.4	8.2	8.7	7.8	5.7	4.0	2.1	1.2	57.9
Bakersfield/Greenlee	1.2	2.2	3.7	5.7	7.4	8.2	8.7	7.8	5.7	4.0	2.1	1.2	57.9
Belridge	1.4	2.2	4.1	5.5	7.7	8.5	8.6	7.8	6.0	3.8	2.0	1.5	59.2
Blackwells Corner	1.4	2.1	3.8	5.4	7.0	7.8	8.5	7.7	5.8	3.9	1.9	1.2	56.6
Buttonwillow	1.0	1.8	3.2	4.7	6.6	7.7	8.5	7.3	5.4	3.4	1.5	0.9	52.0
China Lake	2.1	3.2	5.3	7.7	9.2	10.0	11.0	9.8	7.3	4.9	2.7	1.7	74.8
Delano	0.9	1.8	3.4	4.7	6.6	7.7	8.5	7.3	5.4	3.4	1.4	0.7	52.0
Famoso	1.3	1.9	3.5	4.8	6.7	7.6	8.0	7.3	5.5	3.5	1.7	1.3	53.1
Grapevine	1.3	1.8	3.1	4.4	5.6	6.8	7.6	6.8	5.9	3.4	1.9	1.0	49.5
Inyokern	2.0	3.1	4.9	7.3	8.5	9.7	11.0	9.4	7.1	5.1	2.6	1.7	72.4
Isabella Dam	1.2	1.4	2.8	4.4	5.8	7.3	7.9	7.0	5.0	3.2	1.7	0.9	48.4
Lamont	1.3	2.4	4.4	4.6	6.5	7.0	8.8	7.6	5.7	3.7	1.6	0.8	54.4
Lost Hills	1.6	2.2	3.7	5.1	6.8	7.8	8.7	7.8	5.7	4.0	2.1	1.6	57.1
McFarland/Kern	1.2	2.1	3.7	5.6	7.3	8.0	8.3	7.4	5.6	4.1	2.0	1.2	56.5
Shafter	1.0	1.7	3.4	5.0	6.6	7.7	8.3	7.3	5.4	3.4	1.5	0.9	52.1
Taft	1.3	1.8	3.1	4.3	6.2	7.3	8.5	7.3	5.4	3.4	1.7	1.0	51.2
Tehachapi	1.4	1.8	3.2	5.0	6.1	7.7	7.9	7.3	5.9	3.4	2.1	1.2	52.9

**Appendix A. Reference Evapotranspiration (ET<sub>o</sub>) Table.**

<b>County and City</b>	<b>Jan</b>	<b>Feb</b>	<b>Mar</b>	<b>Apr</b>	<b>May</b>	<b>Jun</b>	<b>Jul</b>	<b>Aug</b>	<b>Sep</b>	<b>Oct</b>	<b>Nov</b>	<b>Dec</b>	<b>Annual ET<sub>o</sub></b>
<b>KINGS</b>													
Caruthers	1.6	2.5	4.0	5.7	7.8	8.7	9.3	8.4	6.3	4.4	2.4	1.6	62.7
Corcoran	1.6	2.2	3.7	5.1	6.8	7.8	8.7	7.8	5.7	4.0	2.1	1.6	57.1
Hanford	0.9	1.5	3.4	5.0	6.6	7.7	8.3	7.2	5.4	3.4	1.4	0.7	51.5
Kettleman	1.1	2.0	4.0	6.0	7.5	8.5	9.1	8.2	6.1	4.5	2.2	1.1	60.2
Lemoore	0.9	1.5	3.4	5.0	6.6	7.7	8.3	7.3	5.4	3.4	1.4	0.7	51.7
Stratford	0.9	1.9	3.9	6.1	7.8	8.6	8.8	7.7	5.9	4.1	2.1	1.0	58.7
<b>LAKE</b>													
Lakeport	1.1	1.3	2.6	3.5	5.1	6.0	7.3	6.1	4.7	2.9	1.2	0.9	42.8
Lower Lake	1.2	1.4	2.7	4.5	5.3	6.3	7.4	6.4	5.0	3.1	1.3	0.9	45.4
<b>LASSEN</b>													
Buntingville	1.0	1.7	3.5	4.9	6.2	7.3	8.4	7.5	5.4	3.4	1.5	0.9	51.8
Ravendale	0.6	1.1	2.3	4.1	5.6	6.7	7.9	7.3	4.7	2.8	1.2	0.5	44.9
Susanville	0.7	1.0	2.2	4.1	5.6	6.5	7.8	7.0	4.6	2.8	1.2	0.5	44.0
<b>LOS ANGELES</b>													
Burbank	2.1	2.8	3.7	4.7	5.1	6.0	6.6	6.7	5.4	4.0	2.6	2.0	51.7
Claremont	2.0	2.3	3.4	4.6	5.0	6.0	7.0	7.0	5.3	4.0	2.7	2.1	51.3
El Dorado	1.7	2.2	3.6	4.8	5.1	5.7	5.9	5.9	4.4	3.2	2.2	1.7	46.3
Glendale	2.0	2.2	3.3	3.8	4.7	4.8	5.7	5.6	4.3	3.3	2.2	1.8	43.7
Glendora	2.0	2.5	3.6	4.9	5.4	6.1	7.3	6.8	5.7	4.2	2.6	2.0	53.1
Gorman	1.6	2.2	3.4	4.6	5.5	7.4	7.7	7.1	5.9	3.6	2.4	1.1	52.4
Hollywood Hills	2.1	2.2	3.8	5.4	6.0	6.5	6.7	6.4	5.2	3.7	2.8	2.1	52.8
Lancaster	2.1	3.0	4.6	5.9	8.5	9.7	11.0	9.8	7.3	4.6	2.8	1.7	71.1
Long Beach	1.8	2.1	3.3	3.9	4.5	4.3	5.3	4.7	3.7	2.8	1.8	1.5	39.7
Los Angeles	2.2	2.7	3.7	4.7	5.5	5.8	6.2	5.9	5.0	3.9	2.6	1.9	50.1
Monrovia	2.2	2.3	3.8	4.3	5.5	5.9	6.9	6.4	5.1	3.2	2.5	2.0	50.2
Palmdale	2.0	2.6	4.6	6.2	7.3	8.9	9.8	9.0	6.5	4.7	2.7	2.1	66.2
Pasadena	2.1	2.7	3.7	4.7	5.1	6.0	7.1	6.7	5.6	4.2	2.6	2.0	52.3
Pearblossom	1.7	2.4	3.7	4.7	7.3	7.7	9.9	7.9	6.4	4.0	2.6	1.6	59.9
Pomona	1.7	2.0	3.4	4.5	5.0	5.8	6.5	6.4	4.7	3.5	2.3	1.7	47.5
Redondo Beach	2.2	2.4	3.3	3.8	4.5	4.7	5.4	4.8	4.4	2.8	2.4	2.0	42.6
San Fernando	2.0	2.7	3.5	4.6	5.5	5.9	7.3	6.7	5.3	3.9	2.6	2.0	52.0
Santa Clarita	2.8	2.8	4.1	5.6	6.0	6.8	7.6	7.8	5.8	5.2	3.7	3.2	61.5
Santa Monica	1.8	2.1	3.3	4.5	4.7	5.0	5.4	5.4	3.9	3.4	2.4	2.2	44.2
<b>MADERA</b>													
Chowchilla	1.0	1.4	3.2	4.7	6.6	7.8	8.5	7.3	5.3	3.4	1.4	0.7	51.4
Madera	0.9	1.4	3.2	4.8	6.6	7.8	8.5	7.3	5.3	3.4	1.4	0.7	51.5
Raymond	1.2	1.5	3.0	4.6	6.1	7.6	8.4	7.3	5.2	3.4	1.4	0.7	50.5
<b>MARIN</b>													
Black Point	1.1	1.7	3.0	4.2	5.2	6.2	6.6	5.8	4.3	2.8	1.3	0.9	43.0
Novato	1.3	1.5	2.4	3.5	4.4	6.0	5.9	5.4	4.4	2.8	1.4	0.7	39.8
Point San Pedro	1.1	1.7	3.0	4.2	5.2	6.2	6.6	5.8	4.3	2.8	1.3	0.9	43.0
San Rafael	1.2	1.3	2.4	3.3	4.0	4.8	4.8	4.9	4.3	2.7	1.3	0.7	35.8
<b>MARIPOSA</b>													
Coulterville	1.1	1.5	2.8	4.4	5.9	7.3	8.1	7.0	5.3	3.4	1.4	0.7	48.8
Mariposa	1.1	1.5	2.8	4.4	5.9	7.4	8.2	7.1	5.0	3.4	1.4	0.7	49.0
Yosemite Village	0.7	1.0	2.3	3.7	5.1	6.5	7.1	6.1	4.4	2.9	1.1	0.6	41.4
<b>MENDOCINO</b>													

## Appendix A. Reference Evapotranspiration (ET<sub>o</sub>) Table.

County and City	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Annual ET <sub>o</sub>
Fort Bragg	0.9	1.3	2.2	3.0	3.7	3.5	3.7	3.7	3.0	2.3	1.2	0.7	29.0
Hopland	1.1	1.3	2.6	3.4	5.0	5.9	6.5	5.7	4.5	2.8	1.3	0.7	40.9
Point Arena	1.0	1.3	2.3	3.0	3.7	3.9	3.7	3.7	3.0	2.3	1.2	0.7	29.6
Sanel Valley	1.0	1.6	3.0	4.6	6.0	7.0	8.0	7.0	5.2	3.4	1.4	0.9	49.1
Ukiah	1.0	1.3	2.6	3.3	5.0	5.8	6.7	5.9	4.5	2.8	1.3	0.7	40.9
<b>MERCED</b>													
Kesterson	0.9	1.7	3.4	5.5	7.3	8.2	8.6	7.4	5.5	3.8	1.8	0.9	55.1
Los Banos	1.0	1.5	3.2	4.7	6.1	7.4	8.2	7.0	5.3	3.4	1.4	0.7	50.0
Merced	1.0	1.5	3.2	4.7	6.6	7.9	8.5	7.2	5.3	3.4	1.4	0.7	51.5
<b>MODOC</b>													
Modoc/Alturas	0.9	1.4	2.8	3.7	5.1	6.2	7.5	6.6	4.6	2.8	1.2	0.7	43.2
<b>MONO</b>													
Bridgeport	0.7	0.9	2.2	3.8	5.5	6.6	7.4	6.7	4.7	2.7	1.2	0.5	43.0
<b>MONTEREY</b>													
Arroyo Seco	1.5	2.0	3.7	5.4	6.3	7.3	7.2	6.7	5.0	3.9	2.0	1.6	52.6
Castroville	1.4	1.7	3.0	4.2	4.6	4.8	4.0	3.8	3.0	2.6	1.6	1.4	36.2
Gonzales	1.3	1.7	3.4	4.7	5.4	6.3	6.3	5.9	4.4	3.4	1.9	1.3	45.7
Greenfield	1.8	2.2	3.4	4.8	5.6	6.3	6.5	6.2	4.8	3.7	2.4	1.8	49.5
King City	1.7	2.0	3.4	4.4	4.4	5.6	6.1	6.7	6.5	5.2	2.2	1.3	49.6
King City-Oasis Rd.	1.4	1.9	3.6	5.3	6.5	7.3	7.4	6.8	5.1	4.0	2.0	1.5	52.7
Long Valley	1.5	1.9	3.2	4.1	5.8	6.5	7.3	6.7	5.3	3.6	2.0	1.2	49.1
Monterey	1.7	1.8	2.7	3.5	4.0	4.1	4.3	4.2	3.5	2.8	1.9	1.5	36.0
Pajaro	1.8	2.2	3.7	4.8	5.3	5.7	5.6	5.3	4.3	3.4	2.4	1.8	46.1
Salinas	1.6	1.9	2.7	3.8	4.8	4.7	5.0	4.5	4.0	2.9	1.9	1.3	39.1
Salinas North	1.2	1.5	2.9	4.1	4.6	5.2	4.5	4.3	3.2	2.8	1.5	1.2	36.9
San Ardo	1.0	1.7	3.1	4.5	5.9	7.2	8.1	7.1	5.1	3.1	1.5	1.0	49.0
San Juan	1.8	2.1	3.4	4.6	5.3	5.7	5.5	4.9	3.8	3.2	2.2	1.9	44.2
Soledad	1.7	2.0	3.4	4.4	5.5	5.4	6.5	6.2	5.2	3.7	2.2	1.5	47.7
<b>NAPA</b>													
Angwin	1.8	1.9	3.2	4.7	5.8	7.3	8.1	7.1	5.5	4.5	2.9	2.1	54.9
Carneros	0.8	1.5	3.1	4.6	5.5	6.6	6.9	6.2	4.7	3.5	1.4	1.0	45.8
Oakville	1.0	1.5	2.9	4.7	5.8	6.9	7.2	6.4	4.9	3.5	1.6	1.2	47.7
St Helena	1.2	1.5	2.8	3.9	5.1	6.1	7.0	6.2	4.8	3.1	1.4	0.9	44.1
Yountville	1.3	1.7	2.8	3.9	5.1	6.0	7.1	6.1	4.8	3.1	1.5	0.9	44.3
<b>NEVADA</b>													
Grass Valley	1.1	1.5	2.6	4.0	5.7	7.1	7.9	7.1	5.3	3.2	1.5	0.9	48.0
Nevada City	1.1	1.5	2.6	3.9	5.8	6.9	7.9	7.0	5.3	3.2	1.4	0.9	47.4
<b>ORANGE</b>													
Irvine	2.2	2.5	3.7	4.7	5.2	5.9	6.3	6.2	4.6	3.7	2.6	2.3	49.6
Laguna Beach	2.2	2.7	3.4	3.8	4.6	4.6	4.9	4.9	4.4	3.4	2.4	2.0	43.2
Santa Ana	2.2	2.7	3.7	4.5	4.6	5.4	6.2	6.1	4.7	3.7	2.5	2.0	48.2
<b>PLACER</b>													
Auburn	1.2	1.7	2.8	4.4	6.1	7.4	8.3	7.3	5.4	3.4	1.6	1.0	50.6
Blue Canyon	0.7	1.1	2.1	3.4	4.8	6.0	7.2	6.1	4.6	2.9	0.9	0.6	40.5
Colfax	1.1	1.5	2.6	4.0	5.8	7.1	7.9	7.0	5.3	3.2	1.4	0.9	47.9
Roseville	1.1	1.7	3.1	4.7	6.2	7.7	8.5	7.3	5.6	3.7	1.7	1.0	52.2
Soda Springs	0.7	0.7	1.8	3.0	4.3	5.3	6.2	5.5	4.1	2.5	0.7	0.7	35.4
Tahoe City	0.7	0.7	1.7	3.0	4.3	5.4	6.1	5.6	4.1	2.4	0.8	0.6	35.5

**Appendix A. Reference Evapotranspiration (ET<sub>o</sub>) Table.**

<b>County and City</b>	<b>Jan</b>	<b>Feb</b>	<b>Mar</b>	<b>Apr</b>	<b>May</b>	<b>Jun</b>	<b>Jul</b>	<b>Aug</b>	<b>Sep</b>	<b>Oct</b>	<b>Nov</b>	<b>Dec</b>	<b>Annual ET<sub>o</sub></b>
Truckee	0.7	0.7	1.7	3.2	4.4	5.4	6.4	5.7	4.1	2.4	0.8	0.6	36.2
<b>PLUMAS</b>													
Portola	0.7	0.9	1.9	3.5	4.9	5.9	7.3	5.9	4.3	2.7	0.9	0.5	39.4
Quincy	0.7	0.9	2.2	3.5	4.9	5.9	7.3	5.9	4.4	2.8	1.2	0.5	40.2
<b>RIVERSIDE</b>													
Beaumont	2.0	2.3	3.4	4.4	6.1	7.1	7.6	7.9	6.0	3.9	2.6	1.7	55.0
Blythe	2.4	3.3	5.3	6.9	8.7	9.6	9.6	8.7	6.9	5.0	3.0	2.2	71.4
Cathedral City	1.6	2.2	3.7	5.1	6.8	7.8	8.7	7.8	5.7	4.0	2.1	1.6	57.1
Coachella	2.9	4.4	6.2	8.4	10.5	11.9	12.3	10.1	8.9	6.2	3.8	2.4	88.1
Desert Center	2.9	4.1	6.4	8.5	11.0	12.1	12.2	11.1	9.0	6.4	3.9	2.6	90.0
Elsinore	2.1	2.8	3.9	4.4	5.9	7.1	7.6	7.0	5.8	3.9	2.6	1.9	55.0
Indio	<b>3.1</b>	3.6	6.5	8.3	10.5	11.0	10.8	9.7	8.3	5.9	3.7	2.7	83.9
<b>RIVERSIDE</b>													
La Quinta	2.4	2.8	5.2	6.5	8.3	8.7	8.5	7.9	6.5	4.5	2.7	2.2	66.2
Mecca	2.6	3.3	5.7	7.2	8.6	9.0	8.8	8.2	6.8	5.0	3.2	2.4	70.8
Oasis	2.9	3.3	5.3	6.1	8.5	8.9	8.7	7.9	6.9	4.8	2.9	2.3	68.4
Palm Desert	2.5	3.4	5.3	6.9	8.7	9.6	9.6	8.7	6.9	5.0	3.0	2.2	71.6
Palm Springs	2.0	2.9	4.9	7.2	8.3	8.5	11.6	8.3	7.2	5.9	2.7	1.7	71.1
Rancho California	1.8	2.2	3.4	4.8	5.6	6.3	6.5	6.2	4.8	3.7	2.4	1.8	49.5
Rancho Mirage	2.4	3.3	5.3	6.9	8.7	9.6	9.6	8.7	6.9	5.0	3.0	2.2	71.4
Ripley	2.7	3.3	5.6	7.2	8.7	8.7	8.4	7.6	6.2	4.6	2.8	2.2	67.8
Salton Sea North	2.5	3.3	5.5	7.2	8.8	9.3	9.2	8.5	6.8	5.2	3.1	2.3	71.7
Temecula East II	2.3	2.4	4.1	4.9	6.4	7.0	7.8	7.4	5.7	4.1	2.6	2.2	56.7
Thermal	2.4	3.3	5.5	7.6	9.1	9.6	9.3	8.6	7.1	5.2	3.1	2.1	72.8
Riverside UC	2.5	2.9	4.2	5.3	5.9	6.6	7.2	6.9	5.4	4.1	2.9	2.6	56.4
Winchester	2.3	2.4	4.1	4.9	6.4	6.9	7.7	7.5	6.0	3.9	2.6	2.1	56.8
<b>SACRAMENTO</b>													
Fair Oaks	1.0	1.6	3.4	4.1	6.5	7.5	8.1	7.1	5.2	3.4	1.5	1.0	50.5
Sacramento	1.0	1.8	3.2	4.7	6.4	7.7	8.4	7.2	5.4	3.7	1.7	0.9	51.9
Twitchell Island	1.2	1.8	3.9	5.3	7.4	8.8	9.1	7.8	5.9	3.8	1.7	1.2	57.9
<b>SAN BENITO</b>													
Hollister	1.5	1.8	3.1	4.3	5.5	5.7	6.4	5.9	5.0	3.5	1.7	1.1	45.1
San Benito	1.2	1.6	3.1	4.6	5.6	6.4	6.9	6.5	4.8	3.7	1.7	1.2	47.2
San Juan Valley	1.4	1.8	3.4	4.5	6.0	6.7	7.1	6.4	5.0	3.5	1.8	1.4	49.1
<b>SAN BERNARDINO</b>													
Baker	2.7	3.9	6.1	8.3	10.4	11.8	12.2	11.0	8.9	6.1	3.3	2.1	86.6
Barstow NE	2.2	2.9	5.3	6.9	9.0	10.1	9.9	8.9	6.8	4.8	2.7	2.1	71.7
Big Bear Lake	1.8	2.6	4.6	6.0	7.0	7.6	8.1	7.4	5.4	4.1	2.4	1.8	58.6
Chino	2.1	2.9	3.9	4.5	5.7	6.5	7.3	7.1	5.9	4.2	2.6	2.0	54.6
Crestline	1.5	1.9	3.3	4.4	5.5	6.6	7.8	7.1	5.4	3.5	2.2	1.6	50.8
Lake Arrowhead	1.8	2.6	4.6	6.0	7.0	7.6	8.1	7.4	5.4	4.1	2.4	1.8	58.6
Lucerne Valley	2.2	2.9	5.1	6.5	9.1	11.0	11.4	9.9	7.4	5.0	3.0	1.8	75.3
Needles	3.2	4.2	6.6	8.9	11.0	12.4	12.8	11.0	8.9	6.6	4.0	2.7	92.1
Newberry Springs	2.1	2.9	5.3	8.4	9.8	10.9	11.1	9.9	7.6	5.2	3.1	2.0	78.2
San Bernardino	2.0	2.7	3.8	4.6	5.7	6.9	7.9	7.4	5.9	4.2	2.6	2.0	55.6
Twentynine Palms	2.6	3.6	5.9	7.9	10.1	11.2	11.2	10.3	8.6	5.9	3.4	2.2	82.9
Victorville	2.0	2.6	4.6	6.2	7.3	8.9	9.8	9.0	6.5	4.7	2.7	2.1	66.2

<b>SAN DIEGO</b>													
Chula Vista	2.2	2.7	3.4	3.8	4.9	4.7	5.5	4.9	4.5	3.4	2.4	2.0	44.2
Escondido SPV	2.4	2.6	3.9	4.7	5.9	6.5	7.1	6.7	5.3	3.9	2.8	2.3	54.2
Miramar	2.3	2.5	3.7	4.1	5.1	5.4	6.1	5.8	4.5	3.3	2.4	2.1	47.1
Oceanside	2.2	2.7	3.4	3.7	4.9	4.6	4.6	5.1	4.1	3.3	2.4	2.0	42.9
Otay Lake	2.3	2.7	3.9	4.6	5.6	5.9	6.2	6.1	4.8	3.7	2.6	2.2	50.4
Pine Valley	1.5	2.4	3.8	5.1	6.0	7.0	7.8	7.3	6.0	4.0	2.2	1.7	54.8
Ramona	2.1	2.1	3.4	4.6	5.2	6.3	6.7	6.8	5.3	4.1	2.8	2.1	51.6
San Diego	2.1	2.4	3.4	4.6	5.1	5.3	5.7	5.6	4.3	3.6	2.4	2.0	46.5
Santee	2.1	2.7	3.7	4.5	5.5	6.1	6.6	6.2	5.4	3.8	2.6	2.0	51.1
Torrey Pines	2.2	2.3	3.4	3.9	4.0	4.1	4.6	4.7	3.8	2.8	2.0	2.0	39.8
Warner Springs	1.6	2.7	3.7	4.7	5.7	7.6	8.3	7.7	6.3	4.0	2.5	1.3	56.0
<b>SAN FRANCISCO</b>													
San Francisco	1.5	1.3	2.4	3.0	3.7	4.6	4.9	4.8	4.1	2.8	1.3	0.7	35.1
<b>SAN JOAQUIN</b>													
Farmington	1.5	1.5	2.9	4.7	6.2	7.6	8.1	6.8	5.3	3.3	1.4	0.7	50.0
<b>SAN JOAQUIN</b>													
Lodi West	1.0	1.6	3.3	4.3	6.3	6.9	7.3	6.4	4.5	3.0	1.4	0.8	46.7
Manteca	0.9	1.7	3.4	5.0	6.5	7.5	8.0	7.1	5.2	3.3	1.6	0.9	51.2
Stockton	0.8	1.5	2.9	4.7	6.2	7.4	8.1	6.8	5.3	3.2	1.4	0.6	49.1
Tracy	1.0	1.5	2.9	4.5	6.1	7.3	7.9	6.7	5.3	3.2	1.3	0.7	48.5
<b>SAN LUIS OBISPO</b>													
Arroyo Grande	2.0	2.2	3.2	3.8	4.3	4.7	4.3	4.6	3.8	3.2	2.4	1.7	40.0
Atascadero	1.2	1.5	2.8	3.9	4.5	6.0	6.7	6.2	5.0	3.2	1.7	1.0	43.7
Morro Bay	2.0	2.2	3.1	3.5	4.3	4.5	4.6	4.6	3.8	3.5	2.1	1.7	39.9
Nipomo	2.2	2.5	3.8	5.1	5.7	6.2	6.4	6.1	4.9	4.1	2.9	2.3	52.1
Paso Robles	1.6	2.0	3.2	4.3	5.5	6.3	7.3	6.7	5.1	3.7	2.1	1.4	49.0
San Luis Obispo	2.0	2.2	3.2	4.1	4.9	5.3	4.6	5.5	4.4	3.5	2.4	1.7	43.8
San Miguel	1.6	2.0	3.2	4.3	5.0	6.4	7.4	6.8	5.1	3.7	2.1	1.4	49.0
San Simeon	2.0	2.0	2.9	3.5	4.2	4.4	4.6	4.3	3.5	3.1	2.0	1.7	38.1
<b>SAN MATEO</b>													
Hal Moon Bay	1.5	1.7	2.4	3.0	3.9	4.3	4.3	4.2	3.5	2.8	1.3	1.0	33.7
Redwood City	1.5	1.8	2.9	3.8	5.2	5.3	6.2	5.6	4.8	3.1	1.7	1.0	42.8
Woodside	1.8	2.2	3.4	4.8	5.6	6.3	6.5	6.2	4.8	3.7	2.4	1.8	49.5
<b>SANTA BARBARA</b>													
Betteravia	2.1	2.6	4.0	5.2	6.0	5.9	5.8	5.4	4.1	3.3	2.7	2.1	49.1
Carpenteria	2.0	2.4	3.2	3.9	4.8	5.2	5.5	5.7	4.5	3.4	2.4	2.0	44.9
Cuyama	2.1	2.4	3.8	5.4	6.9	7.9	8.5	7.7	5.9	4.5	2.6	2.0	59.7
Goleta	2.1	2.5	3.9	5.1	5.7	5.7	5.4	5.4	4.2	3.2	2.8	2.2	48.1
Goleta Foothills	2.3	2.6	3.7	5.4	5.3	5.6	5.5	5.7	4.5	3.9	2.8	2.3	49.6
Guadalupe	2.0	2.2	3.2	3.7	4.9	4.6	4.5	4.6	4.1	3.3	2.4	1.7	41.1
Lompoc	2.0	2.2	3.2	3.7	4.8	4.6	4.9	4.8	3.9	3.2	2.4	1.7	41.1
Los Alamos	1.8	2.0	3.2	4.1	4.9	5.3	5.7	5.5	4.4	3.7	2.4	1.6	44.6
Santa Barbara	2.0	2.5	3.2	3.8	4.6	5.1	5.5	4.5	3.4	2.4	1.8	1.8	40.6
Santa Maria	1.8	2.3	3.7	5.1	5.7	5.8	5.6	5.3	4.2	3.5	2.4	1.9	47.4
Santa Ynez	1.7	2.2	3.5	5.0	5.8	6.2	6.4	6.0	4.5	3.6	2.2	1.7	48.7
Sisquoc	2.1	2.5	3.8	4.1	6.1	6.3	6.4	5.8	4.7	3.4	2.3	1.8	49.2
Solvang	2.0	2.0	3.3	4.3	5.0	5.6	6.1	5.6	4.4	3.7	2.2	1.6	45.6

<b>SANTA CLARA</b>													
Gilroy	1.3	1.8	3.1	4.1	5.3	5.6	6.1	5.5	4.7	3.4	1.7	1.1	43.6
Los Gatos	1.5	1.8	2.8	3.9	5.0	5.6	6.2	5.5	4.7	3.2	1.7	1.1	42.9
Morgan Hill	1.5	1.8	3.4	4.2	6.3	7.0	7.1	6.0	5.1	3.7	1.9	1.4	49.5
Palo Alto	1.5	1.8	2.8	3.8	5.2	5.3	6.2	5.6	5.0	3.2	1.7	1.0	43.0
San Jose	1.5	1.8	3.1	4.1	5.5	5.8	6.5	5.9	5.2	3.3	1.8	1.0	45.3
<b>SANTA CRUZ</b>													
De Laveaga	1.4	1.9	3.3	4.7	4.9	5.3	5.0	4.8	3.6	3.0	1.6	1.3	40.8
Green Valley Rd	1.2	1.8	3.2	4.5	4.6	5.4	5.2	5.0	3.7	3.1	1.6	1.3	40.6
Santa Cruz	1.5	1.8	2.6	3.5	4.3	4.4	4.8	4.4	3.8	2.8	1.7	1.2	36.6
Watsonville	1.5	1.8	2.7	3.7	4.6	4.5	4.9	4.2	4.0	2.9	1.8	1.2	37.7
Webb	1.8	2.2	3.7	4.8	5.3	5.7	5.6	5.3	4.3	3.4	2.4	1.8	46.2
<b>SHASTA</b>													
Burney	0.7	1.0	2.1	3.5	4.9	5.9	7.4	6.4	4.4	2.9	0.9	0.6	40.9
Fall River Mills	0.6	1.0	2.1	3.7	5.0	6.1	7.8	6.7	4.6	2.8	0.9	0.5	41.8
Glenburn	0.6	1.0	2.1	3.7	5.0	6.3	7.8	6.7	4.7	2.8	0.9	0.6	42.1
McArthur	0.7	1.4	2.9	4.2	5.6	6.9	8.2	7.2	5.0	3.0	1.1	0.6	46.8
Redding	1.2	1.4	2.6	4.1	5.6	7.1	8.5	7.3	5.3	3.2	1.4	0.9	48.8
<b>SIERRA</b>													
Downieville	0.7	1.0	2.3	3.5	5.0	6.0	7.4	6.2	4.7	2.8	0.9	0.6	41.3
Sierraville	0.7	1.1	2.2	3.2	4.5	5.9	7.3	6.4	4.3	2.6	0.9	0.5	39.6
<b>SISKIYOU</b>													
Happy Camp	0.5	0.9	2.0	3.0	4.3	5.2	6.1	5.3	4.1	2.4	0.9	0.5	35.1
MacDoel	1.0	1.7	3.1	4.5	5.9	7.2	8.1	7.1	5.1	3.1	1.5	1.0	49.0
Mt Shasta	0.5	0.9	2.0	3.0	4.5	5.3	6.7	5.7	4.0	2.2	0.7	0.5	36.0
Tule lake FS	0.7	1.3	2.7	4.0	5.4	6.3	7.1	6.4	4.7	2.8	1.0	0.6	42.9
Weed	0.5	0.9	2.0	2.5	4.5	5.3	6.7	5.5	3.7	2.0	0.9	0.5	34.9
Yreka	0.6	0.9	2.1	3.0	4.9	5.8	7.3	6.5	4.3	2.5	0.9	0.5	39.2
<b>SOLANO</b>													
<u>Benicia</u>	<u>1.3</u>	<u>1.4</u>	<u>2.7</u>	<u>3.8</u>	<u>4.9</u>	<u>5.0</u>	<u>6.4</u>	<u>5.5</u>	<u>4.4</u>	<u>2.9</u>	<u>1.2</u>	<u>0.7</u>	<u>40.3</u>
Dixon	0.7	1.4	3.2	5.2	6.3	7.6	8.2	7.2	5.5	4.3	1.6	1.1	52.1
Fairfield	1.1	1.7	2.8	4.0	5.5	6.1	7.8	6.0	4.8	3.1	1.4	0.9	45.2
Hastings Tract	1.6	2.2	3.7	5.1	6.8	7.8	8.7	7.8	5.7	4.0	2.1	1.6	57.1
Putah Creek	1.0	1.6	3.2	4.9	6.1	7.3	7.9	7.0	5.3	3.8	1.8	1.2	51.0
Rio Vista	0.9	1.7	2.8	4.4	5.9	6.7	7.9	6.5	5.1	3.2	1.3	0.7	47.0
Suisun Valley	0.6	1.3	3.0	4.7	5.8	7.0	7.7	6.8	5.3	3.8	1.4	0.9	48.3
Winters	0.9	1.7	3.3	5.0	6.4	7.5	7.9	7.0	5.2	3.5	1.6	1.0	51.0
<b>SONOMA</b>													
Bennett Valley	1.1	1.7	3.2	4.1	5.5	6.5	6.6	5.7	4.5	3.1	1.5	0.9	44.4
Cloverdale	1.1	1.4	2.6	3.4	5.0	5.9	6.2	5.6	4.5	2.8	1.4	0.7	40.7
Fort Ross	1.2	1.4	2.2	3.0	3.7	4.5	4.2	4.3	3.4	2.4	1.2	0.5	31.9
Healdsburg	1.2	1.5	2.4	3.5	5.0	5.9	6.1	5.6	4.5	2.8	1.4	0.7	40.8
Lincoln	1.2	1.7	2.8	4.7	6.1	7.4	8.4	7.3	5.4	3.7	1.9	1.2	51.9
Petaluma	1.2	1.5	2.8	3.7	4.6	5.6	4.6	5.7	4.5	2.9	1.4	0.9	39.6
Santa Rosa	1.2	1.7	2.8	3.7	5.0	6.0	6.1	5.9	4.5	2.9	1.5	0.7	42.0
Valley of the Moon	1.0	1.6	3.0	4.5	5.6	6.6	7.1	6.3	4.7	3.3	1.5	1.0	46.1
Windsor	0.9	1.6	3.0	4.5	5.5	6.5	6.5	5.9	4.4	3.2	1.4	1.0	44.2
<b>STANISLAUS</b>													
Denair	1.0	1.9	3.6	4.7	7.0	7.9	8.0	6.1	5.3	3.4	1.5	1.0	51.4
La Grange	1.2	1.5	3.1	4.7	6.2	7.7	8.5	7.3	5.3	3.4	1.4	0.7	51.2
Modesto	0.9	1.4	3.2	4.7	6.4	7.7	8.1	6.8	5.0	3.4	1.4	0.7	49.7

Newman	1.0	1.5	3.2	4.6	6.2	7.4	8.1	6.7	5.0	3.4	1.4	0.7	49.3
Oakdale	1.2	1.5	3.2	4.7	6.2	7.7	8.1	7.1	5.1	3.4	1.4	0.7	50.3
Patterson	1.3	2.1	4.2	5.4	7.9	8.6	8.2	6.6	5.8	4.0	1.9	1.3	57.3
Turlock	0.9	1.5	3.2	4.7	6.5	7.7	8.2	7.0	5.1	3.4	1.4	0.7	50.2
<b>SUTTER</b>													
Nicolaus	0.9	1.6	3.2	4.9	6.3	7.5	8.0	6.9	5.2	3.4	1.5	0.9	50.2
Yuba City	1.3	2.1	2.8	4.4	5.7	7.2	7.1	6.1	4.7	3.2	1.2	0.9	46.7
<b>TEHAMA</b>													
Corning	1.2	1.8	2.9	4.5	6.1	7.3	8.1	7.2	5.3	3.7	1.7	1.1	50.7
Gerber	1.0	1.8	3.5	5.0	6.6	7.9	8.7	7.4	5.8	4.1	1.8	1.1	54.7
Gerber Dryland	0.9	1.6	3.2	4.7	6.7	8.4	9.0	7.9	6.0	4.2	2.0	1.0	55.5
Red Bluff	1.2	1.8	2.9	4.4	5.9	7.4	8.5	7.3	5.4	3.5	1.7	1.0	51.1
<b>TRINITY</b>													
Hay Fork	0.5	1.1	2.3	3.5	4.9	5.9	7.0	6.0	4.5	2.8	0.9	0.7	40.1
Weaverville	0.6	1.1	2.2	3.3	4.9	5.9	7.3	6.0	4.4	2.7	0.9	0.7	40.0
<b>TULARE</b>													
Alpaugh	0.9	1.7	3.4	4.8	6.6	7.7	8.2	7.3	5.4	3.4	1.4	0.7	51.6
Badger	1.0	1.3	2.7	4.1	6.0	7.3	7.7	7.0	4.8	3.3	1.4	0.7	47.3
Delano	1.1	1.9	4.0	4.9	7.2	7.9	8.1	7.3	5.4	3.2	1.5	1.2	53.6
Dinuba	1.1	1.5	3.2	4.7	6.2	7.7	8.5	7.3	5.3	3.4	1.4	0.7	51.2
Lindcove	0.9	1.6	3.0	4.8	6.5	7.6	8.1	7.2	5.2	3.4	1.6	0.9	50.6
Porterville	1.2	1.8	3.4	4.7	6.6	7.7	8.5	7.3	5.3	3.4	1.4	0.7	52.1
Visalia	0.9	1.7	3.3	5.1	6.8	7.7	7.9	6.9	4.9	3.2	1.5	0.8	50.7
<b>TUOLUMNE</b>													
Groveland	1.1	1.5	2.8	4.1	5.7	7.2	7.9	6.6	5.1	3.3	1.4	0.7	47.5
Sonora	1.1	1.5	2.8	4.1	5.8	7.2	7.9	6.7	5.1	3.2	1.4	0.7	47.6
<b>VENTURA</b>													
Camarillo	2.2	2.5	3.7	4.3	5.0	5.2	5.9	5.4	4.2	3.0	2.5	2.1	46.1
Oxnard	2.2	2.5	3.2	3.7	4.4	4.6	5.4	4.8	4.0	3.3	2.4	2.0	42.3
Piru	2.8	2.8	4.1	5.6	6.0	6.8	7.6	7.8	5.8	5.2	3.7	3.2	61.5
Port Hueneme	2.0	2.3	3.3	4.6	4.9	4.9	4.9	5.0	3.7	3.2	2.5	2.2	43.5
Thousand Oaks	2.2	2.6	3.4	4.5	5.4	5.9	6.7	6.4	5.4	3.9	2.6	2.0	51.0
Ventura	2.2	2.6	3.2	3.8	4.6	4.7	5.5	4.9	4.1	3.4	2.5	2.0	43.5
<b>YOLO</b>													
Bryte	0.9	1.7	3.3	5.0	6.4	7.5	7.9	7.0	5.2	3.5	1.6	1.0	51.0
Davis	1.0	1.9	3.3	5.0	6.4	7.6	8.2	7.1	5.4	4.0	1.8	1.0	52.5
Esparto	1.0	1.7	3.4	5.5	6.9	8.1	8.5	7.5	5.8	4.2	2.0	1.2	55.8
Winters	1.7	1.7	2.9	4.4	5.8	7.1	7.9	6.7	5.3	3.3	1.6	1.0	49.4
Woodland	1.0	1.8	3.2	4.7	6.1	7.7	8.2	7.2	5.4	3.7	1.7	1.0	51.6
Zamora	1.1	1.9	3.5	5.2	6.4	7.4	7.8	7.0	5.5	4.0	1.9	1.2	52.8
<b>YUBA</b>													
Browns Valley	1.0	1.7	3.1	4.7	6.1	7.5	8.5	7.6	5.7	4.1	2.0	1.1	52.9
Brownsville	1.1	1.4	2.6	4.0	5.7	6.8	7.9	6.8	5.3	3.4	1.5	0.9	47.4

\* The values in this table were derived from:

- 1) California Irrigation Management Information System (CIMIS);
- 2) Reference EvapoTranspiration Zones Map, UC Dept. of Land, Air & Water Resources and California Dept of Water Resources 1999; and
- 3) Reference Evapotranspiration for California, University of California, Department of Agriculture and Natural Resources (1987) Bulletin 1922,
- 4) Determining Daily Reference Evapotranspiration, Cooperative Extension UC Division of Agriculture and Natural Resources (1987), Publication Leaflet 21426



SECTION B. WATER BUDGET CALCULATIONS

**Section B1. Maximum Applied Water Allowance (MAWA)**

The project's Maximum Applied Water Allowance shall be calculated using ~~these~~ equations:

$MAWA = (ET_o) (0.62) [(0.57 \times LA) + (0.53 \times SLA)]$  for residential areas  
 $MAWA = (ET_o) (0.62) [(0.4 \times LA) + (0.6 \times SLA)]$  for non-residential areas

where:

- MAWA = Maximum Applied Water Allowance (gallons per year)
- ET<sub>o</sub> = Reference Evapotranspiration from Appendix A (inches per year)
- ~~0.5, 0.47~~ = ET Adjustment Factor (ETAF) for residential and non-residential areas, respectively
- LA = Landscaped Area includes Special Landscape Area (square feet)
- 0.62 = Conversion factor (to gallons per square foot per year)
- SLA = Portion of the landscape area identified as Special Landscape Area (square feet)
- ~~0.3, 0.5, 0.6~~ = the additional ET Adjustment Factors for Special Landscape Area in residential and non-residential areas, respectively (~~1.0-0.5=0.5~~), (~~1.0-0.4=0.6~~) (~~1.0-0.7=0.3~~)

**Maximum Applied Water Allowance = \_\_\_\_\_ gallons per year**

Show calculations.

**Effective Precipitation (Eppt)**

If considering Effective Precipitation, use 25% of annual precipitation. Use the following equation to calculate Maximum Applied Water Allowance:

$MAWA = (ET_o - Eppt) (0.62) [(0.57 \times LA) + (0.53 \times SLA)]$  for residential areas  
 $MAWA = (ET_o - Eppt) (0.62) [(0.4 \times LA) + (0.6 \times SLA)]$  for non-residential areas

**Maximum Applied Water Allowance = \_\_\_\_\_ gallons per year**

Show calculations.

**Section B2. Estimated Total Water Use (ETWU)**

The project's Estimated Total Water Use is calculated using the following formula:

$$ETWU = (ET_o)(0.62) \left( \frac{PF \times HA}{IE} + SLA \right)$$

where:

- ETWU = Estimated total water use per year (gallons per year)
- ET<sub>o</sub> = Reference Evapotranspiration (inches per year)
- PF = Plant Factor from WUCOLS (see Definitions)
- HA = Hydrozone Area [high, medium, and low water use areas] (square feet)
- SLA = Special Landscape Area (square feet)
- 0.62 = Conversion Factor (to gallons per square foot)
- IE = Irrigation Efficiency (minimum 0.8574 for residential areas and 0.92 for non-residential areas, averaged site-wide)

**Hydrozone Table for Calculating ETWU**

Please complete the hydrozone table(s). Use as many tables as necessary.

Hydrozone	Plant Water Use Type(s)	Plant Factor (PF)	Area (HA) (square feet)	PF x HA (square feet)
			Sum	
	SLA			

**Estimated Total Water Use = \_\_\_\_\_ gallons**

Show calculations.

## Appendix C – Sample Certificate of Completion.

### CERTIFICATE OF COMPLETION

This certificate is filled out by the project applicant upon completion of the landscape project.

#### PART 1. PROJECT INFORMATION SHEET

Date		
Project Name		
Name of Project Applicant	Telephone No.	
	Fax No.	
Title	Email Address	
Company	Street Address	
City	State	Zip Code

#### Project Address and Location:

Street Address		Parcel, tract or lot number, if available.
City		Latitude/Longitude (optional)
State	Zip Code	

#### Property Owner or his/her designee:

Name	Telephone No.	
	Fax No.	
Title	Email Address	
Company	Street Address	
City	State	Zip Code

#### Property Owner

"I/we certify that I/we have received copies of all the documents within the Landscape Documentation Package and the Certificate of Completion and that it is our responsibility to see that the project is maintained in accordance with the Landscape and Irrigation Maintenance Schedule."

\_\_\_\_\_

Property Owner Signature

Date

#### Please answer the questions below:

1. Date the Landscape Documentation Package was submitted to the local agency \_\_\_\_\_
2. Date the Landscape Documentation Package was approved by the local agency \_\_\_\_\_
3. Date that a copy of the Water Efficient Landscape Worksheet (including the Water Budget Calculation) was submitted to the local water purveyor \_\_\_\_\_

PART 2. CERTIFICATION OF INSTALLATION ACCORDING TO THE LANDSCAPE DOCUMENTATION PACKAGE

"I/we certify that based upon periodic site observations, the work has been substantially completed in accordance with the ordinance and that the landscape planting and irrigation installation conform with the criteria and specifications of the approved Landscape Documentation Package."

Signature*	Date	
Name (print)	Telephone No.	
	Fax No.	
Title	Email Address	
License No. or Certification No.		
Company	Street Address	
City	State	Zip Code

\*Signer of the landscape design plan, signer of the irrigation plan, or a licensed landscape contractor.

PART 3. IRRIGATION SCHEDULING

Attach parameters for setting the irrigation schedule on controller per ordinance Section 492.10.

PART 4. SCHEDULE OF LANDSCAPE AND IRRIGATION MAINTENANCE

Attach schedule of Landscape and Irrigation Maintenance per ordinance Section 492.11.

PART 5. LANDSCAPE IRRIGATION AUDIT REPORT

Attach Landscape Irrigation Audit Report per ordinance Section 492.12.

PART 6. SOIL MANAGEMENT REPORT

Attach soil analysis report, if not previously submitted with the Landscape Documentation Package per ordinance Section 492.65.

Attach documentation verifying implementation of recommendations from soil analysis report per ordinance Section 492.65.